

789. The method of claim 785, wherein heating a selected volume comprises heating with a natural distributed combustors.

790. The method of claim 785, further comprising controlling a pressure and a temperature within at least a majority of the selected volume of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

791. The method of claim 785, further comprising controlling the heating such that an average heating rate of the selected volume is less than about 1 °C per day during pyrolysis.

792. The method of claim 785, wherein a value for C_v is determined as an average heat capacity of two or more samples taken from the hydrocarbon containing formation.

793. The method of claim 785, wherein heating the selected volume comprises transferring heat substantially by conduction.

794. The method of claim 785, wherein heating the selected volume comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

795. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

796. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

797. The method of claim 785, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

798. The method of claim 785, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

799. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

800. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

801. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

802. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

803. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

804. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

5 805. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

10 806. The method of claim 785, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

15 807. The method of claim 785, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

20 808. The method of claim 785, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

809. The method of claim 785, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer

25 810. The method of claim 785, further comprising controlling a pressure within at least a majority of the selected volume of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

30 811. The method of claim 785, further comprising controlling formation conditions to produce a mixture from the formation comprising condensable hydrocarbons and H₂, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

812. ~~The method of claim 785, wherein the partial pressure of H₂ is measured when the mixture is at a production well.~~

5 813. The method of claim 785, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

10 814. The method of claim 785, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

15 815. The method of claim 785, further comprising:
providing hydrogen (H₂) to the heated volume to hydrogenate hydrocarbons within the volume; and
heating a portion of the volume with heat from hydrogenation.

20 816. The method of claim 785, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

25 817. The method of claim 785, further comprising increasing a permeability of a majority of the selected volume to greater than about 100 millidarcy.

30 818. The method of claim 785, further comprising substantially uniformly increasing a permeability of a majority of the selected volume.

819. The method of claim 785, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

820. The method of claim 785, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

821. The method of claim 785, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

822. The method of claim 785, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

823. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation to raise an average temperature within the selected section to, or above, a temperature that will pyrolyze hydrocarbons within the selected section;
controlling heat output from the one or more heat sources such that an average heating rate of the selected section rises by less than about 3 °C per day when the average temperature of the selected section is at, or above, the temperature that will pyrolyze hydrocarbons within the selected section; and
producing a mixture from the formation.

824. The method of claim 823, controlling heat output comprises:
raising the average temperature within the selected section to a first temperature that is at or above a minimum pyrolysis temperature of hydrocarbons within the formation;

limiting energy input into the one or more heat sources to inhibit increase in temperature of the selected section; and

increasing energy input into the formation to raise an average temperature of the selected section above the first temperature when production of formation fluid declines below a desired production rate.

825. The method of claim 823, controlling heat output comprises:

raising the average temperature within the selected section to a first temperature that is at or above a minimum pyrolysis temperature of hydrocarbons within the formation;

limiting energy input into the one or more heat sources to inhibit increase in temperature of the selected section; and

increasing energy input into the formation to raise an average temperature of the selected section above the first temperature when quality of formation fluid produced from the formation falls below a desired quality.

826. The method of claim 823, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section.

827. The method of claim 823, wherein the one or more heat sources comprise electrical heaters.

828. The method of claim 823, wherein the one or more heat sources comprise surface burners.

829. The method of claim 823, wherein the one or more heat sources comprise flameless distributed combustors.

830. The method of claim 823, wherein the one or more heat sources comprise natural distributed combustors.

831. The method of claim 823, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

832. The method of claim 823, wherein the heat is controlled that an average heating rate of the selected section is less than about 1.5 °C per day during pyrolysis.

833. The method of claim 823, wherein the heat is controlled that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

834. The method of claim 823, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density.

835. The method of claim 823, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

836. The method of claim 823, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

837. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

838. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

839. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, wherein the condensable hydrocarbons have an olefin content is less than about 2.5 % by weight of the condensable hydrocarbons, and wherein the olefin content is greater than about 0.1 % by weight of the condensable hydrocarbons.

840. The method of claim 823, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

841. The method of claim 823, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.10 and wherein the ratio of ethene to ethane is greater than about 0.001.

842. The method of claim 823, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.05 and wherein the ratio of ethene to ethane is greater than about 0.001.

843. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

844. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

845. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

846. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

847. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

848. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

849. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

850. The method of claim 823, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

851. The method of claim 823, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen,

wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

5 852. The method of claim 823, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

853. The method of claim 823, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

10 854. The method of claim 823, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

15 855. The method of claim 823, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H₂, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

20 856. The method of claim 823, wherein the partial pressure of H₂ is measured when the mixture is at a production well.

25 857. The method of claim 823, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

858. The method of claim 823, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

30 859. The method of claim 823, further comprising:

providing H₂ to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

5 860. The method of claim 823, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

10 861. The method of claim 823, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

15 862. The method of claim 823, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

20 863. The method of claim 823, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

25 864. The method of claim 823, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

30 865. The method of claim 823, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

866. The method of claim 823, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat

sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

867. A method of treating a hydrocarbon containing formation in situ, comprising:
5 providing heat from one or more heat sources to at least a portion of the formation; to heat a selected section of the formation to an average temperature above about 270 °C;

allowing the heat to transfer from the one or more heat sources to the selected section of the formation;

10 controlling the heat from the one or more heat sources such that an average heating rate of the selected section is less than about 3 °C per day during pyrolysis; and producing a mixture from the formation.

868. The method of claim 867, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources
15 pyrolyzes at least some hydrocarbons within the selected section of the formation.

869. The method of claim 867, wherein the one or more heat sources comprise electrical heaters.

870. The method of claim 867, further comprising supplying electricity to the electrical heaters substantially during non-peak hours.

871. The method of claim 867, wherein the one or more heat sources comprise surface
25 burners.

872. The method of claim 867, wherein the one or more heat sources comprise flameless distributed combustors.

873. The method of claim 867, wherein the one or more heat sources comprise natural
30 distributed combustors.

874. The method of claim 867, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

875. The method of claim 867, wherein the heat is further controlled such that an average heating rate of the selected section is less than about 3 °C/day until production of condensable hydrocarbons substantially ceases.

876. The method of claim 867, wherein the heat is further controlled that an average heating rate of the selected section is less than about 1.5 °C per day during pyrolysis.

877. The method of claim 867, wherein the heat is further controlled such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

878. The method of claim 867, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} ,

wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density.

879. The method of claim 867, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

880. The method of claim 867, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

881. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

882. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

883. The method of claim 867, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

884. The method of claim 867, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

885. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

886. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

887. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

888. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

889. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

890. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

891. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

892. The method of claim 867, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

893. The method of claim 867, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

894. ~~The method of claim 867, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.~~

895. The method of claim 867, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

896. The method of claim 867, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

897. The method of claim 867, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H₂, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

898. The method of claim 897, wherein the partial pressure of H₂ is measured when the mixture is at a production well.

899. The method of claim 867, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

900. The method of claim 867, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

901. The method of claim 867, further comprising:
providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

902. The method of claim 867, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

903. The method of claim 867, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

904. The method of claim 867, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

905. The method of claim 867, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

906. The method of claim 867, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

907. The method of claim 867, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

908. The method of claim 867, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

909. A method of treating a hydrocarbon containing formation in situ, comprising:

providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

5 producing a mixture from the formation through at least one production well;
monitoring a temperature at or in the production well; and
controlling heat input to raise the monitored temperature at a rate of less than about 3 °C per day.

10 910. The method of claim 909, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

15 911. The method of claim 909, wherein the one or more heat sources comprise electrical heaters.

912. The method of claim 909, wherein the one or more heat sources comprise surface burners.

20 913. The method of claim 909, wherein the one or more heat sources comprise flameless distributed combustors.

914. The method of claim 909, wherein the one or more heat sources comprise natural distributed combustors.

25 915. The method of claim 909, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

30

916. The method of claim 909, wherein the heat is controlled that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

917. The method of claim 909, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density.

918. The method of claim 909, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

919. The method of claim 909, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

920. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

921. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

922. The method of claim 909, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-

condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

923. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

924. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

925. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

926. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

927. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

928. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

929. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

930. The method of claim 909, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

931. The method of claim 909, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

932. The method of claim 909, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

933. The method of claim 909, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

934. The method of claim 909, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

935. The method of claim 909, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

936. The method of claim 935, wherein the partial pressure of H_2 is measured when the mixture is at a production well.

937. The method of claim 909, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

05641437-2E41850
1042401

938. The method of claim 909, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

5 939. The method of claim 909, further comprising:

providing H₂ to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

10 940. The method of claim 909, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

15 941. The method of claim 909, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

942. The method of claim 909, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

20 943. The method of claim 909, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

25 944. The method of claim 909, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

30 945. The method of claim 909, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat

sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

946. The method of claim 909, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

947. A method of treating a hydrocarbon containing formation in situ, comprising:
heating a portion of the formation to a temperature sufficient to support oxidation of hydrocarbons within the portion, wherein the portion is located substantially adjacent to a wellbore;

flowing an oxidant through a conduit positioned within the wellbore to a heat source zone within the portion, wherein the heat source zone supports an oxidation reaction between hydrocarbons and the oxidant;

reacting a portion of the oxidant with hydrocarbons to generate heat; and
transferring generated heat substantially by conduction to a pyrolysis zone of the formation to pyrolyze at least a portion of the hydrocarbons within the pyrolysis zone.

948. The method of claim 947, wherein heating the portion of the formation comprises raising a temperature of the portion above about 400 °C.

949. The method of claim 947, wherein the conduit comprises critical flow orifices, the method further comprising flowing the oxidant through the critical flow orifices to the heat source zone.

950. The method of claim 947, further comprising removing reaction products from the heat source zone through the wellbore.

951. The method of claim 947, further comprising removing excess oxidant from the heat source zone to inhibit transport of the oxidant to the pyrolysis zone.

952. The method of claim 947, further comprising transporting the oxidant from the conduit to the heat source zone substantially by diffusion.

953. The method of claim 947, further comprising heating the conduit with reaction products being removed through the wellbore.

954. The method of claim 947, wherein the oxidant comprises hydrogen peroxide.

955. The method of claim 947, wherein the oxidant comprises air.

956. The method of claim 947, wherein the oxidant comprises a fluid substantially free of nitrogen.

957. The method of claim 947, further comprising limiting an amount of oxidant to maintain a temperature of the heat source zone less than about 1200 °C.

958. The method of claim 947, wherein heating the portion of the formation comprises electrically heating the formation.

959. The method of claim 947, wherein heating the portion of the formation comprises heating the portion using exhaust gases from a surface burner.

960. The method of claim 947, wherein heating the portion of the formation comprises heating the portion with a flameless distributed combustor.

961. The method of claim 947, further comprising controlling a pressure and a temperature within at least a majority of the pyrolysis zone, wherein the pressure is

controlled as a function of temperature, or the temperature is controlled as a function of pressure.

962. The method of claim 947, further comprising controlling the heat such that an average heating rate of the pyrolysis zone is less than about 1 °C per day during pyrolysis.

963. The method of claim 947, wherein heating the portion comprises heating the pyrolysis zone such that a thermal conductivity of at least a portion of the pyrolysis zone is greater than about 0.5 W/(m °C).

964. The method of claim 947, further comprising controlling a pressure within at least a majority of the pyrolysis zone of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

965. The method of claim 947, further comprising:
providing hydrogen (H₂) to the pyrolysis zone to hydrogenate hydrocarbons within the pyrolysis zone; and
heating a portion of the pyrolysis zone with heat from hydrogenation.

966. The method of claim 947, wherein transferring generated heat comprises increasing a permeability of a majority of the pyrolysis zone to greater than about 100 millidarcy.

967. The method of claim 947, wherein transferring generated heat comprises substantially uniformly increasing a permeability of a majority of the pyrolysis zone.

968. The method of claim 947, wherein the heating is controlled to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

969. The method of claim 947, wherein the wellbore is located along strike to reduce pressure differentials along a heated length of the wellbore.

970. The method of claim 947, wherein the wellbore is located along strike to increase uniformity of heating along a heated length of the wellbore.

5 971. The method of claim 947, wherein the wellbore is located along strike to increase control of heating along a heated length of the wellbore.

972. A method of treating a hydrocarbon containing formation in situ, comprising:
heating a portion of the formation to a temperature sufficient to support reaction
of hydrocarbons within the portion of the formation with an oxidant;
10 flowing the oxidant into a conduit, and wherein the conduit is connected such that the oxidant can flow from the conduit to the hydrocarbons;
allowing the oxidant and the hydrocarbons to react to produce heat in a heat source zone;
15 allowing heat to transfer from the heat source zone to a pyrolysis zone in the formation to pyrolyze at least a portion of the hydrocarbons within the pyrolysis zone;
and
removing reaction products such that the reaction products are inhibited from flowing from the heat source zone to the pyrolysis zone.

20 973. The method of claim 972, wherein heating the portion of the formation comprises raising the temperature of the portion above about 400 °C.

25 974. The method of claim 972, wherein heating the portion of the formation comprises electrically heating the formation.

975. The method of claim 972, wherein heating the portion of the formation comprises heating the portion using exhaust gases from a surface burner.

976. The method of claim 972, wherein the conduit comprises critical flow orifices, the method further comprising flowing the oxidant through the critical flow orifices to the heat source zone.

977. The method of claim 972, wherein the conduit is located within a wellbore, wherein removing reaction products comprises removing reaction products from the heat source zone through the wellbore.

978. The method of claim 972, further comprising removing excess oxidant from the heat source zone to inhibit transport of the oxidant to the pyrolysis zone.

979. The method of claim 972, further comprising transporting the oxidant from the conduit to the heat source zone substantially by diffusion.

980. The method of claim 972, wherein the conduit is located within a wellbore, the method further comprising heating the conduit with reaction products being removed through the wellbore to raise a temperature of the oxidant passing through the conduit.

981. The method of claim 972, wherein the oxidant comprises hydrogen peroxide.

982. The method of claim 972, wherein the oxidant comprises air.

983. The method of claim 972, wherein the oxidant comprises a fluid substantially free of nitrogen.

984. The method of claim 972, further comprising limiting an amount of oxidant to maintain a temperature of the heat source zone less than about 1200 °C.

985. The method of claim 972, further comprising limiting an amount of oxidant to maintain a temperature of the heat source zone at a temperature that inhibits production of oxides of nitrogen.

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000

986. The method of claim 972, wherein heating a portion of the formation to a temperature sufficient to support oxidation of hydrocarbons within the portion further comprises heating with a flameless distributed combustor.

987. The method of claim 972, further comprising controlling a pressure and a temperature within at least a majority of the pyrolysis zone of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

988. The method of claim 972, further comprising controlling the heat such that an average heating rate of the pyrolysis zone is less than about 1 °C per day during pyrolysis.

989. The method of claim 972, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

990. The method of claim 972, wherein allowing heat to transfer comprises heating the pyrolysis zone such that a thermal conductivity of at least a portion of the pyrolysis zone is greater than about 0.5 W/(m °C).

991. The method of claim 972, further comprising controlling a pressure within at least a majority of the pyrolysis zone, wherein the controlled pressure is at least about 2.0 bar absolute.

992. The method of claim 972, further comprising:
providing hydrogen (H₂) to the pyrolysis zone to hydrogenate hydrocarbons within the pyrolysis zone; and
heating a portion of the pyrolysis zone with heat from hydrogenation.

993. The method of claim 972, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the pyrolysis zone to greater than about 100 millidarcy.

5 994. The method of claim 972, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the pyrolysis zone.

995. The method of claim 972, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

10 996. An in situ method for heating a hydrocarbon containing formation, comprising:
heating a portion of the formation to a temperature sufficient to support reaction
of hydrocarbons within the portion of the formation with an oxidizing fluid, wherein the
15 portion is located substantially adjacent to an opening in the formation;
providing the oxidizing fluid to a heat source zone in the formation;
allowing the oxidizing gas to react with at least a portion of the hydrocarbons at
the heat source zone to generate heat in the heat source zone; and
transferring the generated heat substantially by conduction from the heat source
20 zone to a pyrolysis zone in the formation.

997. The method of claim 996, further comprising transporting the oxidizing fluid through the heat source zone by diffusion.

25 998. The method of claim 996, further comprising directing at least a portion of the oxidizing fluid into the opening through orifices of a conduit disposed in the opening.

999. The method of claim 996, further comprising controlling a flow of the oxidizing fluid with critical flow orifices of a conduit disposed in the opening such that a rate of
30 oxidation is controlled.

1000. The method of claim 996, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit.

5 1001. The method of claim 996, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and transferring substantial heat from the oxidation product in the conduit to the oxidizing fluid in the conduit.

10 1002. The method of claim 996, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

15 1003. The method of claim 996, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and controlling a pressure between the oxidizing fluid and the oxidation product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

20 1004. The method of claim 996, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the outer conduit.

25 1005. The method of claim 996, wherein the heat source zone extends radially from the opening a width of less than approximately 0.15 m.

30 1006. The method of claim 996, wherein heating the portion comprises applying electrical current to an electric heater disposed within the opening.

1007. The method of claim 996, wherein the pyrolysis zone is substantially adjacent to the heat source zone.

1008. The method of claim 996, further comprising controlling a pressure and a temperature within at least a majority of the pyrolysis zone of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1009. The method of claim 996, further comprising controlling the heat such that an average heating rate of the pyrolysis zone is less than about 1 °C per day during pyrolysis.

1010. The method of claim 996, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1011. The method of claim 996, wherein allowing heat to transfer comprises heating the portion such that a thermal conductivity of at least a portion of the pyrolysis zone is greater than about 0.5 W/(m °C).

1012. The method of claim 996, further comprising controlling a pressure within at least a majority of the pyrolysis zone, wherein the controlled pressure is at least about 2.0 bar absolute.

1013. The method of claim 996, further comprising:
providing hydrogen (H₂) to the pyrolysis zone to hydrogenate hydrocarbons within the pyrolysis zone; and
heating a portion of the pyrolysis zone with heat from hydrogenation.

1014. The method of claim 996, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the pyrolysis zone to greater than about 100 millidarcy.

1015. ~~The method of claim 996, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the pyrolysis zone.~~

1016. The method of claim 996, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1017. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation;
producing a mixture from the formation; and
maintaining an average temperature within the selected section above a minimum pyrolysis temperature and below a vaporization temperature of hydrocarbons having carbon numbers greater than 25 to inhibit production of a substantial amount of hydrocarbons having carbon numbers greater than 25 in the mixture.

1018. The method of claim 1017, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1019. The method of claim 1017, wherein maintaining the average temperature within the selected section comprises maintaining the temperature within a pyrolysis temperature range.

1020. The method of claim 1017, wherein the one or more heat sources comprise electrical heaters.

1021. The method of claim 1017, wherein the one or more heat sources comprise surface burners.

1022. The method of claim 1017, wherein the one or more heat sources comprise flameless distributed combustors.

1023. The method of claim 1017, wherein the one or more heat sources comprise natural distributed combustors.

1024. The method of claim 1017, wherein the minimum pyrolysis temperature is greater than about 270 °C.

1025. The method of claim 1017, wherein the vaporization temperature is less than approximately 450 °C at atmospheric pressure.

1026. The method of claim 1017, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1027. The method of claim 1017, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1028. The method of claim 1017, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon-containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} ,
wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the
formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10
°C/day.

1029. The method of claim 1017, wherein allowing the heat to transfer comprises
transferring heat substantially by conduction.

1030. The method of claim 1017, wherein providing heat from the one or more heat
sources comprises heating the selected formation such that a thermal conductivity of at
least a portion of the selected section is greater than about 0.5 W/(m °C).

1031. The method of claim 1017, wherein the produced mixture comprises condensable
hydrocarbons having an API gravity of at least about 25°.

1032. The method of claim 1017, wherein the produced mixture comprises condensable
hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the
condensable hydrocarbons are olefins.

1033. The method of claim 1017, wherein the produced mixture comprises non-
condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight
of the non-condensable hydrocarbons are olefins.

1034. The method of claim 1017, wherein the produced mixture comprises non-
condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-
condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to
ethane is greater than about 0.001.

1035. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

5 1036. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

10 1037. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

15 1038. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

20 1039. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

25 1040. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1041. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

0984-437-0424-01

1042. The method of claim 1017, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

5 1043. The method of claim 1017, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

10 1044. The method of claim 1017, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

15 1045. The method of claim 1017, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

20 1046. The method of claim 1017, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1047. The method of claim 1017, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

25 1048. The method of claim 1047, wherein the partial pressure of H_2 is measured when the mixture is at a production well.

1049. The method of claim 1017, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

30 1050. The method of claim 1017, further comprising:

providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

5 1051. The method of claim 1017, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1052. The method of claim 1017, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1053. The method of claim 1017, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1054. The method of claim 1017, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

20 1055. The method of claim 1017, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

25 1056. The method of claim 1017, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

30 1057. The method of claim 1017, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat

sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1058. A method of treating a hydrocarbon containing formation in situ, comprising:

5 providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

10 controlling a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than 25; and

producing a mixture from the formation.

1059. The method of claim 1058, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1060. The method of claim 1058, wherein the one or more heat sources comprise electrical heaters.

1061. The method of claim 1058, wherein the one or more heat sources comprise surface burners.

1062. The method of claim 1058, wherein the one or more heat sources comprise flameless distributed combustors.

1063. The method of claim 1058, wherein the one or more heat sources comprise natural distributed combustors.

1064. The method of claim 1058, further comprising controlling a temperature within at least a majority of the selected section of the formation, wherein the pressure is

09941437 042401

~~controlled as a function of temperature, or the temperature is controlled as a function of pressure.~~

1065. The method of claim 1064, wherein controlling the temperature comprises maintaining a temperature within the selected section within a pyrolysis temperature range.

1066. The method of claim 1058, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1067. The method of claim 1058, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than Pwr , wherein Pwr is calculated by the equation:

$$Pwr = h * V * C_v * \rho_B$$

wherein Pwr is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1068. The method of claim 1058, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1069. The method of claim 1058, wherein providing heat from the one or more heat sources comprises heating the selected formation such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1070. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1071. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1072. The method of claim 1058, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

1073. The method of claim 1058, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

1074. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1075. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1076. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1077. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable

~~hydrocarbons comprise oxygen-containing compounds, and wherein the oxygen-containing compounds comprise phenols.~~

1078. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1079. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1080. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1081. The method of claim 1058, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1082. The method of claim 1058, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1083. The method of claim 1058, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1084. The method of claim 1058, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1085. The method of claim 1058, further comprising controlling the pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1086. The method of claim 1058, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1087. The method of claim 1086, wherein the partial pressure of H_2 is measured when the mixture is at a production well.

1088. The method of claim 1058, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

1089. The method of claim 1058, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1090. The method of claim 1058, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1091. The method of claim 1058, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1092. The method of claim 1058, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1093. The method of claim 1058, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1094. The method of claim 1058, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1095. The method of claim 1058, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1096. The method of claim 1058, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1097. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and

producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1098. The method of claim 1097, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat

~~sources pyrolyzes at least some hydrocarbons within the selected section of the formation.~~

1099. The method of claim 1097, wherein the one or more heat sources comprise electrical heaters.

1100. The method of claim 1097, wherein the one or more heat sources comprise surface burners.

1101. The method of claim 1097, wherein the one or more heat sources comprise flameless distributed combustors.

1102. The method of claim 1097, wherein the one or more heat sources comprise natural distributed combustors.

1103. The method of claim 1097, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1104. The method of claim 1097, wherein controlling the temperature comprises maintaining the temperature within the selected section within a pyrolysis temperature range.

1105. The method of claim 1097, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1106. The method of claim 1097, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1107. The method of claim 1097, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1108. The method of claim 1097, wherein providing heat from the one or more heat sources comprises heating the selected formation such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1109. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1110. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1111. The method of claim 1097, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

1112. The method of claim 1097, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-

condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

1113. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1114. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1115. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1116. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1117. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1118. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1119. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1120. The method of claim 1097, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1121. The method of claim 1097, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1122. The method of claim 1097, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1123. The method of claim 1097, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1124. The method of claim 1097, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1125. The method of claim 1097, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H₂, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

1126. The method of claim 1125, wherein the partial pressure of H₂ is measured when the mixture is at a production well.

1127. The method of claim 1097, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1128. The method of claim 1097, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

5 1129. The method of claim 1097, further comprising:

providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

10 1130. The method of claim 1097, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

15 1131. The method of claim 1097, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

20 1132. The method of claim 1097, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

25 1133. The method of claim 1097, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1134. The method of claim 1097, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

30 1135. The method of claim 1097, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat

sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1136. The method of claim 1097, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1137. A method of treating a hydrocarbon containing formation in situ, comprising:
heating a section of the formation to a pyrolysis temperature from at least a first heat source, a second heat source and a third heat source, and wherein the first heat source, the second heat source and the third heat source are located along a perimeter of the section;

controlling heat input to the first heat source, the second heat source and the third heat source to limit a heating rate of the section to a rate configured to produce a mixture from the formation with an olefin content of less than about 15% by weight of condensable fluids (on a dry basis) within the produced mixture; and

producing the mixture from the formation through a production well.

1138. The method of claim 1137, wherein superposition of heat from the first heat source, second heat source, and third heat source pyrolyzes a portion of the hydrocarbons within the formation to fluids

1139. The method of claim 1137, wherein the pyrolysis temperature is between about 270 °C and about 400 °C.

1140. The method of claim 1137, wherein the first heat source is operated for less than about twenty four hours a day.

1141. The method of claim 1137, wherein the first heat source comprises an electrical heater.

1142. The method of claim 1137, wherein the first heat source comprises a surface burner.

1143. The method of claim 1137, wherein the first heat source comprises a flameless distributed combustor.

1144. The method of claim 1137, wherein the first heat source, second heat source and third heat source are positioned substantially at apexes of an equilateral triangle.

1145. The method of claim 1137, wherein the production well is located substantially at a geometrical center of the first heat source, second heat source, and third heat source.

1146. The method of claim 1137, further comprising a fourth heat source, fifth heat source, and sixth heat source located along the perimeter of the section.

1147. The method of claim 1146, wherein the heat sources are located substantially at apexes of a regular hexagon.

1148. The method of claim 1147, wherein the production well is located substantially at a center of the hexagon.

1149. The method of claim 1137, further comprising controlling a pressure and a temperature within at least a majority of the section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1150. The method of claim 1137, wherein controlling the temperature comprises maintaining the temperature within the selected section within a pyrolysis temperature range.

1151. The method of claim 1137, further comprising controlling the heat such that an average heating rate of the section is less than about 3 °C per day during pyrolysis.

1152. The method of claim 1137, further comprising controlling the heat such that an average heating rate of the section is less than about 1 °C per day during pyrolysis.

1153. The method of claim 1137, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1154. The method of claim 1137, wherein heating the section of the formation comprises transferring heat substantially by conduction.

1155. The method of claim 1137, wherein providing heat from the one or more heat sources comprises heating the section such that a thermal conductivity of at least a portion of the section is greater than about 0.5 W/(m °C).

1156. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1157. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1158. The method of claim 1137, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

1159. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1160. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1161. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1162. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1163. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1164. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1165. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1166. The method of claim 1137, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1167. The method of claim 1137, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1168. The method of claim 1137, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1169. The method of claim 1137, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1170. The method of claim 1137, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1171. The method of claim 1137, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H₂, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

1172. The method of claim 1171, wherein the partial pressure of H₂ is measured when the mixture is at a production well.

1173. The method of claim 1137, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1174. The method of claim 1137, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

1175. The method of claim 1137, further comprising:
providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1176. The method of claim 1137, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1177. The method of claim 1137, heating the section comprises increasing a permeability of a majority of the section to greater than about 100 millidarcy.

1178. The method of claim 1137, wherein heating the section comprises substantially uniformly increasing a permeability of a majority of the section.

1179. The method of claim 1137, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1180. The method of claim 1137, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1181. The method of claim 1137, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1182. The method of claim 1137, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1183. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and

producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1184. The method of claim 1183, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat

1184. The method of claim 1183, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat

sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1185. The method of claim 1183, wherein the one or more heat sources comprise electrical heaters.

1186. The method of claim 1183, wherein the one or more heat sources comprise surface burners.

1187. The method of claim 1183, wherein the one or more heat sources comprise flameless distributed combustors.

1188. The method of claim 1183, wherein the one or more heat sources comprise natural distributed combustors.

1189. The method of claim 1183, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1190. The method of claim 1189, wherein controlling the temperature comprises maintaining the temperature within the selected section within a pyrolysis temperature range.

1191. The method of claim 1183, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1192. The method of claim 1183, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day

1193. The method of claim 1183, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1194. The method of claim 1183, wherein providing heat from the one or more heat sources comprises heating the selected formation such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1195. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1196. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1197. The method of claim 1183, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

1198. The method of claim 1183, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-

condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

1199. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1200. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1201. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1202. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1203. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1204. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1205. The method of claim 1183, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1206. The method of claim 1183, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1207. The method of claim 1183, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1208. The method of claim 1183, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1209. The method of claim 1183, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1210. The method of claim 1183, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1211. The method of claim 1211, wherein the partial pressure of H_2 is measured when the mixture is at a production well.

1212. The method of claim 1183, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1213. The method of claim 1183, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

1214. The method of claim 1183, further comprising:

providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

1215. The method of claim 1183, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1216. The method of claim 1183, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1217. The method of claim 1183, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1218. The method of claim 1183, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1219. The method of claim 1183, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1220. The method of claim 1183, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1221. The method of claim 1183, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat

sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

5 1222. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the
formation;

allowing the heat to transfer from the one or more heat sources to a selected
section of the formation; and

10 producing a mixture from the formation, wherein the produced mixture comprises
condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated
on an atomic basis, of the condensable hydrocarbons is oxygen.

1223. The method of claim 1222, wherein the one or more heat sources comprise at
15 least two heat sources, and wherein superposition of heat from at least the two heat
sources pyrolyzes at least some hydrocarbons within the selected section of the
formation.

20 1224. The method of claim 1222, wherein the one or more heat sources comprise
electrical heaters.

1225. The method of claim 1222, wherein the one or more heat sources comprise
surface burners.

25 1226. The method of claim 1222, wherein the one or more heat sources comprise
flameless distributed combustors.

30 1227. The method of claim 1222, wherein the one or more heat sources comprise natural
distributed combustors.

1228. The method of claim 1222, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1229. The method of claim 1228, wherein controlling the temperature comprises maintaining the temperature within the selected section within a pyrolysis temperature range.

1230. The method of claim 1222, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1231. The method of claim 1222, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1232. The method of claim 1222, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1233. The method of claim 1222, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1234. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1235. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1236. The method of claim 1222, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

1237. The method of claim 1222, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

1238. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1239. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1240. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1241. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1242. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1243. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1244. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1245. The method of claim 1222, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1246. The method of claim 1222, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1247. The method of claim 1222, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1248. The method of claim 1222, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1249. The method of claim 1222, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1250. The method of claim 1222, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1251. The method of claim 1250, wherein the partial pressure of H_2 is measured when the mixture is at a production well.

1252. The method of claim 1222, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1253. The method of claim 1222, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

1254. The method of claim 1222, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1255. The method of claim 1222, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

09041437-042401

1256. The method of claim 1222, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

5 1257. The method of claim 1222, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1258. The method of claim 1222, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1259. The method of claim 1222, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1260. The method of claim 1222, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1261. The method of claim 1222, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1262. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

30 ~~allowing the heat to transfer from the one or more heat sources to a selected~~
section of the formation; and

producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

5 1263. The method of claim 1262, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

10 1264. The method of claim 1262, wherein the one or more heat sources comprise electrical heaters.

1265. The method of claim 1262, wherein the one or more heat sources comprise surface burners.

15 1266. The method of claim 1262, wherein the one or more heat sources comprise flameless distributed combustors.

20 1267. The method of claim 1262, wherein the one or more heat sources comprise natural distributed combustors.

25 1268. The method of claim 1262, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

30 1269. The method of claim 1268, wherein controlling the temperature comprises maintaining the temperature within the selected section within a pyrolysis temperature range.

1270. The method of claim 1262, further comprising controlling the heat into such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

5 1271. The method of claim 1262, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

10 wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

15 wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1272. The method of claim 1262, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

20 1273. The method of claim 1262, wherein providing heat from the one or more heat sources comprises heating the selected formation such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

25 1274. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

30 1275. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1276. The method of claim 1262, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

5 1277. The method of claim 1262, wherein the produced mixture comprises non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons is less than about 0.15, and wherein the ratio of ethene to ethane is greater than about 0.001.

10 1278. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

15 1279. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

20 1280. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

25 1281. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

30 1282. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1283. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.
- 5 1284. The method of claim 1262, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.
- 10 1285. The method of claim 1262, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.
- 15 1286. The method of claim 1262, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.
1287. The method of claim 1262, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.
- 20 1288. The method of claim 1262, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.
- 25 1289. The method of claim 1262, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H₂, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.
- 30 1290. The method of claim 1289, wherein the partial pressure of H₂ is measured when the mixture is at a production well.

1291. The method of claim 1262, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

5 1292. The method of claim 1262, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

1293. The method of claim 1262, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons
10 within the section; and
heating a portion of the section with heat from hydrogenation.

1294. The method of claim 1262, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.
15

1295. The method of claim 1262, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.
20

1296. The method of claim 1262, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1297. The method of claim 1262, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.
25

1298. The method of claim 1262, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.
30

1299. The method of claim 1262, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

5

1300. The method of claim 1262, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

10

1301. A method of treating a hydrocarbon containing formation in situ, comprising:
raising a temperature of a first section of the formation with one or more heat sources to a first pyrolysis temperature;

15

heating the first section to an upper pyrolysis temperature, wherein heat is supplied to the first section at a rate configured to inhibit olefin production;

producing a first mixture from the formation, wherein the first mixture comprises condensable hydrocarbons and H_2 ;

20

creating a second mixture from the first mixture, wherein the second mixture comprises a higher concentration of H_2 than the first mixture;

raising a temperature of a second section of the formation with one or more heat sources to a second pyrolysis temperature;

25

providing a portion of the second mixture to the second section;

heating the second section to an upper pyrolysis temperature, wherein heat is supplied to the second section at a rate configured to inhibit olefin production; and

producing a third mixture from the second section.

1302. The method of claim 1301, wherein creating the second mixture comprises removing condensable hydrocarbons from the first mixture.

30

09841437 042401

1303. The method of claim 1301, wherein creating the second mixture comprises removing water from the first mixture.
1304. The method of claim 1301, wherein creating the second mixture comprises removing carbon dioxide from the first mixture.
1305. The method of claim 1301, wherein the first pyrolysis temperature is greater than about 270 °C.
1306. The method of claim 1301, wherein the second pyrolysis temperature is greater than about 270 °C.
1307. The method of claim 1301, wherein the upper pyrolysis temperature is about 500 °C.
1308. The method of claim 1301, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the first or second selected section of the formation.
1309. The method of claim 1301, wherein the one or more heat sources comprise electrical heaters.
1310. The method of claim 1301, wherein the one or more heat sources comprise surface burners.
1311. The method of claim 1301, wherein the one or more heat sources comprise flameless distributed combustors.
1312. The method of claim 1301, wherein the one or more heat sources comprise natural distributed combustors.

5

1313. The method of claim 1301, further comprising controlling a pressure and a temperature within at least a majority of the first section and the second section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

10

1314. The method of claim 1301, further comprising controlling the heat to the first and second sections such that an average heating rate of the first and second sections is less than about 1 °C per day during pyrolysis.

15

1315. The method of claim 1301, wherein heating the first and the second sections comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

20

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

25

1316. The method of claim 1301, wherein heating the first and second sections comprises transferring heat substantially by conduction.

30

1317. The method of claim 1301, wherein heating the first and second sections comprises heating the first and second sections such that a thermal conductivity of at least a portion of the first and second sections is greater than about 0.5 W/(m °C).

1318. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1319. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1320. The method of claim 1301, wherein the first or third mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1321. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1322. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1323. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1324. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1325. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1326. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1327. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1328. The method of claim 1301, wherein the first or third mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1329. The method of claim 1301, wherein the first or third mixture comprises a non-condensable component, and wherein the non-condensable component comprises hydrogen, and wherein the hydrogen is greater than about 10 % by volume of the non-condensable component and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1330. The method of claim 1301, wherein the first or third mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1331. The method of claim 1301, wherein the first or third mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1332. The method of claim 1301, further comprising controlling a pressure within at least a majority of the first or second sections of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1333. The method of claim 1301, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1334. The method of claim 1333, wherein the partial pressure of H_2 within a mixture is measured when the mixture is at a production well.

1335. The method of claim 1301, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1336. The method of claim 1301, further comprising:
providing hydrogen (H_2) to the first or second section to hydrogenate hydrocarbons within the first or second section; and
heating a portion of the first or second section with heat from hydrogenation.

1337. The method of claim 1301, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1338. The method of claim 1301, further comprising increasing a permeability of a majority of the first or second section to greater than about 100 millidarcy.

1339. The method of claim 1301, further comprising substantially uniformly increasing a permeability of a majority of the first or second section.

1340. The method of claim 1301, wherein the heating is controlled to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1341. The method of claim 1301, wherein producing the first or third mixture comprises producing the first or third mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

5 1342. The method of claim 1301, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

10 1343. The method of claim 1301, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

15 1344. A method of treating a hydrocarbon containing formation in situ, comprising:
 providing heat from one or more heat sources to at least a portion of the formation;
 allowing the heat to transfer from the one or more heat sources to a selected
 20 section of the formation;
 producing a mixture from the formation; and
 hydrogenating a portion of the produced mixture with H₂ produced from the formation.

25 1345. The method of claim 1344, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

30 1346. The method of claim 1344, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1347. The method of claim 1344, wherein the one or more heat sources comprise electrical heaters.

5 1348. The method of claim 1344, wherein the one or more heat sources comprise surface burners.

1349. The method of claim 1344, wherein the one or more heat sources comprise flameless distributed combustors.

10 1350. The method of claim 1344, wherein the one or more heat sources comprise natural distributed combustors.

1351. The method of claim 1344, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1352. The method of claim 1344, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1353. The method of claim 1344, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

25 heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than Pwr , wherein Pwr is calculated by the equation:

$$Pwr = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

5 1354. The method of claim 1344, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1355. The method of claim 1344, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least
10 a portion of the selected section is greater than about 0.5 W/(m °C).

1356. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

15 1357. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

20 1358. The method of claim 1344, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

25 1359. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

30 1360. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1361. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.
- 5 1362. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.
- 10 1363. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.
1364. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.
- 15 1365. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.
- 20 1366. The method of claim 1344, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.
- 25 1367. The method of claim 1344, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-
- 30 condensable component.

1368. The method of claim 1344, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1369. The method of claim 1344, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1370. The method of claim 1344, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1371. The method of claim 1344, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

1372. The method of claim 1344, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

1373. The method of claim 1344, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1374. The method of claim 1344, further comprising:
providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1375. The method of claim 1344, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1376. The method of claim 1344, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1377. The method of claim 1344, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1378. The method of claim 1344, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1379. The method of claim 1344, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1380. The method of claim 1344, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1381. A method of treating a hydrocarbon containing formation in situ, comprising:
heating a first section of the formation;
producing H₂ from the first section of formation;
heating a second section of the formation; and
recirculating a portion of the H₂ from the first section into the second section of the formation to provide a reducing environment within the second section of the formation.

058414304401

1382. The method of claim 1381, wherein heating the first section or heating the second section comprises heating with an electrical heater.

1383. The method of claim 1381, wherein heating the first section or heating the second section comprises heating with a surface burner.

1384. The method of claim 1381, wherein heating the first section or heating the second section comprises heating with a flameless distributed combustor.

1385. The method of claim 1381, wherein heating the first section or heating the second section comprises heating with a natural distributed combustor.

1386. The method of claim 1381, further comprising controlling a pressure and a temperature within at least a majority of the first or second section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1387. The method of claim 1381, further comprising controlling the heat such that an average heating rate of the first or second section is less than about 1 °C per day during pyrolysis.

1388. The method of claim 1381, wherein heating the first section or heating the second section further comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein Pwr is the heating energy/day, h is an average heating rate of the formation, ρ_b is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1389. The method of claim 1381, wherein heating the first section or heating the second section comprises transferring heat substantially by conduction.

1390. The method of claim 1381, wherein heating the first section or heating the second section comprises heating the formation such that a thermal conductivity of at least a portion of the first or second section is greater than about 0.5 W/(m °C).

1391. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1392. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1393. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1394. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1395. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1396. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1397. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1398. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1399. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1400. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1401. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

5

1402. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

10

1403. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

15

1404. The method of claim 1381, further comprising producing a mixture from the second section, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

20

1405. The method of claim 1381, further comprising controlling a pressure within at least a majority of the first or second section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

25

1406. The method of claim 1381, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

30

1407. The method of claim 1406, wherein the partial pressure of H_2 within a mixture is measured when the mixture is at a production well.

1408. The method of claim 1381, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

5 1409. The method of claim 1381, further comprising:
providing hydrogen (H_2) to the second section to hydrogenate hydrocarbons within the section; and
heating a portion of the second section with heat from hydrogenation.

10 1410. The method of claim 1381, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

15 1411. The method of claim 1381, wherein heating the first section or heating the second section comprises increasing a permeability of a majority of the first or second section, respectively, to greater than about 100 millidarcy.

20 1412. The method of claim 1381, wherein heating the first section or heating the second section comprises substantially uniformly increasing a permeability of a majority of the first or second section, respectively.

25 1413. The method of claim 1381, further comprises controlling the heating of the first section or controlling the heat of the second section to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

30 1414. The method of claim 1381, further comprising producing a mixture from the formation in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1415. ~~The method of claim 1381, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.~~

1416. The method of claim 1381, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1417. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

producing a mixture from the formation; and

controlling formation conditions such that the mixture produced from the formation comprises condensable hydrocarbons including H_2 , wherein the partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1418. The method of claim 1417, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1419. The method of claim 1417, wherein ~~controlling formation conditions comprises maintaining a temperature within the selected section within a pyrolysis temperature range.~~

0904-1437-042401

1420. The method of claim 1417, wherein the one or more heat sources comprise electrical heaters.

1421. The method of claim 1417, wherein the one or more heat sources comprise surface burners.

1422. The method of claim 1417, wherein the one or more heat sources comprise flameless distributed combustors.

1423. The method of claim 1417, wherein the one or more heat sources comprise natural distributed combustors.

1424. The method of claim 1417, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1425. The method of claim 1417, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1426. The method of claim 1417, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_b is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

5 1427. The method of claim 1417, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

10 1428. The method of claim 1417, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1429. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

15 1430. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

20 1431. The method of claim 1417, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

25 1432. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1433. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

30

1434. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1435. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1436. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1437. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1438. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1439. The method of claim 1417, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1440. The method of claim 1417, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1441. The method of claim 1417, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1442. The method of claim 1417, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1443. The method of claim 1417, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1444. The method of claim 1417, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1445. The method of claim 1417, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

1446. The method of claim 1417, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1447. The method of claim 1417, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1448. The method of claim 1417, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1449. The method of claim 1417, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1450. The method of claim 1417, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1451. The method of claim 1417, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1452. The method of claim 1417, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1453. The method of claim 1417, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1454. The method of claim 1417, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1455. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

maintaining a pressure of the selected section above atmospheric pressure to increase a partial pressure of H_2 , as compared to the partial pressure of H_2 at atmospheric pressure, in at least a majority of the selected section; and

producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25° .

1456. The method of claim 1455, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1457. The method of claim 1455, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1458. The method of claim 1455, wherein the one or more heat sources comprise electrical heaters.

1459. The method of claim 1455, wherein the one or more heat sources comprise surface burners.

1460. The method of claim 1455, wherein the one or more heat sources comprise flameless distributed combustors.

1461. The method of claim 1455, wherein the one or more heat sources comprise natural distributed combustors.

1462. The method of claim 1455, further comprising controlling the pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1463. The method of claim 1455, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1464. The method of claim 1455, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1465. The method of claim 1455, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1466. The method of claim 1455, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1467. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1468. The method of claim 1455, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1469. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1470. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1471. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1472. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1473. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1474. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1475. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1476. The method of claim 1455, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1477. The method of claim 1455, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1478. The method of claim 1455, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1479. The method of claim 1455, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1480. The method of claim 1455, further comprising controlling the pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1481. The method of claim 1455, further comprising increasing the pressure of the selected section, to an upper limit of about 21 bar absolute, to increase an amount of non-condensable hydrocarbons produced from the formation.

1482. The method of claim 1455, further comprising decreasing pressure of the selected section, to a lower limit of about atmospheric pressure, to increase an amount of condensable hydrocarbons produced from the formation.

1483. The method of claim 1455, wherein the partial pressure comprises a partial pressure based on properties measured at a production well.

1484. The method of claim 1455, further comprising altering the pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1485. The method of claim 1455, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1486. The method of claim 1455, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1487. The method of claim 1455, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1488. The method of claim 1455, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1489. The method of claim 1455, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1490. The method of claim 1455, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1491. The method of claim 1455, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1492. The method of claim 1455, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1493. The method of claim 1455, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1494. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

providing H_2 to the formation to produce a reducing environment in at least some of the formation;

producing a mixture from the formation.

1495. The method of claim 1494, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1496. The method of claim 1494, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1497. The method of claim 1494, further comprising separating a portion of hydrogen within the mixture and recirculating the portion into the formation.

1498. The method of claim 1494, wherein the one or more heat sources comprise electrical heaters.

1499. The method of claim 1494, wherein the one or more heat sources comprise surface burners.

1500. The method of claim 1494, wherein the one or more heat sources comprise flameless distributed combustors.

1501. The method of claim 1494, wherein the one or more heat sources comprise natural distributed combustors.

1502. The method of claim 1494, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1503. The method of claim 1494, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1504. The method of claim 1494, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

5 1505. The method of claim 1494, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

10 1506. The method of claim 1494, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1507. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

15 1508. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

20 1509. The method of claim 1494, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

25 1510. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

30 1511. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1512. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1513. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1514. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1515. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1516. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1517. The method of claim 1494, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1518. The method of claim 1494, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1519. The method of claim 1494, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1520. The method of claim 1494, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1521. The method of claim 1494, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1522. The method of claim 1494, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

1523. The method of claim 1494, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

1524. The method of claim 1494, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1525. The method of claim 1494, wherein providing hydrogen (H₂) to the formation further comprises:

hydrogenating hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1526. The method of claim 1494, further comprising:

producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1527. ~~The method of claim 1494, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.~~

5 1528. The method of claim 1494, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

10 1529. The method of claim 1494, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

15 1530. The method of claim 1494, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

20 1531. The method of claim 1494, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

25 1532. The method of claim 1494, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

30 1533. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation.

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

providing H₂ to the selected section to hydrogenate hydrocarbons within the selected section and to heat a portion of the section with heat from the hydrogenation; and

controlling heating of the selected section by controlling amounts of H₂ provided to the selected section.

1534. The method of claim 1533, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1535. The method of claim 1533, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1536. The method of claim 1533, wherein the one or more heat sources comprise electrical heaters.

1537. The method of claim 1533, wherein the one or more heat sources comprise surface burners.

1538. The method of claim 1533, wherein the one or more heat sources comprise flameless distributed combustors.

1539. The method of claim 1533, wherein the one or more heat sources comprise natural distributed combustors.

1540. The method of claim 1533, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1541. The method of claim 1533, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

5 1542. The method of claim 1533, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

10 wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

15 wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1543. The method of claim 1533, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

20 1544. The method of claim 1533, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

25 1545. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

30 1546. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1547. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1548. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1549. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1550. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1551. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1552. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1553. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1554. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1555. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1556. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1557. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1558. The method of claim 1533, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1559. The method of claim 1533, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1560. The method of claim 1533, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

1561. The method of claim 1560, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

1562. The method of claim 1533, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1563. The method of claim 1533, further comprising controlling formation conditions by recirculating a portion of hydrogen from a produced mixture into the formation.

1564. The method of claim 1533, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1565. The method of claim 1533, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1566. The method of claim 1533, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

09841437-042401
1567. The method of claim 1533, wherein the heating is controlled of claim 1533, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

5 1568. The method of claim 1533, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

10 1569. The method of claim 1533, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

15 1570. An in situ method for producing H₂ from a hydrocarbon containing formation, comprising:

providing heat from one or more heat sources to at least a portion of the formation;

20 allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and

producing a mixture from the formation, wherein a H₂ partial pressure within the mixture is greater than about 0.5 bar.

25 1571. The method of claim 1570, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

30 1572. The method of claim 1570, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1573. The method of claim 1570, wherein the one or more heat sources comprise electrical heaters.

1574. The method of claim 1570, wherein the one or more heat sources comprise surface burners.

1575. The method of claim 1570, wherein the one or more heat sources comprise flameless distributed combustors.

1576. The method of claim 1570, wherein the one or more heat sources comprise natural distributed combustors.

1577. The method of claim 1570, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1578. The method of claim 1570, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1579. The method of claim 1570, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{hr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

5 1580. The method of claim 1570, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1581. The method of claim 1570, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least
10 a portion of the selected section is greater than about 0.5 W/(m °C).

1582. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

15 1583. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1584. The method of claim 1570, wherein the produced mixture comprises non-
20 condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1585. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic
25 basis, of the condensable hydrocarbons is nitrogen.

1586. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic
30 basis, of the condensable hydrocarbons is oxygen.

1587. The method of claim 1570, ~~wherein the produced mixture~~ comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1588. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1589. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1590. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1591. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1592. The method of claim 1570, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1593. The method of claim 1570, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is ~~greater than about 10 % by volume of the non-condensable component~~, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1594. The method of claim 1570, wherein the produced mixture comprises ammonia and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1595. The method of claim 1570, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1596. The method of claim 1570, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1597. The method of claim 1570, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1598. The method of claim 1570, further comprising recirculating a portion of the hydrogen within the mixture into the formation.

1599. The method of claim 1570, further comprising condensing a hydrocarbon component from the produced mixture and hydrogenating the condensed hydrocarbons with a portion of the hydrogen.

1600. The method of claim 1570, further comprising:
providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1601. The method of claim 1570, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1602. The method of claim 1570, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1603. The method of claim 1570, further comprising controlling the heat to yield greater than about 60% by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1604. The method of claim 1570, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1605. The method of claim 1570, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1606. The method of claim 1570, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1607. The method of claim 1570, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1608. A method of treating a hydrocarbon containing formation in situ, comprising:
 providing heat from one or more heat sources to at least a portion of the formation;
 allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

wherein the selected section has been selected for heating using an atomic hydrogen weight percentage of at least a portion of hydrocarbons in the selected section, and wherein at least the portion of the hydrocarbons in the selected section comprises an atomic hydrogen weight percentage, when measured on a dry, ash-free basis, of greater than about 4.0 %; and
5 producing a mixture from the formation.

1609. The method of claim 1608, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the
10 formation.

1610. The method of claim 1608, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1611. The method of claim 1608, wherein the one or more heat sources comprise electrical heaters.

1612. The method of claim 1608, wherein the one or more heat sources comprise surface burners.
20

1613. The method of claim 1608, wherein the one or more heat sources comprise flameless distributed combustors.

1614. The method of claim 1608, wherein the one or more heat sources comprise natural distributed combustors.
25

1615. The method of claim 1608, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.
30

1616. The method of claim 1608, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1617. The method of claim 1608, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation, and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1618. The method of claim 1608, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1619. The method of claim 1608, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1620. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1621. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

5

1622. The method of claim 1608, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1623. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

10

1624. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

15

1625. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

20

1626. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

25

1627. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

30

1628. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1629. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

5 1630. The method of claim 1608, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

10 1631. The method of claim 1608, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

15 1632. The method of claim 1608, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

20 1633. The method of claim 1608, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

25 1634. The method of claim 1608, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

30 1635. The method of claim 1608, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

1636. The method of claim 1635, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

1637. The method of claim 1608, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1638. The method of claim 1608, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1639. The method of claim 1608, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1640. The method of claim 1608, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a
portion of the produced hydrogen.

1641. The method of claim 1608, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1642. The method of claim 1608, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1643. The method of claim 1608, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1644. The method of claim 1608, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1645. The method of claim 1608, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1646. The method of claim 1608, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1647. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation;
wherein at least some hydrocarbons within the selected section have an initial atomic hydrogen weight percentage of greater than about 4.0 %; and
producing a mixture from the formation.

1648. The method of claim 1647, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1649. The method of claim 1647, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1650. The method of claim 1647, wherein the one or more heat sources comprise electrical heaters.

1651. The method of claim 1647, wherein the one or more heat sources comprise surface burners.

5 1652. The method of claim 1647, wherein the one or more heat sources comprise flameless distributed combustors.

1653. The method of claim 1647, wherein the one or more heat sources comprise natural distributed combustors.

10 1654. The method of claim 1647, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

15 1655. The method of claim 1647, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

20 1656. The method of claim 1647, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

25 wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

30 wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1657. The method of claim 1647, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1658. The method of claim 1647, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1659. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1660. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1661. The method of claim 1647, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1662. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1663. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1664. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1665. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

5

1666. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

10

1667. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

15

1668. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

20

1669. The method of claim 1647, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

25

1670. The method of claim 1647, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

30

1671. The method of claim 1647, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1672. The method of claim 1647, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1673. The method of claim 1647, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1674. The method of claim 1647, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1675. The method of claim 1674, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1676. The method of claim 1647, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1677. The method of claim 1647, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1678. The method of claim 1647, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1679. The method of claim 1647, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1680. The method of claim 1647, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

5 1681. The method of claim 1647, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

10 1682. The method of claim 1647, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

15 1683. The method of claim 1647, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

20 1684. The method of claim 1647, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

25 1685. The method of claim 1647, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

30 1686. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

wherein the selected section has been selected for heating using vitrinite reflectance of at least some hydrocarbons in the selected section, and wherein at least a portion of the hydrocarbons in the selected section comprises a vitrinite reflectance of greater than about 0.3 %;

5 wherein at least a portion of the hydrocarbons in the selected section comprises a vitrinite reflectance of less than about 4.5 %; and
producing a mixture from the formation.

10 1687. The method of claim 1686, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

15 1688. The method of claim 1686, further comprising maintaining a temperature within the selected section within a pyrolysis temperature.

20 1689. The method of claim 1686, wherein the vitrinite reflectance of at least the portion of hydrocarbons within the selected section is between about 0.47 % and about 1.5 % such that a majority of the produced mixture comprises condensable hydrocarbons.

25 1690. The method of claim 1686, wherein the vitrinite reflectance of at least the portion of hydrocarbons within the selected section is between about 1.4 % and about 4.2 % such that a majority of the produced mixture comprises non-condensable hydrocarbons.

1691. The method of claim 1686, wherein the one or more heat sources comprise electrical heaters.

30 1692. The method of claim 1686, wherein the one or more heat sources comprise surface burners.

1693. The method of claim 1686, wherein the one or more heat sources comprise flameless distributed combustors.

1694. The method of claim 1686, wherein the one or more heat sources comprise natural distributed combustors.

1695. The method of claim 1686, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1696. The method of claim 1686, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1697. The method of claim 1686, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1698. The method of claim 1686, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1699. The method of claim 1686, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

5 1700. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

10 1701. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

15 1702. The method of claim 1686, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

20 1703. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

25 1704. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

30 1705. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1706. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1707. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1708. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1709. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1710. The method of claim 1686, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1711. The method of claim 1686, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

1712. The method of claim 1686, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1713. The method of claim 1686, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

~~1714. The method of claim 1686, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.~~

5 1715. The method of claim 1686, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

10 1716. The method of claim 1715, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

15 1717. The method of claim 1686, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1718. The method of claim 1686, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

20 1719. The method of claim 1686, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

25 1720. The method of claim 1686, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

30 1721. The method of claim 1686, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

09841437-042401

1722. The method of claim 1686, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

5 1723. The method of claim 1686, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

10 1724. The method of claim 1686, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

15 1725. The method of claim 1686, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

20 1726. The method of claim 1686, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

25 1727. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

30 wherein the selected section has been selected for heating using a total organic matter weight percentage of at least a portion of the selected section, and wherein at least

the portion of the selected section comprises a total organic matter weight percentage of at least about 5.0 %; and

producing a mixture from the formation.

5 1728. The method of claim 1727, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

10 1729. The method of claim 1727, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1730. The method of claim 1727, wherein the one or more heat sources comprise electrical heaters.

15 1731. The method of claim 1727, wherein the one or more heat sources comprise surface burners.

20 1732. The method of claim 1727, wherein the one or more heat sources comprise flameless distributed combustors.

1733. The method of claim 1727, wherein the one or more heat sources comprise natural distributed combustors.

25 1734. The method of claim 1727, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

09841437-04240

1735. The method of claim 1727, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

5 1736. The method of claim 1727, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

10 wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

15 wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1737. The method of claim 1727, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

20 1738. The method of claim 1727, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

25 1739. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1740. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the
30 condensable hydrocarbons are olefins.

1741. The method of claim 1727, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

5 1742. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

10 1743. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

15 1744. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

20 1745. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

25 1746. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1747. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1748. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

5 1749. The method of claim 1727, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

10 1750. The method of claim 1727, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

15 1751. The method of claim 1727, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1752. The method of claim 1727, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

20 1753. The method of claim 1727, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

25 1754. The method of claim 1727, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

30 1755. The method of claim 1754, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1756. The method of claim 1727, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

5 1757. The method of claim 1727, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

10 1758. The method of claim 1727, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

15 1759. The method of claim 1727, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

20 1760. The method of claim 1727, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1761. The method of claim 1727, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

25 1762. The method of claim 1727, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

30 1763. The method of claim 1727, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1764. The method of claim 1727, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1765. The method of claim 1727, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1766. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

wherein at least some hydrocarbons within the selected section have an initial total organic matter weight percentage of at least about 5.0%; and

producing a mixture from the formation.

1767. The method of claim 1766, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1768. The method of claim 1766, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1769. The method of claim 1766, wherein the one or more heat sources comprise electrical heaters.

1770. The method of claim 1766, wherein the one or more heat sources comprise surface burners.

5 1771. The method of claim 1766, wherein the one or more heat sources comprise flameless distributed combustors.

1772. The method of claim 1766, wherein the one or more heat sources comprise natural distributed combustors.

10 1773. The method of claim 1766, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

15 1774. The method of claim 1766, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

20 1775. The method of claim 1766, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

25 heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than Pwr , wherein Pwr is calculated by the equation:

$$Pwr = h * V * C_v * \rho_B$$

30 wherein Pwr is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1776. The method of claim 1766, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

5 1777. The method of claim 1766, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

10 1778. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

15 1779. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

20 1780. The method of claim 1766, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

25 1781. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

30 1782. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1783. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

00041437 042401

1784. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

5

1785. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

10

1786. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

15

1787. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

20

1788. The method of claim 1766, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

25

1789. The method of claim 1766, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

30

1790. The method of claim 1766, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1791. The method of claim 1766, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1792. The method of claim 1766, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1793. The method of claim 1766, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1794. The method of claim 1793, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1795. The method of claim 1766, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1796. The method of claim 1766, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1797. The method of claim 1766, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1798. The method of claim 1766, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

~~1799.~~ The method of claim 1766, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1800. The method of claim 1766, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1801 The method of claim 1766, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1802. The method of claim 1766, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1803. The method of claim 1766, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1804. The method of claim 1766, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1805. / A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the
formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

wherein the selected section has been selected for heating using an atomic oxygen weight percentage of at least a portion of hydrocarbons in the selected section, and wherein at least a portion of the hydrocarbons in the selected section comprises an atomic oxygen weight percentage of less than about 15% when measured on a dry, ash free basis; and

producing a mixture from the formation.

1806. The method of claim 1805, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1807. The method of claim 1805, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1808. The method of claim 1805, wherein the one or more heat sources comprise electrical heaters.

1809. The method of claim 1805, wherein the one or more heat sources comprise surface burners.

1810. The method of claim 1805, wherein the one or more heat sources comprise flameless distributed combustors.

1811. The method of claim 1805, wherein the one or more heat sources comprise natural distributed combustors.

1812. The method of claim 1805, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1813. The method of claim 1805, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1814. The method of claim 1805, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1815. The method of claim 1805, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1816. The method of claim 1805, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1817. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1818. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

1819. The method of claim 1805, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

1820. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

1821. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1822. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1823. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1824. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1825. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1826. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

5 1827. The method of claim 1805, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

10 1828. The method of claim 1805, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

15 1829. The method of claim 1805, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

20 1830. The method of claim 1805, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

25 1831. The method of claim 1805, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1832. The method of claim 1805, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

30 1833. The method of claim 1832, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1834. The method of claim 1805, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

5 1835. The method of claim 1805, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1836. The method of claim 1805, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons
10 within the section; and
heating a portion of the section with heat from hydrogenation.

1837. The method of claim 1805, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
15 hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1838. The method of claim 1805, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100
20 millidarcy.

1839. The method of claim 1805, wherein allowing the heat to transfer further comprises substantially uniformly increasing a permeability of a majority of the selected section.
25

1840. The method of claim 1805, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1841. The method of claim 1805, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

5 1842. The method of claim 1805, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

10 1843. The method of claim 1805, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

15 1844. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to a selected section of the
formation;
allowing the heat to transfer from the one or more heat sources to the selected
20 section of the formation to pyrolyze hydrocarbon within the selected section;
wherein at least some hydrocarbons within the selected section have an initial
atomic oxygen weight percentage of less than about 15%; and
producing a mixture from the formation.

25 1845. The method of claim 1844, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

30 1846. The method of claim 1844, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range

09841437-04401

1847. The method of claim 1844, wherein the one or more heat sources comprise electrical heaters.

1848. The method of claim 1844, wherein the one or more heat sources comprise surface burners.

1849. The method of claim 1844, wherein the one or more heat sources comprise flameless distributed combustors.

1850. The method of claim 1844, wherein the one or more heat sources comprise natural distributed combustors.

1851. The method of claim 1844, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1852. The method of claim 1844, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1853. The method of claim 1844, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} ,

wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

5 1854. The method of claim 1844, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

10 1855. The method of claim 1844, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1856. The method of claim 1844, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

15 1857. The method of claim 1844, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

20 1858. The method of claim 1844, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

25 1859. The method of claim 1844, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

30 1860. The method of claim 1844, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1868. The method of claim 1844, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1869. The method of claim 1844, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1870. The method of claim 1844, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1871. The method of claim 1844, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1872. The method of claim 1871, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1873. The method of claim 1844, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1874. The method of claim 1844, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1875. The method of claim 1844, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1876. The method of claim 1844, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and

hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1877. The method of claim 1844, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1878. The method of claim 1844, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1879. The method of claim 1844, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1880. The method of claim 1844, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1881. The method of claim 1844, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1882. The method of claim 1844, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1883. A method of treating a hydrocarbon containing formation in situ, comprising:

09841437-042401

~~providing heat from one or more heat sources to at least a portion of the~~
formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

wherein the selected section has been selected for heating using an atomic hydrogen to carbon ratio of at least a portion of hydrocarbons in the selected section, wherein at least a portion of the hydrocarbons in the selected section comprises an atomic hydrogen to carbon ratio greater than about 0.70, and wherein the atomic hydrogen to carbon ratio is less than about 1.65; and producing a mixture from the formation.

1884. The method of claim 1883, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1885. The method of claim 1883, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

~~1886. The method of claim 1883, wherein the one or more heat sources comprise electrical heaters.~~

~~1887.~~ The method of claim 1883, wherein the one or more heat sources comprise surface burners.

1888. The method of claim 1883, wherein the one or more heat sources comprise flameless distributed combustors.

1889. The method of claim 1883, wherein the one or more heat sources comprise natural distributed combustors.

1890. The method of claim 1883, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1891. The method of claim 1883, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1892. The method of claim 1883, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1893. The method of claim 1883, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1894. The method of claim 1883, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

1895. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

1896. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

5

1897. The method of claim 1883, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

10

1898. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

15

1899. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

20

1900. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

25

1901. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen-containing compounds comprise phenols.

30

1902. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1903. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

5 1904. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

10 1905. The method of claim 1883, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

15 1906. The method of claim 1883, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

20 1907. The method of claim 1883, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1908. The method of claim 1883, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

25 1909. The method of claim 1883, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

30 1910. The method of claim 1883, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1911. The method of claim 1910, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1912. The method of claim 1883, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1913. The method of claim 1883, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1914. The method of claim 1883, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1915. The method of claim 1883, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1916. The method of claim 1883, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1917. The method of claim 1883, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1918. The method of claim 1883, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1919. The method of claim 1883, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1920. The method of claim 1883, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1921. The method of claim 1883, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1922. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to a selected section of the formation;

allowing the heat to transfer from the one or more heat sources to the selected section of the formation to pyrolyze hydrocarbons within the selected section;

wherein at least some hydrocarbons within the selected section have an initial atomic hydrogen to carbon ratio greater than about 0.70;

wherein the initial atomic hydrogen to carbon ration is less than about 1.65; and

producing a mixture from the formation.

1923. The method of claim 1922, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

1924. The method of claim 1922, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

1925. The method of claim 1922, wherein the one or more heat sources comprise electrical heaters.

1926. The method of claim 1922, wherein the one or more heat sources comprise surface burners.

1927. The method of claim 1922, wherein the one or more heat sources comprise flameless distributed combustors.

1928. The method of claim 1922, wherein the one or more heat sources comprise natural distributed combustors.

1929. The method of claim 1922, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1930. The method of claim 1922, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1931. The method of claim 1922, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} ,
wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the
5 formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10
°C/day.

1932. The method of claim 1922, wherein allowing the heat to transfer comprises
transferring heat substantially by conduction.

1933. The method of claim 1922, wherein providing heat from the one or more heat
sources comprises heating the selected section such that a thermal conductivity of at least
a portion of the selected section is greater than about 0.5 W/(m °C).

1934. The method of claim 1922, wherein the produced mixture comprises condensable
hydrocarbons having an API gravity of at least about 25°.

1935. The method of claim 1922, wherein the produced mixture comprises condensable
hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the
condensable hydrocarbons are olefins.

1936. The method of claim 1922, wherein the produced mixture comprises non-
condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-
condensable hydrocarbons ranges from about 0.001 to about 0.15.

1937. The method of claim 1922, wherein the produced mixture comprises condensable
hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic
basis, of the condensable hydrocarbons is nitrogen.

1938. The method of claim 1922, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

1939. The method of claim 1922, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1940. The method of claim 1922, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

1941. The method of claim 1922, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

1942. The method of claim 1922, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

1943. The method of claim 1922, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

1944. The method of claim 1922, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

1945. The method of claim 1922, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen,

FOIb240-2443-0440

wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

5 1946. The method of claim 1922, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

1947. The method of claim 1922, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

10 1948. The method of claim 1922, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

15 1949. The method of claim 1922, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

20 1950. The method of claim 1949, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

25 1951. The method of claim 1922, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1952. The method of claim 1922, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

30 1953. The method of claim 1922, further comprising:

providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

1954. The method of claim 1922, further comprising:

producing hydrogen and condensable hydrocarbons from the formation; and

hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1955. The method of claim 1922, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1956. The method of claim 1922, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

1957. The method of claim 1922, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

1958. The method of claim 1922, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

1959. The method of claim 1922, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

1960. The method of claim 1922, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat

sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

1961. A method of treating a hydrocarbon containing formation in situ, comprising:
5 providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

10 wherein the selected section has been selected for heating using an atomic oxygen to carbon ratio of at least a portion of hydrocarbons in the selected section, wherein at least a portion of the hydrocarbons in the selected section comprises an atomic oxygen to carbon ratio greater than about 0.025, and wherein the atomic oxygen to carbon ratio of at least a portion of the hydrocarbons in the selected section is less than about 0.15 and producing a mixture from the formation.

15 1962. The method of claim 1961, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

20 1963. The method of claim 1961, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

25 1964. The method of claim 1961, wherein the one or more heat sources comprise electrical heaters.

1965. The method of claim 1961, wherein the one or more heat sources comprise surface burners.

30 1966. The method of claim 1961, wherein the one or more heat sources comprise flameless distributed combustors.

1967. The method of claim 1961, wherein the one or more heat sources comprise natural distributed combustors.

1968. The method of claim 1961, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

1969. The method of claim 1961, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

1970. The method of claim 1961, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

1971. The method of claim 1961, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

1972. The method of claim 1961, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

5 1973. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

10 1974. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

15 1975. The method of claim 1961, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

20 1976. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

25 1977. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

30 1978. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

1979. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

- 5 1980. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.
- 10 1981. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.
- 15 1982. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.
- 20 1983. The method of claim 1961, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.
- 25 1984. The method of claim 1961, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.
1985. The method of claim 1961, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.
1986. The method of claim 1961, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

1987. The method of claim 1961, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

1988. The method of claim 1961, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

1989. The method of claim 1988, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

1990. The method of claim 1961, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

1991. The method of claim 1961, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

1992. The method of claim 1961, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

1993. The method of claim 1961, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

1994. The method of claim 1961, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

1995. The method of claim 1961, wherein allowing the heat to transfer further comprises substantially uniformly increasing a permeability of a majority of the selected section.

5

1996. The method of claim 1961, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

10

1997. The method of claim 1961, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

15

1998. The method of claim 1961, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

20

1999. The method of claim 1961, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

25

2000. A method of treating a hydrocarbon containing formation in situ, comprising providing heat from one or more heat sources to a selected section of the formation;

30

allowing the heat to transfer from the one or more heat sources to the selected section of the formation to pyrolyze hydrocarbons within the selected section;

wherein at least some hydrocarbons within the selected section have an initial atomic oxygen to carbon ratio greater than about 0.025;

wherein the initial atomic oxygen to carbon ratio is less than about 0.15; and producing a mixture from the formation.

2001. The method of claim 2000, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2002. The method of claim 2000, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2003. The method of claim 2000, wherein the one or more heat sources comprise electrical heaters.

2004. The method of claim 2000, wherein the one or more heat sources comprise surface burners.

2005. The method of claim 2000, wherein the one or more heat sources comprise flameless distributed combustors.

2006. The method of claim 2000, wherein the one or more heat sources comprise natural distributed combustors.

2007. The method of claim 2000, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2008. The method of claim 2000, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1°C per day during pyrolysis.

2009. The method of claim 2000, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2010. The method of claim 2000, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2011. The method of claim 2000, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2012. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2013. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2014. The method of claim 2000, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2015. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

5

2016. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

10

2017. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

15

2018. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

20

2019. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

25

2020. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

30

2021. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2022. The method of claim 2000, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2023. The method of claim 2000, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2024. The method of claim 2000, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2025. The method of claim 2000, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2026. The method of claim 2000, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2027. The method of claim 2000, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2028. The method of claim 2027, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2029. The method of claim 2000, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2030. ~~The method of claim 2000, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.~~

2031. The method of claim 2000, further comprising:

5 providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
 heating a portion of the section with heat from hydrogenation.

2032. The method of claim 2000, further comprising:

10 producing hydrogen and condensable hydrocarbons from the formation; and
 hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2033. The method of claim 2000, wherein allowing the heat to transfer comprises
15 increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2034. The method of claim 2000, wherein allowing the heat to transfer further
20 comprises substantially uniformly increasing a permeability of a majority of the selected section.

2035. The method of claim 2000, further comprising controlling the heat to yield greater
25 than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2036. The method of claim 2000, wherein producing the mixture comprises producing
the mixture in a production well, and wherein at least about 7 heat sources are disposed in
the formation for each production well.

30 2037. ~~The method of claim 2000, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat~~

09841437-042401

sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2038. The method of claim 2000, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2039. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation;

wherein the selected section has been selected for heating using a moisture content in the selected section, and wherein at least a portion of the selected section comprises a moisture content of less than about 15%; and

producing a mixture from the formation.

2040. The method of claim 2039, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2041. The method of claim 2039, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2042. The method of claim 2039, wherein the one or more heat sources comprise electrical heaters.

09841437 042401

2043. The method of claim 2039, wherein the one or more heat sources comprise surface burners.

2044. The method of claim 2039, wherein the one or more heat sources comprise flameless distributed combustors.

2045. The method of claim 2039, wherein the one or more heat sources comprise natural distributed combustors.

2046. The method of claim 2039, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2047. The method of claim 2039, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2048. The method of claim 2039, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2049. The method of claim 2039, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2050. The method of claim 2039, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2051. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2052. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2053. The method of claim 2039, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2054. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2055. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2056. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

09841437 042401

2057. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

5

2058. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

10

2059. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

15

2060. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

20

2061. The method of claim 2039, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

25

2062. The method of claim 2039, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

30

2063. The method of claim 2039, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2064. The method of claim 2039, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2065. The method of claim 2039, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2066. The method of claim 2039, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2067. The method of claim 2066, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2068. The method of claim 2039, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2069. The method of claim 2039, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2070. The method of claim 2039, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

2071. The method of claim 2039, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2072. The method of claim 2039, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

5 2073. The method of claim 2039, wherein allowing the heat to transfer further comprises substantially uniformly increasing a permeability of a majority of the selected section.

10 2074. The method of claim 2039, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

15 2075. The method of claim 2039, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

20 2076. The method of claim 2039, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

25 2077. The method of claim 2039, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

30 2078. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to a selected section of the
formation;

allowing the heat to transfer from the one or more heat sources to the selected section of the formation;

wherein at least a portion of the selected section has an initial moisture content of less than about 15%; and

5 producing a mixture from the formation.

10 2079. The method of claim 2078, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

15 2080. The method of claim 2078, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

20 2081. The method of claim 2078, wherein the one or more heat sources comprise electrical heaters.

25 2082. The method of claim 2078, wherein the one or more heat sources comprise surface burners.

30 2083. The method of claim 2078, wherein the one or more heat sources comprise flameless distributed combustors.

2084. The method of claim 2078, wherein the one or more heat sources comprise natural distributed combustors.

2085. The method of claim 2078, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

0984147-042401

2086. The method of claim 2078, ~~further comprising controlling~~ the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2087. The method of claim 2078, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2088. The method of claim 2078, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2089. The method of claim 2078, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2090. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2091. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2092. The method of claim 2078, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

5 2093. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

10 2094. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

15 2095. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

20 2096. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

25 2097. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2098. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2099. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

5 2100. The method of claim 2078, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

10 2101. The method of claim 2078, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

15 2102. The method of claim 2078, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

20 2103. The method of claim 2078, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2104. The method of claim 2078, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

25 2105. The method of claim 2078, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

30 2106. The method of claim 2105, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

09841437 042401

2107. ~~The method of claim 2078, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.~~

5 2108. The method of claim 2078, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2109. The method of claim 2078, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons
10 within the section; and
heating a portion of the section with heat from hydrogenation.

2110. The method of claim 2078, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
15 hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2111. The method of claim 2078, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100
20 millidarcy.

2112. The method of claim 2078, wherein allowing the heat to transfer further comprises substantially uniformly increasing a permeability of a majority of the selected section.

25 2113. The method of claim 2078, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2114. ~~The method of claim 2078, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.~~

5 2115. The method of claim 2078, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

10 2116. The method of claim 2078, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

15 2117. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected
20 section of the formation;
wherein the selected section is heated in a reducing environment during at least a portion of the time that the selected section is being heated; and
producing a mixture from the formation.

25 2118. The method of claim 2117, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

30 2119. The method of claim 2117, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

~~2120. The method of claim 2117, wherein the one or more heat sources comprise electrical heaters.~~

2121. The method of claim 2117, wherein the one or more heat sources comprise surface burners.

2122. The method of claim 2117, wherein the one or more heat sources comprise flameless distributed combustors.

2123. The method of claim 2117, wherein the one or more heat sources comprise natural distributed combustors.

2124. The method of claim 2117, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2125. The method of claim 2117, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2126. The method of claim 2117, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_b is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2127. The method of claim 2117, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2128. The method of claim 2117, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2129. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2130. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2131. The method of claim 2117, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2132. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2133. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

TOH210" 2E4F360

2134. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

5 2135. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

10 2136. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

15 2137. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

20 2138. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

25 2139. The method of claim 2117, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

30 2140. The method of claim 2117, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2141. The method of claim 2117, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2142. The method of claim 2117, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2143. The method of claim 2117, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2144. The method of claim 2117, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2145. The method of claim 2144, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2146. The method of claim 2117, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2147. The method of claim 2117, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2148. The method of claim 2117, further comprising:
 providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
 heating a portion of the section with heat from hydrogenation.

2149. The method of claim 2117, further comprising:
 producing hydrogen and condensable hydrocarbons from the formation; and

hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2150. The method of claim 2117, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2151. The method of claim 2117, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

2152. The method of claim 2117, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2153. The method of claim 2117, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2154. The method of claim 2117, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2155. The method of claim 2117, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2156. A method of treating a hydrocarbon containing formation in situ, comprising:
heating a first section of the formation to produce a mixture from the formation;

heating a second section of the formation; and

recirculating a portion of the produced mixture from the first section into the second section of the formation to provide a reducing environment within the second section of the formation.

5

2157. The method of claim 2156, further comprising maintaining a temperature within the first section or the second section within a pyrolysis temperature range.

10

2158. The method of claim 2156, wherein heating the first or the second section comprises heating with an electrical heater.

2159. The method of claim 2156, wherein heating the first or the second section comprises heating with a surface burner.

15

2160. The method of claim 2156, wherein heating the first or the second section comprises heating with a flameless distributed combustor.

20

2161. The method of claim 2156, wherein heating the first or the second section comprises heating with a natural distributed combustor.

25

2162. The method of claim 2156, further comprising controlling a pressure and a temperature within at least a majority of the first or second section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

30

2163. The method of claim 2156, further comprising controlling the heat such that an average heating rate of the first or the second section is less than about 1 °C per day during pyrolysis.

2164. The method of claim 2156, wherein heating the first or the second section comprises:

heating a selected volume (V) of the hydrocarbon containing formation from one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

5 wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

10 wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2165. The method of claim 2156, wherein heating the first or the second section comprises transferring heat substantially by conduction.

15 2166. The method of claim 2156, wherein heating the first or the second section comprises heating the first or the second section such that a thermal conductivity of at least a portion of the first or the second section is greater than about 0.5 W/(m °C).

20 2167. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2168. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

25 2169. The method of claim 2156, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2170. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

5 2171. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

10 2172. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

15 2173. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

20 2174. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

25 2175. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2176. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2177. The method of claim 2156, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2178. The method of claim 2156, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2179. The method of claim 2156, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2180. The method of claim 2156, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2181. The method of claim 2156, further comprising controlling a pressure within at least a majority of the first or second section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2182. The method of claim 2156, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2183. The method of claim 2182, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2184. The method of claim 2156, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

09841437 042401
FOH240 2E41860

2185. The method of claim 2156, further comprising:
providing hydrogen (H_2) to the first or second section to hydrogenate
hydrocarbons within the first or second section; and
heating a portion of the first or second section with heat from hydrogenation.

2186. The method of claim 2156, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a
portion of the produced hydrogen.

2187. The method of claim 2156, wherein heating the first or the second section
comprises increasing a permeability of a majority of the first or the second section to
greater than about 100 millidarcy.

2188. The method of claim 2156, wherein heating the first or the second section
comprises substantially uniformly increasing a permeability of a majority of the first or
the second section.

2189. The method of claim 2156, further comprising controlling the heat to yield greater
than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer
Assay.

2190. The method of claim 2156, wherein producing the mixture comprises producing
the mixture in a production well, and wherein at least about 7 heat sources are disposed in
the formation for each production well.

2191. The method of claim 2156, further comprising providing heat from three or more
heat sources to at least a portion of the formation, wherein three or more of the heat
sources are located in the formation in a unit of heat sources, and wherein the unit of heat
sources comprises a triangular pattern.

09441437 042401

5 2192. The method of claim 2156, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

10 2193. A method of treating a hydrocarbon containing formation in situ, comprising: providing heat from one or more heat sources to at least a portion of the formation; and allowing the heat to transfer from the one or more heat sources to a selected section of the formation such that a permeability of at least a portion of the selected section increases to greater than about 100 millidarcy.

15 2194. The method of claim 2193, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

20 2195. The method of claim 2193, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

25 2196. The method of claim 2193, wherein the one or more heat sources comprise electrical heaters.

2197. The method of claim 2193, wherein the one or more heat sources comprise surface burners.

30 2198. The method of claim 2193, wherein the one or more heat sources comprise flameless distributed combustors.

2199. The method of claim 2193, wherein the one or more heat sources comprise natural distributed combustors.

2200. The method of claim 2193, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2201. The method of claim 2193, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2202. The method of claim 2193, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2203. The method of claim 2193, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2204. The method of claim 2193, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2205. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

5

2206. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

10

2207. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

15

2208. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

20

2209. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

25

2210. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

30

09841437-042401

2211. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2212. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2213. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2214. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2215. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2216. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

5

2217. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

10

2218. The method of claim 2193, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer

15

2219. The method of claim 2193, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

20

2220. The method of claim 2193, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

25

2221. The method of claim 2220, further comprising producing a mixture from the formation, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

30

2222. The method of claim 2193, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2223. The method of claim 2193, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2224. The method of claim 2193, further comprising:

providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

5 2225. The method of claim 2193, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a
portion of the produced hydrogen.

10 2226. The method of claim 2193, further comprising increasing a permeability of a
majority of the selected section to greater than about 5 Darcy.

15 2227. The method of claim 2193, wherein allowing the heat to transfer comprises
substantially uniformly increasing a permeability of a majority of the selected section.

20 2228. The method of claim 2193, further comprising controlling the heat to yield greater
than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer
Assay.

25 2229. The method of claim 2193, further comprising producing a mixture in a
production well, wherein at least about 7 heat sources are disposed in the formation for
each production well.

30 2230. The method of claim 2193, further comprising providing heat from three or more
heat sources to at least a portion of the formation, wherein three or more of the heat
sources are located in the formation in a unit of heat sources, and wherein the unit of heat
sources comprises a triangular pattern.

2231. The method of claim 2193, further comprising providing heat from three or more
heat sources to at least a portion of the formation, wherein three or more of the heat
sources are located in the formation in a unit of heat sources, wherein the unit of heat

sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2232. A method of treating a hydrocarbon containing formation in situ, comprising:

5 providing heat from one or more heat sources to at least a portion of the formation; and

allowing the heat to transfer from the one or more heat sources to a selected section of the formation such that a permeability of a majority of at least a portion of the selected section increases substantially uniformly.

10 2233. The method of claim 2232, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

15 2234. The method of claim 2232, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

20 2235. The method of claim 2232, wherein the one or more heat sources comprise electrical heaters.

2236. The method of claim 2232, wherein the one or more heat sources comprise surface burners.

25 2237. The method of claim 2232, wherein the one or more heat sources comprise flameless distributed combustors.

30 2238. The method of claim 2232, wherein the one or more heat sources comprise natural distributed combustors.

2239. The method of claim 2232, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2240. The method of claim 2232, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2241. The method of claim 2232, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2242. The method of claim 2232, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2243. The method of claim 2232, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

09841437-042401

2244. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

5 2245. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

10 2246. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

15 2247. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

20 2248. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

25 2249. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

30 2250. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein

about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

5 2251. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

10 2252. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

15 2253. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

20 2254. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

25 2255. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

30

2256. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

5 2257. The method of claim 2232, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

10 2258. The method of claim 2232, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

15 2259. The method of claim 2232, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

20 2260. The method of claim 2232, further comprising producing a mixture from the formation, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

2261. The method of claim 2232, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

25 2262. The method of claim 2232, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

30 2263. The method of claim 2232, further comprising:
providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and

~~heating a portion of the section with heat from hydrogenation.~~

2264. The method of claim 2232, further comprising:

producing hydrogen and condensable hydrocarbons from the formation; and

hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2265. The method of claim 2232, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2266. The method of claim 2232, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2267. The method of claim 2232, further comprising producing a mixture in a production well, wherein at least about 7 heat sources are disposed in the formation for each production well.

2268. The method of claim 2232, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2269. The method of claim 2232, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2270. ~~A method of treating a hydrocarbon containing formation in situ, comprising:~~

providing heat from one or more heat sources to at least a portion of the formation; and

allowing the heat to transfer from the one or more heat sources to a selected section of the formation such that a porosity of a majority of at least a portion of the selected section increases substantially uniformly.

2271. The method of claim 2270, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2272. The method of claim 2270, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2273. The method of claim 2270, wherein the one or more heat sources comprise electrical heaters.

2274. The method of claim 2270, wherein the one or more heat sources comprise surface burners.

2275. The method of claim 2270, wherein the one or more heat sources comprise flameless distributed combustors.

2276. The method of claim 2270, wherein the one or more heat sources comprise natural distributed combustors.

2277. The method of claim 2270, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2278. The method of claim 2270, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2279. The method of claim 2270, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2280. The method of claim 2270, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2281. The method of claim 2270, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2282. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2283. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2284. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2285. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2286. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2287. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2288. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2289. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2290. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2291. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2292. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2293. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2294. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2295. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2296. The method of claim 2270, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2297. The method of claim 2270, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2298. The method of claim 2270, further comprising producing a mixture from the formation, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2299. The method of claim 2270, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2300. The method of claim 2270, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2301. The method of claim 2270, further comprising:
 providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
 heating a portion of the section with heat from hydrogenation.

2302. The method of claim 2270, further comprising:
 producing hydrogen and condensable hydrocarbons from the formation; and
 hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2303. The method of claim 2270, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2304. The method of claim 2270, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

2305. The method of claim 2270, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2306. The method of claim 2270, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2307. The method of claim 2270, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2308. The method of claim 2270, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2309. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and

controlling the heat to yield at least about 15 % by weight of a total organic carbon content of at least some of the hydrocarbon containing formation into condensable hydrocarbons.

5 2310. The method of claim 2309, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

10 2311. The method of claim 2309, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2312. The method of claim 2309, wherein the one or more heat sources comprise electrical heaters.

15 2313. The method of claim 2309, wherein the one or more heat sources comprise surface burners.

20 2314. The method of claim 2309, wherein the one or more heat sources comprise flameless distributed combustors.

2315. The method of claim 2309, wherein the one or more heat sources comprise natural distributed combustors.

25 2316. The method of claim 2309, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2317. The method of claim 2309, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2318. The method of claim 2309, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2319. The method of claim 2309, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2320. The method of claim 2309, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2321. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2322. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2323. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2324. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2325. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2326. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2327. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2328. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2329. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2330. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2331. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2332. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2333. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2334. The method of claim 2309, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2335. The method of claim 2309, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2336. The method of claim 2309, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2337. The method of claim 2309, further comprising producing a mixture from the formation, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2338. The method of claim 2309, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2339. The method of claim 2309, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2340. The method of claim 2309, further comprising:
 providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
 heating a portion of the section with heat from hydrogenation.

2341. The method of claim 2309, further comprising:
 producing hydrogen and condensable hydrocarbons from the formation; and
 hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2342. The method of claim 2309, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2343. The method of claim 2309, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

2344. The method of claim 2309, wherein the heating is controlled to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2345. The method of claim 2309, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2346. The method of claim 2309, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2347. The method of claim 2309, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2348. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and

controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2349. The method of claim 2348, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2350. The method of claim 2348, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2351. The method of claim 2348, wherein the one or more heat sources comprise electrical heaters.

2352. The method of claim 2348, wherein the one or more heat sources comprise surface burners.

2353. The method of claim 2348, wherein the one or more heat sources comprise flameless distributed combustors.

2354. The method of claim 2348, wherein the one or more heat sources comprise natural distributed combustors.

2355. The method of claim 2348, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2356. The method of claim 2348, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2357. The method of claim 2348, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2358. The method of claim 2348, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2359. The method of claim 2348, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2360. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2361. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2362. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2363. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2364. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2365. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2366. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2367. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

09841437-042401

2368. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2369. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2370. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2371. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2372. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2373. The method of claim 2348, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2374. The method of claim 2348, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2375. The method of claim 2348, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2376. The method of claim 2348, further comprising producing a mixture from the formation, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2377. The method of claim 2348, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2378. The method of claim 2348, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2379. The method of claim 2348, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

2380. The method of claim 2348, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen

2381. The method of claim 2348, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

5 2382. The method of claim 2348, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

10 2383. The method of claim 2348, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

15 2384. The method of claim 2348, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

20 2385. The method of claim 2348, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

25 2386. A method of treating a hydrocarbon containing formation in situ, comprising:
 heating a first section of the formation to pyrolyze at least some hydrocarbons in the first section and produce a first mixture from the formation;
 heating a second section of the formation to pyrolyze at least some hydrocarbons in the second section and produce a second mixture from the formation; and
 leaving an unpyrolyzed section between the first section and the second section to inhibit subsidence of the formation.

30

2387. The method of claim 2386, further comprising maintaining a temperature within the first section or the second section within a pyrolysis temperature range.

2388. The method of claim 2386, wherein heating the first section or heating the second section comprises heating with an electrical heater.

2389. The method of claim 2386, wherein heating the first section or heating the second section comprises heating with a surface burner.

2390. The method of claim 2386, wherein heating the first section or heating the second section comprises heating with a flameless distributed combustor.

2391. The method of claim 2386, wherein heating the first section or heating the second section comprises heating with a natural distributed combustor.

2392. The method of claim 2386, further comprising controlling a pressure and a temperature within at least a majority of the first or second section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2393. The method of claim 2386, further comprising controlling the heat such that an average heating rate of the first or second section is less than about 1 °C per day during pyrolysis.

2394. The method of claim 2386, wherein heating the first section or heating the second section comprises:

heating a selected volume (V) of the hydrocarbon containing formation from one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} ,
wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the
5 formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10
°C/day.

2395. The method of claim 2386, wherein heating the first section or heating the second
section comprises transferring heat substantially by conduction.

2396. The method of claim 2386, wherein heating the first section or heating the second
section comprises heating the formation such that a thermal conductivity of at least a
portion of the first or second section, respectively, is greater than about 0.5 W/(m °C).

2397. The method of claim 2386, wherein the first or second mixture comprises
condensable hydrocarbons having an API gravity of at least about 25°.

2398. The method of claim 2386, wherein the first or second mixture comprises
condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight
20 of the condensable hydrocarbons are olefins.

2399. The method of claim 2386, wherein the first or second mixture comprises non-
condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-
condensable hydrocarbons ranges from about 0.001 to about 0.15.

2400. The method of claim 2386, wherein the first or second mixture comprises
condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated
on an atomic basis, of the condensable hydrocarbons is nitrogen.

2401. The method of claim 2386, wherein the first or second mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2402. The method of claim 2386, wherein the first or second mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2403. The method of claim 2386, wherein the first or second mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2404. The method of claim 2386, wherein the first or second mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2405. The method of claim 2386, wherein the first or second mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2406. The method of claim 2386, wherein the first or second mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2407. The method of claim 2386, wherein the first or second mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2408. The method of claim 2386, wherein the first or second mixture comprises a non-condensable component, and wherein the non-condensable component comprises

hydrogen, and wherein the hydrogen is greater than about 10 % by volume of the non-condensable component and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

5 2409. The method of claim 2386, wherein the first or second mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the first or second mixture is ammonia.

2410. The method of claim 2386, wherein the first or second mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2411. The method of claim 2386, further comprising controlling a pressure within at least a majority of the first or second section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2412. The method of claim 2386, further comprising controlling formation conditions to produce the first or second mixture, wherein a partial pressure of H₂ within the first or second mixture is greater than about 0.5 bar.

20 2413. The method of claim 2386, wherein a partial pressure of H₂ within the first or second mixture is measured when the first or second mixture is at a production well.

2414. The method of claim 2386, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon
25 numbers greater than about 25.

2415. The method of claim 2386, further comprising controlling formation conditions by recirculating a portion of hydrogen from the first or second mixture into the formation.

30 2416. The method of claim 2386, further comprising:

providing hydrogen (H₂) to the first or second section to hydrogenate hydrocarbons within the first or second section, respectively; and

heating a portion of the first or second section, respectively, with heat from hydrogenation.

5

2417. The method of claim 2386, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2418. The method of claim 2386, wherein heating the first section or heating the second section comprises increasing a permeability of a majority of the first or second section, respectively, to greater than about 100 millidarcy.

2419. The method of claim 2386, wherein heating the first section or heating the second section comprises substantially uniformly increasing a permeability of a majority of the first or second section, respectively.

2420. The method of claim 2386, further comprising controlling heating of the first or second section to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay, from the first or second section, respectively.

2421. The method of claim 2386, wherein producing the first or second mixture comprises producing the first or second mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2422. The method of claim 2386, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2423. The method of claim 2386, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units

2424. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and
producing a mixture from the formation through one or more production wells, wherein the heating is controlled such that the mixture can be produced from the formation as a vapor, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2425. The method of claim 2424, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2426. The method of claim 2424, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2427. The method of claim 2424, wherein the one or more heat sources comprise electrical heaters.

2428. The method of claim 2424, wherein the one or more heat sources comprise surface burners.

2429. The method of claim 2424, wherein the one or more heat sources comprise flameless distributed combustors.

2430. The method of claim 2424, wherein the one or more heat sources comprise natural distributed combustors.

2431. The method of claim 2424, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2432. The method of claim 2424, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2433. The method of claim 2424, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2434. The method of claim 2424, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2435. The method of claim 2424, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2436. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2437. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2438. The method of claim 2424, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2439. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2440. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2441. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2442. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2443. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2444. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2445. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2446. The method of claim 2424, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2447. The method of claim 2424, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2448. The method of claim 2424, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2449. The method of claim 2424, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2450. The method of claim 2424, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2451. The method of claim 2424, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2452. The method of claim 2452, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2453. The method of claim 2424, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2454. The method of claim 2424, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2455. The method of claim 2424, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

2456. The method of claim 2424, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2457. The method of claim 2424, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2458. The method of claim 2424, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

2459. The method of claim 2424, wherein the heating is controlled to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2460. The method of claim 2424, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2461. The method of claim 2424, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2462. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation, wherein the one or more heat sources are disposed within one or more first wells;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and

producing a mixture from the formation through one or more second wells, wherein one or more of the first or second wells are initially used for a first purpose and are then used for one or more other purposes.

2463. The method of claim 2462, wherein the first purpose comprises removing water from the formation, and wherein the second purpose comprises providing heat to the formation.

2464. The method of claim 2462, wherein the first purpose comprises removing water from the formation, and wherein the second purpose comprises producing the mixture.

2465. The method of claim 2462, wherein the first purpose comprises heating, and wherein the second purpose comprises removing water from the formation.

2466. The method of claim 2462, wherein the first purpose comprises producing the mixture, and wherein the second purpose comprises removing water from the formation.

2467. The method of claim 2462, wherein the one or more heat sources comprise electrical heaters.

2468. The method of claim 2462, wherein the one or more heat sources comprise surface burners.

2469. The method of claim 2462, wherein the one or more heat sources comprise flameless distributed combustors.

2470. The method of claim 2462, wherein the one or more heat sources comprise natural distributed combustors.

2471. The method of claim 2462, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2472. The method of claim 2462, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1.0 ° C per day during pyrolysis.

2473. The method of claim 2462, wherein providing heat from the one or more heat sources to at least the portion of the formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2474. The method of claim 2462, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2475. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2476. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2477. The method of claim 2462, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2478. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2479. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2480. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2481. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2482. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2483. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2484. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2485. The method of claim 2462, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

104443-0440-2480-2485

2486. The method of claim 2462, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2487. The method of claim 2462, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2488. The method of claim 2462, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2489. The method of claim 2462, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2490. The method of claim 2462, further comprising controlling formation conditions to produce a mixture of condensable hydrocarbons and H_2 , wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2491. The method of claim 2490, wherein the partial pressure of H_2 is measured when the mixture is at a production well.

2492. The method of claim 2462, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2493. The method of claim 2462, further comprising controlling formation conditions, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

2494. The method of claim 2462, further comprising:

providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and

heating a portion of the section with heat from hydrogenation.

2495. The method of claim 2462, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2496. The method of claim 2462, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2497. The method of claim 2462, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

2498. The method of claim 2462, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2499. The method of claim 2462, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2500. The method of claim 2462, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2501. The method of claim 2462, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat

sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

5 2502. A method for forming heater wells in a hydrocarbon containing formation, comprising.

forming a first wellbore in the formation;

forming a second wellbore in the formation using magnetic tracking such that the second wellbore is arranged substantially parallel to the first wellbore; and

10 providing at least one heating mechanism within the first wellbore and at least one heating mechanism within the second wellbore such that the heating mechanisms can provide heat to at least a portion of the formation.

15 2503. The method of claim 1, wherein superposition of heat from the at least one heating mechanism within the first wellbore and the at least one heating mechanism within the second wellbore pyrolyzes at least some hydrocarbons within a selected section of the formation.

20 2504. The method of claim 2502, further comprising maintaining a temperature within a selected section within a pyrolysis temperature range.

2505. The method of claim 2502, wherein the heating mechanisms comprise electrical heaters.

25 2506. The method of claim 2502, wherein the heating mechanisms comprise surface burners.

30 2507. The method of claim 2502, wherein the heating mechanisms comprise flameless distributed combustors.

2508. The method of claim 2502, wherein the heating mechanisms comprise natural distributed combustors.

2509. The method of claim 2502, further comprising controlling a pressure and a temperature within at least a majority of a selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2510. The method of claim 2502, further comprising controlling the heat from the heating mechanisms such that heat transferred from the heating mechanisms to at least the portion of the hydrocarbons is less than about 1 °C per day during pyrolysis.

2511. The method of claim 2502, further comprising:

heating a selected volume (V) of the hydrocarbon containing formation from the heating mechanisms, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2512. The method of claim 2502, further comprising allowing the heat to transfer from the heating mechanisms to at least the portion of the formation substantially by conduction.

2513. The method of claim 2502, further comprising providing heat from the heating mechanisms to at least the portion of the formation such that a thermal conductivity of at least the portion of the formation is greater than about 0.5 W/(m °C).

2514. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2515. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2516. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2517. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2518. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2519. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2520. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2521. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2522. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2523. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2524. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2525. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2526. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2527. The method of claim 2502, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2528. The method of claim 2502, further comprising controlling a pressure within at least a majority of a selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2529. The method of claim 2528, wherein the partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2530. The method of claim 2502, further comprising producing a mixture from the formation, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2531. The method of claim 2502, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2532. The method of claim 2502, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2533. The method of claim 2502, further comprising:
providing hydrogen (H_2) to the portion to hydrogenate hydrocarbons within the formation; and

heating a portion of the formation with heat from hydrogenation.

2534. The method of claim 2502, further comprising:

producing hydrogen and condensable hydrocarbons from the formation; and

hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2535. The method of claim 2502, further comprising allowing heat to transfer from the heating mechanisms to a selected section of the formation to pyrolyze at least some hydrocarbons within the selected section such that a permeability of a majority of a selected section of the formation increases to greater than about 100 millidarcy.

2536. The method of claim 2502, further comprising allowing heat to transfer from the heating mechanisms to a selected section of the formation to pyrolyze at least some hydrocarbons within the selected section such that a permeability of a majority of the selected section increases substantially uniformly.

2537. The method of claim 2502, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2538. The method of claim 2502, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2539. The method of claim 2502, further comprising forming a production well in the formation using magnetic tracking such that the production well is substantially parallel to the first wellbore and coupling a wellhead to the third wellbore.

2540. The method of claim 2502, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat

sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2541. The method of claim 2502, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2542. A method for installing a heater well into a hydrocarbon containing formation, comprising:

forming a bore in the ground using a steerable motor and an accelerometer; and providing a heating mechanism within the bore such that the heating mechanism can transfer heat to at least a portion of the formation.

2543. The method of claim 2542, further comprising installing at least two heater wells, and wherein superposition of heat from at least the two heater wells pyrolyzes at least some hydrocarbons within a selected section of the formation.

2544. The method of claim 2542, further comprising maintaining a temperature within a selected section within a pyrolysis temperature range.

2545. The method of claim 2542, wherein the heating mechanism comprises an electrical heater.

2546. The method of claim 2542, wherein the heating mechanism comprises a surface burner.

2547. The method of claim 2542, wherein the heating mechanism comprises a flameless distributed combustor.

2548. The method of claim 2542, wherein the heating mechanism comprises a natural distributed combustor.

2549. The method of claim 2542, further comprising controlling a pressure and a temperature within at least a majority of a selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2550. The method of claim 2542, further comprising controlling the heat from the heating mechanism such that heat transferred from the heating mechanism to at least the portion of the formation is less than about 1 °C per day during pyrolysis.

2551. The method of claim 2542, further comprising:

heating a selected volume (V) of the hydrocarbon containing formation from the heating mechanism, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day

2552. The method of claim 2542, further comprising allowing the heat to transfer from the heating mechanism to at least the portion of the formation substantially by conduction.

2553. The method of claim 2542, further comprising providing heat from the heating mechanism to at least the portion of the formation such that a thermal conductivity of at least the portion of the formation is greater than about 0.5 W/(m °C).

2554. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

5

2555. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2556. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2557. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2558. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2559. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

10
15
20
25
30

2560. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2561. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2562. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2563. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2564. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2565. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2566. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2567. The method of claim 2542, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2568. The method of claim 2542, further comprising controlling a pressure within at least a majority of a selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2569. The method of claim 2542, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

2570. The method of claim 2569, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

2571. The method of claim 2542, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2572. The method of claim 2542, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2573. The method of claim 2542, further comprising:
providing hydrogen (H₂) to the at least the heated portion to hydrogenate hydrocarbons within the formation; and

heating a portion of the formation with heat from hydrogenation.

2574. The method of claim 2542, further comprising:

producing hydrogen and condensable hydrocarbons from the formation; and

hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2575. The method of claim 2542, further comprising allowing heat to transfer from the heating mechanism to a selected section of the formation to pyrolyze at least some hydrocarbons within the selected section such that a permeability of a majority of a selected section of the formation increases to greater than about 100 millidarcy.

2576. The method of claim 2542, further comprising allowing heat to transfer from the heating mechanism to a selected section of the formation to pyrolyze at least some hydrocarbons within the selected section such that a permeability of a majority of the selected section increases substantially uniformly.

2577. The method of claim 2542, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2578. The method of claim 2542, further comprising producing a mixture in a production well, and wherein at least about 7 heating mechanisms are disposed in the formation for each production well.

2579. The method of claim 2542, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2580. The method of claim 2542, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2581. A method for installing of wells in a hydrocarbon containing formation, comprising:

forming a wellbore in the formation by geosteered drilling; and
providing a heating mechanism within the wellbore such that the heating mechanism can transfer heat to at least a portion of the formation.

2582. The method of claim 2581, further comprising maintaining a temperature within a selected section within a pyrolysis temperature range.

2583. The method of claim 2581, wherein the heating mechanism comprises an electrical heater.

2584. The method of claim 2581, wherein the heating mechanism comprises a surface burner.

2585. The method of claim 2581, wherein the heating mechanism comprises a flameless distributed combustor.

2586. The method of claim 2581, wherein the heating mechanism comprises a natural distributed combustor.

2587. The method of claim 2581, further comprising controlling a pressure and a temperature within at least a majority of a selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2588. The method of claim 2581, further comprising controlling the heat from the heating mechanism such that heat transferred from the heating mechanism to at least the portion of the formation is less than about 1 °C per day during pyrolysis.

2589. The method of claim 2581, further comprising:

heating a selected volume (V) of the hydrocarbon containing formation from the heating mechanism, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2590. The method of claim 2581, further comprising allowing the heat to transfer from the heating mechanism to at least the portion of the formation substantially by conduction.

2591. The method of claim 2581, further comprising providing heat from the heating mechanism to at least the portion of the formation such that a thermal conductivity of at least the portion of the formation is greater than about 0.5 W/(m °C).

2592. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2593. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2594. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2595. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2596. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2597. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2598. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2599. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2600. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2601. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2602. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2603. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2604. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2605. The method of claim 2581, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2606. The method of claim 2581, further comprising controlling a pressure within at least a majority of a selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2607. The method of claim 2581, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2608. The method of claim 2607, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2609. The method of claim 2581, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2610. The method of claim 2581, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2611. The method of claim 2581, further comprising:
providing hydrogen (H_2) to at least the heated portion to hydrogenate hydrocarbons within the formation; and
heating a portion of the formation with heat from hydrogenation.

2612. The method of claim 2581, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2613. The method of claim 2581, further comprising allowing heat to transfer from the heating mechanism to a selected section of the formation to pyrolyze at least some hydrocarbons within the selected section such that a permeability of a majority of a selected section of the formation increases to greater than about 100 millidarcy.

2614. The method of claim 2581, further comprising allowing heat to transfer from the heating mechanism to a selected section of the formation to pyrolyze at least some hydrocarbons within the selected section such that a permeability of a majority of the selected section increases substantially uniformly.

2615. The method of claim 2581, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2616. The method of claim 2581, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2617. The method of claim 2581, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2618. The method of claim 2581, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2619. A method of treating a hydrocarbon containing formation in situ, comprising:

heating a selected section of the formation with a heating element placed within a wellbore, wherein at least one end of the heating element is free to move axially within the wellbore to allow for thermal expansion of the heating element.

5 2620. The method of claim 2619, further comprising at least two heating elements within at least two wellbores, and wherein superposition of heat from at least the two heating elements pyrolyzes at least some hydrocarbons within a selected section of the formation.

10 2621. The method of claim 2619, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2622. The method of claim 2619, wherein the heating element comprises a pipe-in-pipe heater.

2623. The method of claim 2619, wherein the heating element comprises a flameless distributed combustor.

20 2624. The method of claim 2619, wherein the heating element comprises a mineral insulated cable coupled to a support, and wherein the support is free to move within the wellbore.

2625. The method of claim 2619, wherein the heating element comprises a mineral insulated cable suspended from a wellhead.

25 2626. The method of claim 2619, further comprising controlling a pressure and a temperature within at least a majority of a heated section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2627. The method of claim 2619, further comprising controlling the heat such that an average heating rate of the heated section is less than about 1 °C per day during pyrolysis.

2628. The method of claim 2619, wherein heating the section of the formation further comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the heating element, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2629. The method of claim 2619, wherein heating the section of the formation comprises transferring heat substantially by conduction.

2630. The method of claim 2619, further comprising heating the selected section of the formation such that a thermal conductivity of the selected section is greater than about 0.5 W/(m °C).

2631. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2632. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2633. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2634. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2635. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2636. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2637. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2638. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2639. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-
5 ring aromatics with more than two rings.

2640. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are
10 asphaltenes.

2641. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2642. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2643. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein greater than
25 about 0.05 % by weight of the produced mixture is ammonia.

2644. The method of claim 2619, further comprising producing a mixture from the formation, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

098447-04240-2541860

2645. The method of claim 2619, further comprising controlling a pressure within the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2646. The method of claim 2619, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2647. The method of claim 2647, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2648. The method of claim 2619, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2649. The method of claim 2619, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2650. The method of claim 2619, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the heated section; and
heating a portion of the section with heat from hydrogenation.

2651. The method of claim 2619, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2652. The method of claim 2619, wherein heating comprises increasing a permeability of a majority of the heated section to greater than about 100 millidarcy.

2653. The method of claim 2619, wherein heating comprises substantially uniformly increasing a permeability of a majority of the heated section.

2654. The method of claim 2619, wherein the heating is controlled to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2655. The method of claim 2619, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2656. The method of claim 2619, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2657. The method of claim 2619, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2658. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;

allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and

producing a mixture from the formation through a production well, wherein the production well is located such that a majority of the mixture produced from the formation comprises non-condensable hydrocarbons and a non-condensable component comprising hydrogen.

2659. The method of claim 2658, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2660. The method of claim 2658, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2661. The method of claim 2658, wherein the production well is less than approximately 6 m from a heat source of the one or more heat sources.

2662. The method of claim 2658, wherein the production well is less than approximately 3 m from a heat source of the one or more heat sources.

2663. The method of claim 2658, wherein the production well is less than approximately 1.5 m from a heat source of the one or more heat sources.

2664. The method of claim 2658, wherein an additional heat source is positioned within a wellbore of the production well.

2665. The method of claim 2658, wherein the one or more heat sources comprise electrical heaters.

2666. The method of claim 2658, wherein the one or more heat sources comprise surface burners.

2667. The method of claim 2658, wherein the one or more heat sources comprise flameless distributed combustors.

2668. The method of claim 2658, wherein the one or more heat sources comprise natural distributed combustors.

2669. The method of claim 2658; further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2670. The method of claim 2658, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2671. The method of claim 2658, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than Pwr , wherein Pwr is calculated by the equation:

$$Pwr = h * V * C_v * \rho_B$$

wherein Pwr is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2672. The method of claim 2658, wherein allowing the heat to transfer from the one or more heat sources to the selected section comprises transferring heat substantially by conduction.

2673. The method of claim 2658, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

5 2674. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2675. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the
10 condensable hydrocarbons are olefins.

2676. The method of claim 2658, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2677. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2678. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2679. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic
25 basis, of the condensable hydrocarbons is sulfur.

2680. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen
30 containing compounds comprise phenols.

2681. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2682. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2683. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2684. The method of claim 2658, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2685. The method of claim 2658, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2686. The method of claim 2658, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2687. The method of claim 2658, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2688. The method of claim 2658, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2689. The method of claim 2658, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H₂ within the mixture is greater than about 0.5 bar.

2690. The method of claim 2689, wherein the partial pressure of H₂ within the mixture is measured when the mixture is at a production well.

2691. The method of claim 2658, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2692. The method of claim 2658, further comprising controlling formation conditions by recirculating a portion of the hydrogen from the mixture into the formation.

2693. The method of claim 2658, further comprising:
providing hydrogen (H₂) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

2694. The method of claim 2658, further comprising:
producing condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2695. The method of claim 2658, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2696. The method of claim 2658, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

2697. The method of claim 2658, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2698. The method of claim 2658, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.

2699. The method of claim 2658, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2700. The method of claim 2658, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2701. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat to at least a portion of the formation from one or more first heat sources placed within a pattern in the formation;

allowing the heat to transfer from the one or more first heat sources to a first section of the formation;

heating a second section of the formation with at least one second heat source, wherein the second section is located within the first section, and wherein at least the one second heat source is configured to raise an average temperature of a portion of the second section to a higher temperature than an average temperature of the first section;

and

producing a mixture from the formation through a production well positioned within the second section, wherein a majority of the produced mixture comprises non-condensable hydrocarbons and a non-condensable component comprising H₂ components.

2702. The method of claim 2701, wherein the one or more first heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the first section of the formation.

2703. The method of claim 2701, further comprising maintaining a temperature within the first section within a pyrolysis temperature range.

2704. The method of claim 2701, wherein at least the one heat source comprises a heater element positioned within the production well.

2705. The method of claim 2701, wherein at least the one second heat source comprises an electrical heater.

2706. The method of claim 2701, wherein at least the one second heat source comprises a surface burner.

2707. The method of claim 2701, wherein at least the one second heat source comprises a flameless distributed combustor.

2708. The method of claim 2701, wherein at least the one second heat source comprises a natural distributed combustor.

2709. The method of claim 2701, further comprising controlling a pressure and a temperature within at least a majority of the first or the second section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2710. The method of claim 2701, further comprising controlling the heat such that an average heating rate of the first section is less than about 1 °C per day during pyrolysis.

2711. The method of claim 2701, wherein providing heat to the formation further comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more first heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2712. The method of claim 2701, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2713. The method of claim 2701, wherein providing heat from the one or more first heat sources comprises heating the first section such that a thermal conductivity of at least a portion of the first section is greater than about 0.5 W/(m °C).

2714. The method of claim 2701, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2715. The method of claim 2701, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2716. ~~The method of claim 2701, wherein a molar ratio of ethene to ethane in the non-~~
condensable hydrocarbons ranges from about 0.001 to about 0.15.

2717. The method of claim 2701, wherein the produced mixture comprises condensable
hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic
basis, of the condensable hydrocarbons is nitrogen.

2718. The method of claim 2701, wherein the produced mixture comprises condensable
hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic
basis, of the condensable hydrocarbons is oxygen.

2719. The method of claim 2701, wherein the produced mixture comprises condensable
hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic
basis, of the condensable hydrocarbons is sulfur.

2720. The method of claim 2701, wherein the produced mixture comprises condensable
hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable
hydrocarbons comprise oxygen containing compounds, and wherein the oxygen
containing compounds comprise phenols.

2721. The method of claim 2701, wherein the produced mixture comprises condensable
hydrocarbons, and wherein greater than about 20 % by weight of the condensable
hydrocarbons are aromatic compounds.

2722. The method of claim 2701, wherein the produced mixture comprises condensable
hydrocarbons, and wherein less than about 5 % by weight of the condensable
hydrocarbons comprises multi-ring aromatics with more than two rings.

2723. The method of claim 2701, wherein the produced mixture comprises condensable
hydrocarbons, and wherein less than about 0.5 % by weight of the condensable
hydrocarbons are asphaltenes.

2724. The method of claim 2701, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2725. The method of claim 2701, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2726. The method of claim 2701, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2727. The method of claim 2701, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2728. The method of claim 2701, further comprising controlling a pressure within at least a majority of the first or the second section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2729. The method of claim 2701, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2730. The method of claim 2729, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2731. The method of claim 2701, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2732. The method of claim 2701, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2733. The method of claim 2701, further comprising:
providing hydrogen (H_2) to the first or second section to hydrogenate hydrocarbons within the first or second section, respectively; and
heating a portion of the first or second section, respectively, with heat from hydrogenation.

2734. The method of claim 2701, further comprising:
producing condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2735. The method of claim 2701, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the first or second section to greater than about 100 millidarcy.

2736. The method of claim 2701, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the first or second section.

2737. The method of claim 2701, wherein heating the first or the second section is controlled to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2738. The method of claim 2701, wherein at least about 7 heat sources are disposed in the formation for each production well.

2739. The method of claim 2701, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2740. The method of claim 2701, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2741. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat into the formation from a plurality of heat sources placed in a pattern within the formation, wherein a spacing between heat sources is greater than about 6 m;
allowing the heat to transfer from the plurality of heat sources to a selected section of the formation;
producing a mixture from the formation from a plurality of production wells, wherein the plurality of production wells are positioned within the pattern, and wherein a spacing between production wells is greater than about 12 m.

2742. The method of claim 2741, wherein superposition of heat from the plurality of heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2743. The method of claim 2741, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2744. The method of claim 2741, wherein the plurality of heat sources comprises electrical heaters.

2745. The method of claim 2741, wherein the plurality of heat sources comprises surface burners.

2746. The method of claim 2741, wherein the plurality of heat sources comprises flameless distributed combustors.

2747. The method of claim 2741, wherein the plurality of heat sources comprises natural distributed combustors.

2748. The method of claim 2741, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

2749. The method of claim 2741, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

2750. The method of claim 2741, wherein providing heat from the plurality of heat comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the plurality of heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2751. The method of claim 2741, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

2752. The method of claim 2741, wherein providing heat comprises heating the selected formation such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

2753. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

2754. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

2755. The method of claim 2741, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

2756. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

2757. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

2758. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

2759. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

2760. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

2761. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

2762. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

2763. The method of claim 2741, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

2764. The method of claim 2741, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable component, and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

2765. The method of claim 2741, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

2766. The method of claim 2741, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

2767. The method of claim 2741, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

2768. The method of claim 2741, further comprising controlling formation conditions to produce the mixture, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.

2769. The method of claim 2768, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.

2770. The method of claim 2741, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

2771. The method of claim 2741, further comprising controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.

2772. The method of claim 2741, further comprising:
providing hydrogen (H_2) to the selected section to hydrogenate hydrocarbons within the selected section; and
heating a portion of the selected section with heat from hydrogenation.

2773. The method of claim 2741, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

2774. The method of claim 2741, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

2775. The method of claim 2741, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

2776. The method of claim 2741, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

2777. The method of claim 2741, wherein at least about 7 heat sources are disposed in the formation for each production well.

2778. The method of claim 2741, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

2779. The method of claim 2741, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

2780. A system configured to heat a hydrocarbon containing formation, comprising:
a heater disposed in an opening in the formation, wherein the heater is configured to provide heat to at least a portion of the formation during use;
an oxidizing fluid source;
a conduit disposed in the opening, wherein the conduit is configured to provide an oxidizing fluid from the oxidizing fluid source to a reaction zone in the formation during

use, and wherein the oxidizing fluid is selected to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is configured to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

5 2781. The system of claim 2780, wherein the oxidizing fluid is configured to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

10 2782. The system of claim 2780, wherein the conduit comprises orifices, and wherein the orifices are configured to provide the oxidizing fluid into the opening.

15 2783. The system of claim 2780, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configured to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

20 2784. The system of claim 2780, wherein the conduit is further configured to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

25 2785. The system of claim 2780, wherein the conduit is further configured to remove an oxidation product.

30 2786. The system of claim 2780, wherein the conduit is further configured to remove an oxidation product such that the oxidation product transfers substantial heat to the oxidizing fluid.

2787. The system of claim 2780, wherein the conduit is further configured to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

2788. The system of claim 2780, wherein the conduit is further configured to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

2789. The system of claim 2780, wherein the conduit is further configured to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2790. The system of claim 2780, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2791. The system of claim 2780, further comprising a center conduit disposed within the conduit, wherein the center conduit is configured to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configured to remove an oxidation product during use.

2792. The system of claim 2780, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2793. The system of claim 2780, further comprising a conductor disposed in a second conduit, wherein the second conduit is disposed within the opening, and wherein the conductor is configured to heat at least a portion of the formation during application of an electrical current to the conductor.

2794. The system of claim 2780, further comprising an insulated conductor disposed within the opening, wherein the insulated conductor is configured to heat at least a portion of the formation during application of an electrical current to the insulated conductor.

09841437 042400

2795. ~~The system of claim 2780, further comprising at least one elongated member~~
disposed within the opening, wherein the at least the one elongated member is configured
to heat at least a portion of the formation during application of an electrical current to the
at least the one elongated member.

2796. The system of claim 2780, further comprising a heat exchanger disposed external
to the formation, wherein the heat exchanger is configured to heat the oxidizing fluid,
wherein the conduit is further configured to provide the heated oxidizing fluid into the
opening during use, and wherein the heated oxidizing fluid is configured to heat at least a
portion of the formation during use.

2797. The system of claim 2780, further comprising an overburden casing coupled to
the opening, wherein the overburden casing is disposed in an overburden of the
formation.

2798. The system of claim 2780, further comprising an overburden casing coupled to
the opening, wherein the overburden casing is disposed in an overburden of the
formation, and wherein the overburden casing comprises steel.

2799. The system of claim 2780, further comprising an overburden casing coupled to
the opening, wherein the overburden casing is disposed in an overburden of the
formation, and wherein the overburden casing is further disposed in cement.

2800. The system of claim 2780, further comprising an overburden casing coupled to
the opening, wherein a packing material is disposed at a junction of the overburden
casing and the opening.

2801. The system of claim 2780, further comprising an overburden casing coupled to
the opening, wherein the overburden casing is disposed in an overburden of the
formation, wherein a packing material is disposed at a junction of the overburden casing

and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

2802. The system of claim 2780, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

2803. The system of claim 2780, wherein the system is further configured such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

2804. A system configurable to heat a hydrocarbon containing formation, comprising:
a heater configurable to be disposed in an opening in the formation, wherein the heater is further configurable to provide heat to at least a portion of the formation during use;

a conduit configurable to be disposed in the opening, wherein the conduit is configurable to provide an oxidizing fluid from an oxidizing fluid source to a reaction zone in the formation during use, and wherein the system is configurable to allow the oxidizing fluid to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is further configurable to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

2805. The system of claim 2804, wherein the oxidizing fluid is configurable to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

2806. The system of claim 2804, wherein the conduit comprises orifices, and wherein the orifices are configurable to provide the oxidizing fluid into the opening.

09841437 042401

2807. The system of claim 2804, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configurable to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

5 2808. The system of claim 2804, wherein the conduit is further configurable to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

10 2809. The system of claim 2804, wherein the conduit is further configurable to remove an oxidation product.

2810. The system of claim 2804, wherein the conduit is further configurable to remove an oxidation product, such that the oxidation product transfers heat to the oxidizing fluid.

5 2811. The system of claim 2804, wherein the conduit is further configurable to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

20 2812. The system of claim 2804, wherein the conduit is further configurable to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

25 2813. The system of claim 2804, wherein the conduit is further configurable to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

30 2814. The system of claim 2804, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2815. The system of claim 2804, further comprising a center conduit disposed within the conduit, wherein center conduit is configurable to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configurable to remove an oxidation product during use.

2816. The system of claim 2804, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2817. The system of claim 2804, further comprising a conductor disposed in a second conduit, wherein the second conduit is disposed within the opening, and wherein the conductor is configurable to heat at least a portion of the formation during application of an electrical current to the conductor.

2818. The system of claim 2804, further comprising an insulated conductor disposed within the opening, wherein the insulated conductor is configurable to heat at least a portion of the formation during application of an electrical current to the insulated conductor.

2819. The system of claim 2804, further comprising at least one elongated member disposed within the opening, wherein the at least the one elongated member is configurable to heat at least a portion of the formation during application of an electrical current to the at least the one elongated member.

2820. The system of claim 2804, further comprising a heat exchanger disposed external to the formation, wherein the heat exchanger is configurable to heat the oxidizing fluid, wherein the conduit is further configurable to provide the heated oxidizing fluid into the opening during use, and wherein the heated oxidizing fluid is configurable to heat at least a portion of the formation during use.

2821. The system of claim 2804, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2822. The system of claim 2804, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2823. The system of claim 2804, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2824. The system of claim 2804, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2825. The system of claim 2804, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

2826. The system of claim 2804, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

2827. The system of claim 2804, wherein the system is further configurable such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

2828. An in situ method for heating a hydrocarbon containing formation, comprising:

heating a portion of the formation to a temperature sufficient to support reaction of hydrocarbons within the portion of the formation with an oxidizing fluid;

providing the oxidizing fluid to a reaction zone in the formation;

allowing the oxidizing fluid to react with at least a portion of the hydrocarbons at the reaction zone to generate heat at the reaction zone; and

transferring the generated heat substantially by conduction from the reaction zone to a pyrolysis zone in the formation.

2829. The method of claim 2828, further comprising transporting the oxidizing fluid through the reaction zone by diffusion.

2830. The method of claim 2828, further comprising directing at least a portion of the oxidizing fluid into the opening through orifices of a conduit disposed in the opening.

2831. The method of claim 2828, further comprising controlling a flow of the oxidizing fluid with critical flow orifices of a conduit disposed in the opening such that a rate of oxidation is controlled.

2832. The method of claim 2828, further comprising increasing a flow of the oxidizing fluid in the opening to accommodate an increase in a volume of the reaction zone such that a rate of oxidation is substantially constant over time within the reaction zone.

2833. The method of claim 2828, wherein a conduit is disposed in the opening, the method further comprising cooling the conduit with the oxidizing fluid to reduce heating of the conduit by oxidation.

2834. The method of claim 2828, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit.

2835. The method of claim 2828, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and transferring heat from the oxidation product in the conduit to oxidizing fluid in the conduit.

2836. The method of claim 2828, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

2837. The method of claim 2828, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and controlling a pressure between the oxidizing fluid and the oxidation product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

2838. The method of claim 2828, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and substantially inhibiting the oxidation product from flowing into portions of the formation beyond the reaction zone.

2839. The method of claim 2828, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.

2840. The method of claim 2828, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the outer conduit.

2841. The method of claim 2828, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2842. The method of claim 2828, wherein heating the portion comprises applying electrical current to a conductor disposed in a conduit, wherein the conduit is disposed within the opening.

2843. The method of claim 2828, wherein heating the portion comprises applying electrical current to an insulated conductor disposed within the opening.

2844. The method of claim 2828, wherein heating the portion comprises applying electrical current to at least one elongated member disposed within the opening.

2845. The method of claim 2828, wherein heating the portion comprises heating the oxidizing fluid in a heat exchanger disposed external to the formation such that providing the oxidizing fluid into the opening comprises transferring heat from the heated oxidizing fluid to the portion.

2846. The method of claim 2828, further comprising removing water from the formation prior to heating the portion.

2847. The method of claim 2828, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

2848. The method of claim 2828, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2849. The method of claim 2828, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

FOOTNOTES

2850. The method of claim 2828, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2851. The method of claim 2828, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2852. The method of claim 2828, wherein the pyrolysis zone is substantially adjacent to the reaction zone

2853. A system configured to heat a hydrocarbon containing formation, comprising:
a heater disposed in an opening in the formation, wherein the heater is configured to provide heat to at least a portion of the formation during use;
an oxidizing fluid source;
a conduit disposed in the opening, wherein the conduit is configured to provide an oxidizing fluid from the oxidizing fluid source to a reaction zone in the formation during use, wherein the oxidizing fluid is selected to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone, and wherein the conduit is further configured to remove an oxidation product from the formation during use; and

wherein the system is configured to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

2854. The system of claim 2853, wherein the oxidizing fluid is configured to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

2855. The system of claim 2853, wherein the conduit comprises orifices, and wherein the orifices are configured to provide the oxidizing fluid into the opening.

2856. The system of claim 2853, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configured to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

2857. The system of claim 2853, wherein the conduit is further configured to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

2858. The system of claim 2853, wherein the conduit is further configured such that the oxidation product transfers heat to the oxidizing fluid.

2859. The system of claim 2853, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

2860. The system of claim 2853, wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

2861. The system of claim 2853, wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2862. The system of claim 2853, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2863. The system of claim 2853, further comprising a center conduit disposed within the conduit, wherein the center conduit is configured to provide the oxidizing fluid into the opening during use.

2864. The system of claim 2853, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2865. The system of claim 2853, further comprising a conductor disposed in a second conduit, wherein the second conduit is disposed within the opening, and wherein the conductor is configured to heat at least a portion of the formation during application of an electrical current to the conductor.

2866. The system of claim 2853, further comprising an insulated conductor disposed within the opening, wherein the insulated conductor is configured to heat at least a portion of the formation during application of an electrical current to the insulated conductor.

2867. The system of claim 2853, further comprising at least one elongated member disposed within the opening, wherein the at least the one elongated member is configured to heat at least a portion of the formation during application of an electrical current to the at least the one elongated member.

2868. The system of claim 2853, further comprising a heat exchanger disposed external to the formation, wherein the heat exchanger is configured to heat the oxidizing fluid, wherein the conduit is further configured to provide the heated oxidizing fluid into the opening during use, and wherein the heated oxidizing fluid is configured to heat at least a portion of the formation during use.

2869. The system of claim 2853, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2870. The system of claim 2853, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2871. The system of claim 2853, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2872. The system of claim 2853, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2873. The system of claim 2853, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

2874. The system of claim 2853, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

2875. The system of claim 2853, wherein the system is further configured such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

2876. A system configurable to heat a hydrocarbon containing formation, comprising:
a heater configurable to be disposed in an opening in the formation, wherein the heater is further configurable to provide heat to at least a portion of the formation during use;

a conduit configurable to be disposed in the opening, wherein the conduit is further configurable to provide an oxidizing fluid from an oxidizing fluid source to a reaction zone in the formation during use, wherein the system is configurable to allow the oxidizing fluid to oxidize at least some hydrocarbons at the reaction zone during use such

that heat is generated at the reaction zone, and wherein the conduit is further configurable to remove an oxidation product from the formation during use; and

wherein the system is further configurable to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone during use.

2877. The system of claim 2876, wherein the oxidizing fluid is configurable to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

2878. The system of claim 2876, wherein the conduit comprises orifices, and wherein the orifices are configurable to provide the oxidizing fluid into the opening.

2879. The system of claim 2876, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configurable to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

2880. The system of claim 2876, wherein the conduit is further configurable to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

2881. The system of claim 2876, wherein the conduit is further configurable such that the oxidation product transfers heat to the oxidizing fluid.

2882. The system of claim 2876, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

2883. The system of claim 2876, wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

0984-1437-042401

opening during use, and wherein the heated oxidizing fluid is configurable to heat at least a portion of the formation during use.

2892. The system of claim 2876, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2893. The system of claim 2876, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2894. The system of claim 2876, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2895. The system of claim 2876, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2896. The system of claim 2876, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

2897. The system of claim 2876, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

2898. The system of claim 2876, wherein the system is further configurable such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

2899. An in situ method for heating a hydrocarbon containing formation, comprising:
heating a portion of the formation to a temperature sufficient to support reaction of
hydrocarbons within the portion of the formation with an oxidizing fluid, wherein the
portion is located substantially adjacent to an opening in the formation;

providing the oxidizing fluid to a reaction zone in the formation;

allowing the oxidizing gas to react with at least a portion of the hydrocarbons at
the reaction zone to generate heat in the reaction zone;

removing at least a portion of an oxidation product through the opening; and

transferring the generated heat substantially by conduction from the reaction zone
to a pyrolysis zone in the formation.

2900. The method of claim 2899, further comprising transporting the oxidizing fluid
through the reaction zone by diffusion.

2901. The method of claim 2899, further comprising directing at least a portion of the
oxidizing fluid into the opening through orifices of a conduit disposed in the opening.

2902. The method of claim 2899, further comprising controlling a flow of the oxidizing
fluid with critical flow orifices of a conduit disposed in the opening such that a rate of
oxidation is controlled.

2903. The method of claim 2899, further comprising increasing a flow of the oxidizing
fluid in the opening to accommodate an increase in a volume of the reaction zone such
that a rate of oxidation is substantially maintained within the reaction zone.

2904. The method of claim 2899, wherein a conduit is disposed in the opening, the
method further comprising cooling the conduit with the oxidizing fluid such that the
conduit is not substantially heated by oxidation.

2905. The method of claim 2899, wherein a conduit is disposed within the opening, and wherein removing at least the portion of the oxidation product through the opening comprises removing at least the portion of the oxidation product through the conduit.

2906. The method of claim 2899, wherein a conduit is disposed within the opening, and wherein removing at least the portion of the oxidation product through the opening comprises removing at least the portion of the oxidation product through the conduit, the method further comprising transferring substantial heat from the oxidation product in the conduit to the oxidizing fluid in the conduit.

2907. The method of claim 2899, wherein a conduit is disposed within the opening, wherein removing at least the portion of the oxidation product through the opening comprises removing at least the portion of the oxidation product through the conduit, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

2908. The method of claim 2899, wherein a conduit is disposed within the opening, and wherein removing at least the portion of the oxidation product through the opening comprises removing at least the portion of the oxidation product through the conduit, the method further comprising controlling a pressure between the oxidizing fluid and the oxidation product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

2909. The method of claim 2899, wherein a conduit is disposed within the opening, and wherein removing at least the portion of the oxidation product through the opening comprises removing at least the portion of the oxidation product through the conduit, the method further comprising substantially inhibiting the oxidation product from flowing into portions of the formation beyond the reaction zone.

2910. The method of claim 2899, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.

2911. The method of claim 2899, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing at least a portion of the oxidation product through the outer conduit.

2912. The method of claim 2899, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2913. The method of claim 2899, wherein heating the portion comprises applying electrical current to a conductor disposed in a conduit, wherein the conduit is disposed within the opening.

2914. The method of claim 2899, wherein heating the portion comprises applying electrical current to an insulated conductor disposed within the opening.

2915. The method of claim 2899, wherein heating the portion comprises applying electrical current to at least one elongated member disposed within the opening.

2916. The method of claim 2899, wherein heating the portion comprises heating the oxidizing fluid in a heat exchanger disposed external to the formation such that providing the oxidizing fluid into the opening comprises transferring heat from the heated oxidizing fluid to the portion.

2917. The method of claim 2899, further comprising removing water from the formation prior to heating the portion.

2918. The method of claim 2899, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

2919. The method of claim 2899, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2920. The method of claim 2899, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2921. The method of claim 2899, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2922. The method of claim 2899, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2923. The method of claim 2899, wherein the pyrolysis zone is substantially adjacent to the reaction.

2924. A system configured to heat a hydrocarbon containing formation, comprising:
an electric heater disposed in an opening in the formation, wherein the electric heater is configured to provide heat to at least a portion of the formation during use;
an oxidizing fluid source;
a conduit disposed in the opening, wherein the conduit is configured to provide an oxidizing fluid from the oxidizing fluid source to a reaction zone in the formation during use, and wherein the oxidizing fluid is selected to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and
wherein the system is configured to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

2925. The system of claim 2924, wherein the oxidizing fluid is configured to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

2926. The system of claim 2924, wherein the conduit comprises orifices, and wherein the orifices are configured to provide the oxidizing fluid into the opening.

2927. The system of claim 2924, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configured to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

2928. The system of claim 2924, wherein the conduit is further configured to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

2929. The system of claim 2924, wherein the conduit is further configured to remove an oxidation product.

2930. The system of claim 2924, wherein the conduit is further configured to remove an oxidation product, such that the oxidation product transfers heat to the oxidizing fluid.

2931. The system of claim 2924, wherein the conduit is further configured to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

2932. The system of claim 2924, wherein the conduit is further configured to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

2933. The system of claim 2924, wherein the conduit is further configured to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2934. The system of claim 2924, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2935. The system of claim 2924, further comprising a center conduit disposed within the conduit, wherein the center conduit is configured to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configured to remove an oxidation product during use.

2936. The system of claim 2924, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2937. The system of claim 2924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2938. The system of claim 2924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2939. The system of claim 2924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2940. The system of claim 2924, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2941. The system of claim 2924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

2942. The system of claim 2924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

2943. The system of claim 2924, wherein the system is further configured such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

2944. A system configurable to heat a hydrocarbon containing formation, comprising: an electric heater configurable to be disposed in an opening in the formation, wherein the electric heater is further configurable to provide heat to at least a portion of the formation during use, and wherein at least the portion is located substantially adjacent to the opening;

a conduit configurable to be disposed in the opening, wherein the conduit is further configurable to provide an oxidizing fluid from an oxidizing fluid source to a reaction zone in the formation during use, and wherein the system is configurable to allow the oxidizing fluid to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is further configurable to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

2945. The system of claim 2944, wherein the oxidizing fluid is configurable to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

2946. The system of claim 2944, wherein the conduit comprises orifices, and wherein the orifices are configurable to provide the oxidizing fluid into the opening.

2947. The system of claim 2944, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configurable to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

2948. The system of claim 2944, wherein the conduit is further configurable to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

2949. The system of claim 2944, wherein the conduit is further configurable to remove an oxidation product.

2950. The system of claim 2944, wherein the conduit is further configurable to remove an oxidation product such that the oxidation product transfers heat to the oxidizing fluid.

2951. The system of claim 2944, wherein the conduit is further configurable to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

2952. The system of claim 2944, wherein the conduit is further configurable to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

2953. The system of claim 2944, wherein the conduit is further configurable to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2954. The system of claim 2944, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2955. The system of claim 2944, further comprising a center conduit disposed within the conduit, wherein center conduit is configurable to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configurable to remove an oxidation product during use.

2956. The system of claim 2944, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2957. The system of claim 2944, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2958. The system of claim 2944, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2959. The system of claim 2944, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2960. The system of claim 2944, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2961. The system of claim 2944, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing

and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

2962. The system of claim 2944, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

2963. The system of claim 2944, wherein the system is further configurable such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

2964. A system configured to heat a hydrocarbon containing formation, comprising:
a conductor disposed in a first conduit, wherein the first conduit is disposed in an opening in the formation, and wherein the conductor is configured to provide heat to at least a portion of the formation during use;
an oxidizing fluid source;
a second conduit disposed in the opening, wherein the second conduit is configured to provide an oxidizing fluid from the oxidizing fluid source to a reaction zone in the formation during use, and wherein the oxidizing fluid is selected to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is configured to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

2965. The system of claim 2964, wherein the oxidizing fluid is configured to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

2966. The system of claim 2964, wherein the second conduit comprises orifices, and wherein the orifices are configured to provide the oxidizing fluid into the opening.

2967. The system of claim 2964, wherein the second conduit comprises critical flow orifices, and wherein the critical flow orifices are configured to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

2968. The system of claim 2964, wherein the second conduit is further configured to be cooled with the oxidizing fluid to reduce heating of the second conduit by oxidation.

2969. The system of claim 2964, wherein the second conduit is further configured to remove an oxidation product.

2970. The system of claim 2964, wherein the second conduit is further configured to remove an oxidation product such that the oxidation product transfers heat to the oxidizing fluid.

2971. The system of claim 2964, wherein the second conduit is further configured to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the second conduit.

2972. The system of claim 2964, wherein the second conduit is further configured to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the second conduit and a pressure of the oxidation product in the second conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

2973. The system of claim 2964, wherein the second conduit is further configured to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2974. The system of claim 2964, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

FORMATION ZONE

2975. The system of claim 2964, further comprising a center conduit disposed within the second conduit, wherein the center conduit is configured to provide the oxidizing fluid into the opening during use, and wherein the second conduit is further configured to remove an oxidation product during use.

2976. The system of claim 2964, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2977. The system of claim 2964, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2978. The system of claim 2964, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2979. The system of claim 2964, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

2980. The system of claim 2964, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

2981. The system of claim 2964, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

2982. The system of claim 2964, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

2983. The system of claim 2964, wherein the system is further configured such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

2984. A system configurable to heat a hydrocarbon containing formation, comprising:
a conductor configurable to be disposed in a first conduit, wherein the first conduit is configurable to be disposed in an opening in the formation, and wherein the conductor is further configurable to provide heat to at least a portion of the formation during use;

a second conduit configurable to be disposed in the opening, wherein the second conduit is further configurable to provide an oxidizing fluid from an oxidizing fluid source to a reaction zone in the formation during use, and wherein the system is configurable to allow the oxidizing fluid to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is further configurable to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

2985. The system of claim 2984, wherein the oxidizing fluid is configurable to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

2986. The system of claim 2984, wherein the second conduit comprises orifices, and wherein the orifices are configurable to provide the oxidizing fluid into the opening.

2987. The system of claim 2984, wherein the second conduit comprises critical flow orifices, and wherein the critical flow orifices are configurable to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

2988. The system of claim 2984, wherein the second conduit is further configurable to be cooled with the oxidizing fluid to reduce heating of the second conduit by oxidation.

5 2989. The system of claim 2984, wherein the second conduit is further configurable to remove an oxidation product.

10 2990. The system of claim 2984, wherein the second conduit is further configurable to remove an oxidation product such that the oxidation product transfers heat to the oxidizing fluid.

15 2991. The system of claim 2984, wherein the second conduit is further configurable to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the second conduit.

20 2992. The system of claim 2984, wherein the second conduit is further configurable to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the second conduit and a pressure of the oxidation product in the second conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

25 2993. The system of claim 2984, wherein the second conduit is further configurable to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

30 2994. The system of claim 2984, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

2995. The system of claim 2984, further comprising a center conduit disposed within the second conduit, wherein center conduit is configurable to provide the oxidizing fluid into the opening during use, and wherein the second conduit is further configurable to remove an oxidation product during use.

2996. The system of claim 2984, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

2997. The system of claim 2984, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

2998. The system of claim 2984, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

2999. The system of claim 2984, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3000. The system of claim 2984, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3001. The system of claim 2984, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3002. The system of claim 2984, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3003. The system of claim 2984, wherein the system is further configurable such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

3004. An in situ method for heating a hydrocarbon containing formation, comprising:
5 heating a portion of the formation to a temperature sufficient to support reaction of hydrocarbons within the portion of the formation with an oxidizing fluid, wherein heating comprises applying an electrical current to a conductor disposed in a first conduit to provide heat to the portion, and wherein the first conduit is disposed within the opening;

10 providing the oxidizing fluid to a reaction zone in the formation;
allowing the oxidizing fluid to react with at least a portion of the hydrocarbons at the reaction zone to generate heat at the reaction zone; and
transferring the generated heat substantially by conduction from the reaction zone to a pyrolysis zone in the formation.

15 3005. The method of claim 3004, further comprising transporting the oxidizing fluid through the reaction zone by diffusion.

20 3006. The method of claim 3004, further comprising directing at least a portion of the oxidizing fluid into the opening through orifices of a second conduit disposed in the opening.

25 3007. The method of claim 3004, further comprising controlling a flow of the oxidizing fluid with critical flow orifices of a second conduit disposed in the opening such that a rate of oxidation is controlled.

30 3008. The method of claim 3004, further comprising increasing a flow of the oxidizing fluid in the opening to accommodate an increase in a volume of the reaction zone such that a rate of oxidation is substantially constant over time within the reaction zone.

3009. The method of claim 3004, wherein a second conduit is disposed in the opening, the method further comprising cooling the second conduit with the oxidizing fluid to reduce heating of the second conduit by oxidation.

5 3010. The method of claim 3004, wherein a second conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the second conduit.

10 3011. The method of claim 3004, wherein a second conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the second conduit and transferring heat from the oxidation product in the conduit to the oxidizing fluid in the second conduit.

15 3012. The method of claim 3004, wherein a second conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the second conduit, wherein a flow rate of the oxidizing fluid in the second conduit is approximately equal to a flow rate of the oxidation product in the second conduit.

20 3013. The method of claim 3004, wherein a second conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the second conduit and controlling a pressure between the oxidizing fluid and the oxidation product in the second conduit to reduce contamination of the oxidation product by the oxidizing fluid.

25 3014. The method of claim 3004, wherein a second conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and substantially inhibiting the oxidation product from flowing into portions of the formation beyond the reaction zone.

3015. The method of claim 3004, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.

3016. The method of claim 3004, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the outer conduit.

3017. The method of claim 3004, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3018. The method of claim 3004, further comprising removing water from the formation prior to heating the portion.

3019. The method of claim 3004, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

3020. The method of claim 3004, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3021. The method of claim 3004, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3022. The method of claim 3004, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3023. The method of claim 3004, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3024. A system configured to heat a hydrocarbon containing formation, comprising:
an insulated conductor disposed in an opening in the formation, wherein the insulated conductor is configured to provide heat to at least a portion of the formation during use;

an oxidizing fluid source;

a conduit disposed in the opening, wherein the conduit is configured to provide an oxidizing fluid from the oxidizing fluid source to a reaction zone in the formation during use, and wherein the oxidizing fluid is selected to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is configured to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

3025. The system of claim 3024, wherein the oxidizing fluid is configured to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

3026. The system of claim 3024, wherein the conduit comprises orifices, and wherein the orifices are configured to provide the oxidizing fluid into the opening.

3027. The system of claim 3024, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configured to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

3028. The system of claim 3024, wherein the conduit is configured to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

3029. The system of claim 3024, wherein the conduit is further configured to remove an oxidation product.

3030. The system of claim 3024, wherein the conduit is further configured to remove an oxidation product, and wherein the conduit is further configured such that the oxidation product transfers substantial heat to the oxidizing fluid.

3031. The system of claim 3024, wherein the conduit is further configured to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3032. The system of claim 3024, wherein the conduit is further configured to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the second conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

3033. The system of claim 3024, wherein the conduit is further configured to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3034. The system of claim 3024, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3035. The system of claim 3024, further comprising a center conduit disposed within the conduit, wherein the center conduit is configured to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configured to remove an oxidation product during use.

3036. The system of claim 3024, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3037. The system of claim 3024, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

5 3038. The system of claim 3024, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

10 3039. The system of claim 3024, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

15 3040. The system of claim 3024, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

20 3041. The system of claim 3024, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

25 3042. The system of claim 3024, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

30 3043. The system of claim 3024, wherein the system is further configured such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

3044. A system configurable to heat a hydrocarbon containing formation, comprising:

an insulated conductor configurable to be disposed in an opening in the formation, wherein the insulated conductor is further configurable to provide heat to at least a portion of the formation during use;

a conduit configurable to be disposed in the opening, wherein the conduit is further configurable to provide an oxidizing fluid from an oxidizing fluid source to a reaction zone in the formation during use, and wherein the system is configurable to allow the oxidizing fluid to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is further configurable to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

3045. The system of claim 3044, wherein the oxidizing fluid is configurable to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

3046. The system of claim 3044, wherein the conduit comprises orifices, and wherein the orifices are configurable to provide the oxidizing fluid into the opening.

3047. The system of claim 3044, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configurable to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

3048. The system of claim 3044, wherein the conduit is further configurable to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

3049. The system of claim 3044, wherein the conduit is further configurable to remove an oxidation product.

3050. The system of claim 3044, wherein the conduit is further configurable to remove an oxidation product, such that the oxidation product transfers heat to the oxidizing fluid.

09041430
104270" 2E-41860

3051. The system of claim 3044, wherein the conduit is further configurable to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3052. The system of claim 3044, wherein the conduit is further configurable to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

3053. The system of claim 3044, wherein the conduit is further configurable to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3054. The system of claim 3044, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3055. The system of claim 3044, further comprising a center conduit disposed within the conduit, wherein center conduit is configurable to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configurable to remove an oxidation product during use.

3056. The system of claim 3044, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3057. The system of claim 3044, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3058. The system of claim 3044, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3059. The system of claim 3044, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3060. The system of claim 3044, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3061. The system of claim 3044, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3062. The system of claim 3044, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3063. The system of claim 3044, wherein the system is further configurable such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

3064. An in situ method for heating a hydrocarbon containing formation, comprising:
heating a portion of the formation to a temperature sufficient to support reaction of hydrocarbons within the portion of the formation with an oxidizing fluid, wherein heating comprises applying an electrical current to an insulated conductor to provide heat to the portion, and wherein the insulated conductor is disposed within the opening;

providing the oxidizing fluid to a reaction zone in the formation;

allowing the oxidizing fluid to react with at least a portion of the hydrocarbons at the reaction zone to generate heat at the reaction zone; and

transferring the generated heat substantially by conduction from the reaction zone to a pyrolysis zone in the formation.

3065. The method of claim 3064, further comprising transporting the oxidizing fluid through the reaction zone by diffusion.

3066. The method of claim 3064, further comprising directing at least a portion of the oxidizing fluid into the opening through orifices of a conduit disposed in the opening.

3067. The method of claim 3064, further comprising controlling a flow of the oxidizing fluid with critical flow orifices of a conduit disposed in the opening such that a rate of oxidation is controlled.

3068. The method of claim 3064, further comprising increasing a flow of the oxidizing fluid in the opening to accommodate an increase in a volume of the reaction zone such that a rate of oxidation is substantially constant over time within the reaction zone.

3069. The method of claim 3064, wherein a conduit is disposed in the opening, the method further comprising cooling the conduit with the oxidizing fluid to reduce heating of the conduit by oxidation.

3070. The method of claim 3064, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit.

3071. The method of claim 3064, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through

the conduit and transferring heat from the oxidation product in the conduit to the oxidizing fluid in the conduit.

3072. The method of claim 3064, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3073. The method of claim 3064, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and controlling a pressure between the oxidizing fluid and the oxidation product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

3074. The method of claim 3064, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and substantially inhibiting the oxidation product from flowing into portions of the formation beyond the reaction zone.

3075. The method of claim 3064, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.

3076. The method of claim 3064, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the outer conduit.

3077. The method of claim 3064, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3078. The method of claim 3064, further comprising removing water from the formation prior to heating the portion.

3079. The method of claim 3064, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

3080. The method of claim 3064, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3081. The method of claim 3064, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3082. The method of claim 3064, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3083. The method of claim 3064, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3084. The method of claim 3064, wherein the pyrolysis zone is substantially adjacent to the reaction zone.

3085. An in situ method for heating a hydrocarbon containing formation, comprising:
heating a portion of the formation to a temperature sufficient to support reaction of hydrocarbons within the portion of the formation with an oxidizing fluid, wherein the portion is located substantially adjacent to an opening in the formation, wherein heating comprises applying an electrical current to an insulated conductor to provide heat to the

1094414360

portion, wherein the insulated conductor is coupled to a conduit, wherein the conduit comprises critical flow orifices, and wherein the conduit is disposed within the opening;

providing the oxidizing fluid to a reaction zone in the formation;

allowing the oxidizing fluid to react with at least a portion of the hydrocarbons at the reaction zone to generate heat at the reaction zone; and

transferring the generated heat substantially by conduction from the reaction zone to a pyrolysis zone in the formation.

3086. The method of claim 3085, further comprising transporting the oxidizing fluid through the reaction zone by diffusion.

3087. The method of claim 3085, further comprising controlling a flow of the oxidizing fluid with the critical flow orifices such that a rate of oxidation is controlled.

3088. The method of claim 3085, further comprising increasing a flow of the oxidizing fluid in the opening to accommodate an increase in a volume of the reaction zone such that a rate of oxidation is substantially constant over time within the reaction zone.

3089. The method of claim 3085, further comprising cooling the conduit with the oxidizing fluid to reduce heating of the conduit by oxidation.

3090. The method of claim 3085, further comprising removing an oxidation product from the formation through the conduit.

3091. The method of claim 3085, further comprising removing an oxidation product from the formation through the conduit and transferring heat from the oxidation product in the conduit to the oxidizing fluid in the conduit.

3092. The method of claim 3085, further comprising removing an oxidation product from the formation through the conduit, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3093. The method of claim 3085, further comprising removing an oxidation product from the formation through the conduit and controlling a pressure between the oxidizing fluid and the oxidation product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

3094. The method of claim 3085, further comprising removing an oxidation product from the formation through the conduit and substantially inhibiting the oxidation product from flowing into portions of the formation beyond the reaction zone.

3095. The method of claim 3085, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.

3096. The method of claim 3085, wherein a center conduit is disposed within the conduit, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the conduit.

3097. The method of claim 3085, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3098. The method of claim 3085, further comprising removing water from the formation prior to heating the portion.

3099. The method of claim 3085, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

3100. The method of claim 3085, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3101. The method of claim 3085, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

5 3102. The method of claim 3085, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

10 3103. The method of claim 3085, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

15 3104. The method of claim 3085, wherein the pyrolysis zone is substantially adjacent to the reaction zone.

20 3105. A system configured to heat a hydrocarbon containing formation, comprising:
at least one elongated member disposed in an opening in the formation, wherein at least the one elongated member is configured to provide heat to at least a portion of the formation during use;

25 an oxidizing fluid source;
a conduit disposed in the opening, wherein the conduit is configured to provide an oxidizing fluid from the oxidizing fluid source to a reaction zone in the formation during use, and wherein the oxidizing fluid is selected to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and
wherein the system is configured to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

30 3106. The system of claim 3105, wherein the oxidizing fluid is configured to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

3107. The system of claim 3105, wherein the conduit comprises orifices, and wherein the orifices are configured to provide the oxidizing fluid into the opening.

3108. The system of claim 3105, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configured to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

3109. The system of claim 3105, wherein the conduit is further configured to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

3110. The system of claim 3105, wherein the conduit is further configured to remove an oxidation product.

3111. The system of claim 3105, wherein the conduit is further configured to remove an oxidation product such that the oxidation product transfers heat to the oxidizing fluid.

3112. The system of claim 3105, wherein the conduit is further configured to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3113. The system of claim 3105, wherein the conduit is further configured to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

3114. The system of claim 3105, wherein the conduit is further configured to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3115. The system of claim 3105, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3116. The system of claim 3105, further comprising a center conduit disposed within the conduit, wherein the center conduit is configured to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configured to remove an oxidation product during use.

3117. The system of claim 3105, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3118. The system of claim 3105, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3119. The system of claim 3105, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3120. The system of claim 3105, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3121. The system of claim 3105, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3122. The system of claim 3105, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3123. The system of claim 3105, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3124. The system of claim 3105, wherein the system is further configured such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

3125. A system configurable to heat a hydrocarbon containing formation, comprising:
at least one elongated member configurable to be disposed in an opening in the formation, wherein at least the one elongated member is further configurable to provide heat to at least a portion of the formation during use;

a conduit configurable to be disposed in the opening, wherein the conduit is further configurable to provide an oxidizing fluid from the oxidizing fluid source to a reaction zone in the formation during use, and wherein the system is configurable to allow the oxidizing fluid to oxidize at least some hydrocarbons at the reaction zone during use such that heat is generated at the reaction zone; and

wherein the system is further configurable to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

3126. The system of claim 3125, wherein the oxidizing fluid is configurable to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

3127. The system of claim 3125, wherein the conduit comprises orifices, and wherein the orifices are configurable to provide the oxidizing fluid into the opening.

3128. The system of claim 3125, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configurable to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

3129. The system of claim 3125, wherein the conduit is further configurable to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

3130. The system of claim 3125, wherein the conduit is further configurable to remove an oxidation product.

3131. The system of claim 3125, wherein the conduit is further configurable to remove an oxidation product such that the oxidation product transfers heat to the oxidizing fluid.

3132. The system of claim 3125, wherein the conduit is further configurable to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3133. The system of claim 3125, wherein the conduit is further configurable to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

3134. The system of claim 3125, wherein the conduit is further configurable to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3135. The system of claim 3125, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3136. The system of claim 3125, further comprising a center conduit disposed within the conduit, wherein center conduit is configurable to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configurable to remove an oxidation product during use.

3137. The system of claim 3125, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3138. The system of claim 3125, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3139. The system of claim 3125, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3140. The system of claim 3125, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3141. The system of claim 3125, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3142. The system of claim 3125, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3143. The system of claim 3125, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3144. The system of claim 3125, wherein the system is further configurable such that transferred heat can pyrolyze at least some hydrocarbons in the pyrolysis zone.

3145. An in situ method for heating a hydrocarbon containing formation, comprising:
5 heating a portion of the formation to a temperature sufficient to support reaction of hydrocarbons within the portion of the formation with an oxidizing fluid, wherein heating comprises applying an electrical current to at least one elongated member to provide heat to the portion, and wherein at least the one elongated member is disposed within the opening;

10 providing the oxidizing fluid to a reaction zone in the formation;
allowing the oxidizing fluid to react with at least a portion of the hydrocarbons at the reaction zone to generate heat at the reaction zone; and
15 transferring the generated heat substantially by conduction from the reaction zone to a pyrolysis zone in the formation.

3146. The method of claim 3145, further comprising transporting the oxidizing fluid through the reaction zone by diffusion.

3147. The method of claim 3145, further comprising directing at least a portion of the oxidizing fluid into the opening through orifices of a conduit disposed in the opening.
20

3148. The method of claim 3145, further comprising controlling a flow of the oxidizing fluid with critical flow orifices of a conduit disposed in the opening such that a rate of oxidation is controlled.
25

3149. The method of claim 3145, further comprising increasing a flow of the oxidizing fluid in the opening to accommodate an increase in a volume of the reaction zone such that a rate of oxidation is substantially constant over time within the reaction zone.

3150. The method of claim 3145, wherein a conduit is disposed in the opening, the method further comprising cooling the conduit with the oxidizing fluid to reduce heating of the conduit by oxidation.

5 3151. The method of claim 3145, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit.

10 3152. The method of claim 3145, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and transferring heat from the oxidation product in the conduit to the oxidizing fluid in the conduit.

15 3153. The method of claim 3145, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

20 3154. The method of claim 3145, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and controlling a pressure between the oxidizing fluid and the oxidation product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

25 3155. The method of claim 3145, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and substantially inhibiting the oxidation product from flowing into portions of the formation beyond the reaction zone.

30 3156. The method of claim 3145, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.

3157. The method of claim 3145, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the outer conduit.

3158. The method of claim 3145, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3159. The method of claim 3145, further comprising removing water from the formation prior to heating the portion.

3160. The method of claim 3145, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

3161. The method of claim 3145, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3162. The method of claim 3145, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3163. The method of claim 3145, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3164. The method of claim 3145, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3165. The method of claim 3145, wherein the pyrolysis zone is substantially adjacent to the reaction zone.

3166. A system configured to heat a hydrocarbon containing formation, comprising:
a heat exchanger disposed external to the formation, wherein the heat exchanger is configured to heat an oxidizing fluid during use;

a conduit disposed in the opening, wherein the conduit is configured to provide the heated oxidizing fluid from the heat exchanger to at least a portion of the formation during use, wherein the system is configured to allow heat to transfer from the heated oxidizing fluid to at least the portion of the formation during use, and wherein the oxidizing fluid is selected to oxidize at least some hydrocarbons at a reaction zone in the formation during use such that heat is generated at the reaction zone; and

wherein the system is configured to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

3167. The system of claim 3166, wherein the oxidizing fluid is configured to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

3168. The system of claim 3166, wherein the conduit comprises orifices, and wherein the orifices are configured to provide the oxidizing fluid into the opening.

3169. The system of claim 3166, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configured to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

3170. The system of claim 3166, wherein the conduit is further configured to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

3171. The system of claim 3166, wherein the conduit is further configured to remove an oxidation product.

3172. The system of claim 3166, wherein the conduit is further configured to remove an oxidation product, such that the oxidation product transfers heat to the oxidizing fluid.

5 3173. The system of claim 3166, wherein the conduit is further configured to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

10 3174. The system of claim 3166, wherein the conduit is further configured to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

15 3175. The system of claim 3166, wherein the conduit is further configured to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

20 3176. The system of claim 3166, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

25 3177. The system of claim 3166, further comprising a center conduit disposed within the conduit, wherein the center conduit is configured to provide the oxidizing fluid into the opening during use, and wherein the conduit is further configured to remove an oxidation product during use.

30 3178. The system of claim 3166, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3179. The system of claim 3166, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3180. The system of claim 3166, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3181. The system of claim 3166, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3182. The system of claim 3166, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3183. The system of claim 3166, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3184. The system of claim 3166, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3185. A system configurable to heat a hydrocarbon containing formation, comprising:
a heat exchanger configurable to be disposed external to the formation, wherein the heat exchanger is further configurable to heat an oxidizing fluid during use;
a conduit configurable to be disposed in the opening, wherein the conduit is further configurable to provide the heated oxidizing fluid from the heat exchanger to at least a portion of the formation during use, wherein the system is configurable to allow heat to transfer from the heated oxidizing fluid to at least the portion of the formation

oxidize at least some hydrocarbons at a reaction zone in the formation during use such that heat is generated at the reaction zone; and

wherein the system is further configurable to allow heat to transfer substantially by conduction from the reaction zone to a pyrolysis zone of the formation during use.

3186. The system of claim 3185, wherein the oxidizing fluid is configurable to generate heat in the reaction zone such that the oxidizing fluid is transported through the reaction zone substantially by diffusion.

3187. The system of claim 3186, wherein the conduit comprises orifices, and wherein the orifices are configurable to provide the oxidizing fluid into the opening.

3188. The system of claim 3185, wherein the conduit comprises critical flow orifices, and wherein the critical flow orifices are configurable to control a flow of the oxidizing fluid such that a rate of oxidation in the formation is controlled.

3189. The system of claim 3185, wherein the conduit is further configurable to be cooled with the oxidizing fluid such that the conduit is not substantially heated by oxidation.

3190. The system of claim 3185, wherein the conduit is further configurable to remove an oxidation product.

3191. The system of claim 3185, wherein the conduit is further configurable to remove an oxidation product such that the oxidation product transfers heat to the oxidizing fluid.

3192. The system of claim 3185, wherein the conduit is further configurable to remove an oxidation product, and wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3193. The system of claim 3185, wherein the conduit is further configurable to remove an oxidation product, and wherein a pressure of the oxidizing fluid in the conduit and a pressure of the oxidation product in the conduit are controlled to reduce contamination of the oxidation product by the oxidizing fluid.

3194. The system of claim 3185, wherein the conduit is further configurable to remove an oxidation product, and wherein the oxidation product is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3195. The system of claim 3185, wherein the oxidizing fluid is substantially inhibited from flowing into portions of the formation beyond the reaction zone.

3196. The system of claim 3185, further comprising a center conduit disposed within the conduit, wherein center conduit is configurable to provide the oxidizing fluid into the opening during use, and wherein the second conduit is further configurable to remove an oxidation product during use.

3197. The system of claim 3185, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3198. The system of claim 3185, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3199. The system of claim 3185, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3200. The system of claim 3185, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3201. The system of claim 3185, further comprising an overburden casing coupled to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3202. The system of claim 3185, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3203. The system of claim 3185, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3204. An in situ method for heating a hydrocarbon containing formation, comprising:
heating a portion of the formation to a temperature sufficient to support reaction of hydrocarbons within the portion of the formation with an oxidizing fluid, wherein heating comprises:

heating the oxidizing fluid with a heat exchanger, wherein the heat exchanger is disposed external to the formation;

providing the heated oxidizing fluid from the heat exchanger to the portion of the formation; and

allowing heat to transfer from the heated oxidizing fluid to the portion of the formation;

providing the oxidizing fluid to a reaction zone in the formation;

allowing the oxidizing fluid to react with at least a portion of the hydrocarbons at the reaction zone to generate heat at the reaction zone; and

transferring the generated heat substantially by conduction from the reaction zone to a pyrolysis zone in the formation.

3205. The method of claim 3204, further comprising transporting the oxidizing fluid through the reaction zone by diffusion.

5 3206. The method of claim 3204, further comprising directing at least a portion of the oxidizing fluid into the opening through orifices of a conduit disposed in the opening.

10 3207. The method of claim 3204, further comprising controlling a flow of the oxidizing fluid with critical flow orifices of a conduit disposed in the opening such that a rate of oxidation is controlled.

15 3208. The method of claim 3204, further comprising increasing a flow of the oxidizing fluid in the opening to accommodate an increase in a volume of the reaction zone such that a rate of oxidation is substantially constant over time within the reaction zone.

20 3209. The method of claim 3204, wherein a conduit is disposed in the opening, the method further comprising cooling the conduit with the oxidizing fluid to reduce heating of the conduit by oxidation.

25 3210. The method of claim 3204, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit.

30 3211. The method of claim 3204, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and transferring heat from the oxidation product in the conduit to the oxidizing fluid in the conduit.

3212. The method of claim 3204, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through

the conduit, wherein a flow rate of the oxidizing fluid in the conduit is approximately equal to a flow rate of the oxidation product in the conduit.

3213. The method of claim 3204, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and controlling a pressure between the oxidizing fluid and the oxidation product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

3214. The method of claim 3204, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and substantially inhibiting the oxidation product from flowing into portions of the formation beyond the reaction zone.

3215. The method of claim 3204, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.

3216. The method of claim 3204, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the outer conduit.

3217. The method of claim 3204, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3218. The method of claim 3204, further comprising removing water from the formation prior to heating the portion.

3219. The method of claim 3204, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

3220. The method of claim 3204, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3221. The method of claim 3204, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3222. The method of claim 3204, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3223. The method of claim 3204, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3224. The method of claim 3204, wherein the pyrolysis zone is substantially adjacent to the reaction zone.

3225. An in situ method for heating a hydrocarbon containing formation, comprising:
heating a portion of the formation to a temperature sufficient to support reaction of hydrocarbons within the portion of the formation with an oxidizing fluid, wherein heating comprises:

oxidizing a fuel gas in a heater, wherein the heater is disposed external to the formation;

providing the oxidized fuel gas from the heater to the portion of the formation;

and

allowing heat to transfer from the oxidized fuel gas to the portion of the formation;

providing the oxidizing fluid to a reaction zone in the formation;

allowing the oxidizing fluid to react with at least a portion of the hydrocarbons at the reaction zone to generate heat at the reaction zone; and

transferring the generated heat substantially by conduction from the reaction zone to a pyrolysis zone in the formation.

3226. The method of claim 3225, further comprising transporting the oxidizing fluid through the reaction zone by diffusion.

3227. The method of claim 3225, further comprising directing at least a portion of the oxidizing fluid into the opening through orifices of a conduit disposed in the opening.

3228. The method of claim 3225, further comprising controlling a flow of the oxidizing fluid with critical flow orifices of a conduit disposed in the opening such that a rate of oxidation is controlled.

3229. The method of claim 3225, further comprising increasing a flow of the oxidizing fluid in the opening to accommodate an increase in a volume of the reaction zone such that a rate of oxidation is substantially constant over time within the reaction zone.

3230. The method of claim 3225, wherein a conduit is disposed in the opening, the method further comprising cooling the conduit with the oxidizing fluid to reduce heating of the conduit by oxidation.

3231. The method of claim 3225, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit.

3232. The method of claim 3225, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and transferring heat from the oxidation product in the conduit to the oxidizing fluid in the conduit.

09841437-042401
3233. The method of claim 3225, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit, wherein a flow rate of the oxidizing fluid in the conduit is approximately
5 equal to a flow rate of the oxidation product in the conduit.

3234. The method of claim 3225, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and controlling a pressure between the oxidizing fluid and the oxidation
10 product in the conduit to reduce contamination of the oxidation product by the oxidizing fluid.

3235. The method of claim 3225, wherein a conduit is disposed within the opening, the method further comprising removing an oxidation product from the formation through the conduit and substantially inhibiting the oxidation product from flowing into portions
15 of the formation beyond the reaction zone.

3236. The method of claim 3225, further comprising substantially inhibiting the oxidizing fluid from flowing into portions of the formation beyond the reaction zone.
20

3237. The method of claim 3225, wherein a center conduit is disposed within an outer conduit, and wherein the outer conduit is disposed within the opening, the method further comprising providing the oxidizing fluid into the opening through the center conduit and removing an oxidation product through the outer conduit.
25

3238. The method of claim 3225, wherein the portion of the formation extends radially from the opening a width of less than approximately 0.2 m.

3239. The method of claim 3225, further comprising removing water from the formation
30 prior to heating the portion.

3240. The method of claim 3225, further comprising controlling the temperature of the formation to substantially inhibit production of oxides of nitrogen during oxidation.

3241. The method of claim 3225, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3242. The method of claim 3225, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3243. The method of claim 3225, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3244. The method of claim 3225, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

3245. The method of claim 3225, wherein the pyrolysis zone is substantially adjacent to the reaction zone.

3246. A system configured to heat a hydrocarbon containing formation, comprising:
an insulated conductor disposed within an open wellbore in the formation,
wherein the insulated conductor is configured to provide radiant heat to at least a portion of the formation during use; and
wherein the system is configured to allow heat to transfer from the insulated conductor to a selected section of the formation during use.

09841437
1042401

3247. The system of claim 3246, wherein the insulated conductor is further configured to generate heat during application of an electrical current to the insulated conductor during use.

5 3248. The system of claim 3246, further comprising a support member, wherein the support member is configured to support the insulated conductor.

3249. The system of claim 3246, further comprising a support member and a centralizer, wherein the support member is configured to support the insulated conductor, and wherein the centralizer is configured to maintain a location of the insulated conductor on the support member.

3250. The system of claim 3246, wherein the open wellbore comprises a diameter of at least approximately 5 cm.

3251. The system of claim 3246, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

20 3252. The system of claim 3246, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a rubber insulated conductor.

25 3253. The system of claim 3246, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a copper wire.

3254. The system of claim 3246, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor.

3255. The system of claim 3246, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

5 3256. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath.

10 3257. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the conductor comprises a copper-nickel alloy.

15 3258. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight.

20 3259. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 2 % nickel by weight to approximately 6 % nickel by weight.

25 3260. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises a thermally conductive material.

30 3261. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

3262. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

3263. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

3264. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configured to occupy porous spaces within the magnesium oxide.

3265. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3266. The system of claim 3246, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3267. The system of claim 3246, further comprising two additional insulated conductors, wherein the insulated conductor and the two additional insulated conductors are configured in a 3-phase Y configuration.

3268. The system of claim 3246, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a

support member, and wherein the insulated conductor and the additional insulated conductor are configured in a series electrical configuration.

3269. The system of claim 3246, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a support member, and wherein the insulated conductor and the additional insulated conductor are configured in a parallel electrical configuration.

3270. The system of claim 3246, wherein the insulated conductor is configured to generate radiant heat of approximately 500 W/m to approximately 1150 W/m during use.

3271. The system of claim 3246, further comprising a support member configured to support the insulated conductor, wherein the support member comprises orifices configured to provide fluid flow through the support member into the open wellbore during use.

3272. The system of claim 3246, further comprising a support member configured to support the insulated conductor, wherein the support member comprises critical flow orifices configured to provide a substantially constant amount of fluid flow through the support member into the open wellbore during use.

3273. The system of claim 3246, further comprising a tube coupled to the insulated conductor, wherein the tube is configured to provide a flow of fluid into the open wellbore during use.

3274. The system of claim 3246, further comprising a tube coupled to the insulated conductor, wherein the tube comprises critical flow orifices configured to provide a substantially constant amount of fluid flow through the support member into the open wellbore during use.

3275. The system of claim 3246, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation.

5 3276. The system of claim 3246, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

10 3277. The system of claim 3246, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

15 3278. The system of claim 3246, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the open wellbore.

20 3279. The system of claim 3246, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the open wellbore, and wherein the packing material is configured to substantially inhibit a flow of fluid between the open wellbore and the overburden casing during use.

25 3280. The system of claim 3246, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the open wellbore, and wherein the packing material comprises cement.

30 3281. The system of claim 3246, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, the system further comprising a wellhead coupled to the overburden casing

and a lead-in conductor coupled to the insulated conductor, wherein the wellhead is disposed external to the overburden, wherein the wellhead comprises at least one sealing flange, and wherein at least the one sealing flange is configured to couple to the lead-in conductor.

5

3282. The system of claim 3246, wherein the system is further configured to transfer heat such that the transferred heat can pyrolyze at least some of the hydrocarbons in the selected section.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100

3283. A system configurable to heat a hydrocarbon containing formation, comprising:
an insulated conductor configurable to be disposed within an open wellbore in the formation, wherein the insulated conductor is further configurable to provide radiant heat to at least a portion of the formation during use; and

wherein the system is configurable to allow heat to transfer from the insulated conductor to a selected section of the formation during use.

3284. The system of claim 3283, wherein the insulated conductor is further configurable to generate heat during application of an electrical current to the insulated conductor during use.

3285. The system of claim 3283, further comprising a support member, wherein the support member is configurable to support the insulated conductor.

3286. The system of claim 3283, further comprising a support member and a centralizer, wherein the support member is configurable to support the insulated conductor, and wherein the centralizer is configurable to maintain a location of the insulated conductor on the support member.

3287. The system of claim 3283, wherein the open wellbore comprises a diameter of at least approximately 5 cm.

3288. The system of claim 3283, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a low resistance conductor configurable to generate substantially no heat.

5 3289. The system of claim 3283, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a rubber insulated conductor.

10 3290. The system of claim 3283, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a copper wire.

15 3291. The system of claim 3283, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor.

20 3292. The system of claim 3283, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

25 3293. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath.

30 3294. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the conductor comprises a copper-nickel alloy.

3295. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight.

3296. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 2 % nickel by weight to approximately 6 % nickel by weight.

3297. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises a thermally conductive material.

3298. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

3299. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

3300. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

3301. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configurable to occupy porous spaces within the magnesium oxide.

3302. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating

09841437 042401

material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3303. The system of claim 3283, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3304. The system of claim 3283, further comprising two additional insulated conductors, wherein the insulated conductor and the two additional insulated conductors are configurable in a 3-phase Y configuration.

3305. The system of claim 3283, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a support member, and wherein the insulated conductor and the additional insulated conductor are configurable in a series electrical configuration.

3306. The system of claim 3283, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a support member, and wherein the insulated conductor and the additional insulated conductor are configurable in a parallel electrical configuration.

3307. The system of claim 3283, wherein the insulated conductor is configurable to generate radiant heat of approximately 500 W/m to approximately 1150 W/m during use.

3308. The system of claim 3283, further comprising a support member configurable to support the insulated conductor, wherein the support member comprises orifices configurable to provide fluid flow through the support member into the open wellbore during use.

3309. The system of claim 3283, further comprising a support member configurable to support the insulated conductor, wherein the support member comprises critical flow

orifices configurable to provide a substantially constant amount of fluid flow through the support member into the open wellbore during use.

5 3310. The system of claim 3283, further comprising a tube coupled to the insulated conductor, wherein the tube is configurable to provide a flow of fluid into the open wellbore during use.

10 3311. The system of claim 3283, further comprising a tube coupled to the first insulated conductor, wherein the tube comprises critical flow orifices configurable to provide a substantially constant amount of fluid flow through the support member into the open wellbore during use.

15 3312. The system of claim 3283, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation.

20 3313. The system of claim 3283, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3314. The system of claim 3283, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

25 3315. The system of claim 3283, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the open wellbore.

30 3316. The system of claim 3283, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the

formation, wherein a packing material is disposed at a junction of the overburden casing and the open wellbore, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the open wellbore and the overburden casing during use.

5 3317. The system of claim 3283, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the open wellbore, and wherein the packing material comprises cement.

10 3318. The system of claim 3283, further comprising an overburden casing coupled to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, the system further comprising a wellhead coupled to the overburden casing and a lead-in conductor coupled to the insulated conductor, wherein the wellhead is disposed external to the overburden, wherein the wellhead comprises at least one sealing flange, and wherein at least the one sealing flange is configurable to couple to the lead-in conductor.

15 3319. The system of claim 3283, wherein the system is further configured to transfer heat such that the transferred heat can pyrolyze at least some hydrocarbons in the selected section.

20 3320. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to an insulated conductor to provide radiant heat to at least a portion of the formation, wherein the insulated conductor is disposed within an
25 open wellbore in the formation; and
allowing the radiant heat to transfer from the insulated conductor to a selected section of the formation.

30 3321. The method of claim 3320, further comprising supporting the insulated conductor on a support member.

3322. The method of claim 3320, further comprising supporting the insulated conductor on a support member and maintaining a location of the insulated conductor on the support member with a centralizer.

5 3323. The method of claim 3320, wherein the insulated conductor is coupled to two additional insulated conductors, wherein the insulated conductor and the two insulated conductors are disposed within the open wellbore, and wherein the three insulated conductors are electrically coupled in a 3-phase Y configuration.

10 3324. The method of claim 3320, wherein an additional insulated conductor is disposed within the open wellbore.

15 3325. The method of claim 3320, wherein an additional insulated conductor is disposed within the open wellbore, and wherein the insulated conductor and the additional insulated conductor are electrically coupled in a series configuration.

20 3326. The method of claim 3320, wherein an additional insulated conductor is disposed within the open wellbore, and wherein the insulated conductor and the additional insulated conductor are electrically coupled in a parallel configuration.

3327. The method of claim 3320, wherein the provided heat comprises approximately 500 W/m to approximately 1150 W/m.

25 3328. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the conductor comprises a copper-nickel alloy.

30 3329. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight.

3330. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 2 % nickel by weight to approximately 6 % nickel by weight.

3331. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

3332. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

3333. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

3334. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configured to occupy porous spaces within the magnesium oxide.

3335. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3336. The method of claim 3320, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

5 3337. The method of claim 3320, further comprising supporting the insulated conductor on a support member and flowing a fluid into the open wellbore through an orifice in the support member.

10 3338. The method of claim 3320, further comprising supporting the insulated conductor on a support member and flowing a substantially constant amount of fluid into the open wellbore through critical flow orifices in the support member.

15 3339. The method of claim 3320, wherein a perforated tube is disposed in the open wellbore proximate to the insulated conductor, the method further comprising flowing a fluid into the open wellbore through the perforated tube.

20 3340. The method of claim 3320, wherein a tube is disposed in the open wellbore proximate to the insulated conductor, the method further comprising flowing a substantially constant amount a fluid into the open wellbore through critical flow orifices in the tube.

25 3341. The method of claim 3320, further comprising supporting the insulated conductor on a support member and flowing a corrosion inhibiting fluid into the open wellbore through an orifice in the support member.

3342. The method of claim 3320, wherein a perforated tube is disposed in the open wellbore proximate to the insulated conductor, the method further comprising flowing a corrosion inhibiting fluid into the open wellbore through the perforated tube.

3343. The method of claim 3320, further comprising determining a temperature distribution in the insulated conductor using an electromagnetic signal provided to the insulated conductor.

3344. The method of claim 3320, further comprising monitoring a leakage current of the insulated conductor.

3345. The method of claim 3320, further comprising monitoring the applied electrical current.

3346. The method of claim 3320, further comprising monitoring a voltage applied to the insulated conductor.

3347. The method of claim 3320, further comprising monitoring a temperature in the insulated conductor with at least one thermocouple.

3348. The method of claim 3320, further comprising electrically coupling a lead-in conductor to the insulated conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

3349. The method of claim 3320, further comprising electrically coupling a lead-in conductor to the insulated conductor using a cold pin transition conductor.

3350. The method of claim 3320, further comprising electrically coupling a lead-in conductor to the insulated conductor using a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3351. The method of claim 3320, further comprising coupling an overburden casing to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation.

3352. The method of claim 3320, further comprising coupling an overburden casing to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3353. The method of claim 3320, further comprising coupling an overburden casing to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3354. The method of claim 3320, further comprising coupling an overburden casing to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the open wellbore.

3355. The method of claim 3320, further comprising coupling an overburden casing to the open wellbore, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the open wellbore and the overburden casing with a packing material.

3356. The method of claim 3320, further comprising heating at least the portion of the formation to pyrolyze at least some hydrocarbons within the formation.

3357. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to an insulated conductor to provide heat to at least a portion of the formation, wherein the insulated conductor is disposed within an opening in the formation; and
allowing the heat to transfer from the insulated conductor to a section of the formation.

3358. The method of claim 1, further comprising supporting the insulated conductor on a support member.

3359. The method of claim 1, further comprising supporting the insulated conductor on a support member and maintaining a location of the first insulated conductor on the support member with a centralizer.

3360. The method of claim 1, wherein the insulated conductor is coupled to two additional insulated conductors, wherein the insulated conductor and the two insulated conductors are disposed within the opening, and wherein the three insulated conductors are electrically coupled in a 3-phase Y configuration.

3361. The method of claim 1, wherein an additional insulated conductor is disposed within the opening.

3362. The method of claim 1, wherein an additional insulated conductor is disposed within the opening, and wherein the insulated conductor and the additional insulated conductor are electrically coupled in a series configuration.

3363. The method of claim 1, wherein an additional insulated conductor is disposed within the opening, and wherein the insulated conductor and the additional insulated conductor are electrically coupled in a parallel configuration.

3364. The method of claim 1, wherein the provided heat comprises approximately 500 W/m to approximately 1150 W/m.

3365. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the conductor comprises a copper-nickel alloy.

3366. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-

nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight.

3367. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 2 % nickel by weight to approximately 6 % nickel by weight.

3368. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

3369. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

3370. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

3371. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configured to occupy porous spaces within the magnesium oxide.

3372. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3373. The method of claim 1, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3374. The method of claim 1, further comprising supporting the insulated conductor on a support member and flowing a fluid into the opening through an orifice in the support member.

3375. The method of claim 1, further comprising supporting the insulated conductor on a support member and flowing a substantially constant amount of fluid into the opening through critical flow orifices in the support member.

3376. The method of claim 1, wherein a perforated tube is disposed in the opening proximate to the insulated conductor, the method further comprising flowing a fluid into the opening through the perforated tube.

3377. The method of claim 1, wherein a tube is disposed in the opening proximate to the insulated conductor, the method further comprising flowing a substantially constant amount a fluid into the opening through critical flow orifices in the tube.

3378. The method of claim 1, further comprising supporting the insulated conductor on a support member and flowing a corrosion inhibiting fluid into the opening through an orifice in the support member.

3379. The method of claim 1, wherein a perforated tube is disposed in the opening proximate to the insulated conductor, the method further comprising flowing a corrosion inhibiting fluid into the opening through the perforated tube.

3380. The method of claim 1, further comprising determining a temperature distribution in the insulated conductor using an electromagnetic signal provided to the insulated conductor.

3381. The method of claim 1, further comprising monitoring a leakage current of the insulated conductor.

3382. The method of claim 1, further comprising monitoring the applied electrical current.

3383. The method of claim 1, further comprising monitoring a voltage applied to the insulated conductor.

3384. The method of claim 1, further comprising monitoring a temperature in the insulated conductor with at least one thermocouple.

3385. The method of claim 1, further comprising electrically coupling a lead-in conductor to the insulated conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

3386. The method of claim 1, further comprising electrically coupling a lead-in conductor to the insulated conductor using a cold pin transition conductor.

3387. The method of claim 1, further comprising electrically coupling a lead-in conductor to the insulated conductor using a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3388. The method of claim 1, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3389. The method of claim 1, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

760-240-4860

3390. The method of claim 1, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3391. The method of claim 1, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3392. The method of claim 1, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with a packing material.

3393. The method of claim 1, further comprising heating at least the portion of the formation to substantially pyrolyze at least some hydrocarbons within the formation.

3394. A system configured to heat a hydrocarbon containing formation, comprising:
an insulated conductor disposed within an opening in the formation, wherein the insulated conductor is configured to provide heat to at least a portion of the formation during use, wherein the insulated conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight; and

wherein the system is configured to allow heat to transfer from the insulated conductor to a selected section of the formation during use.

3395. The system of claim 3394, wherein the insulated conductor is further configured to generate heat during application of an electrical current to the insulated conductor during use.

3396. The system of claim 3394, further comprising a support member, wherein the support member is configured to support the insulated conductor.

3397. The system of claim 3394, further comprising a support member and a centralizer, wherein the support member is configured to support the insulated conductor, and wherein the centralizer is configured to maintain a location of the insulated conductor on the support member.

3398. The system of claim 3394, wherein the opening comprises a diameter of at least approximately 5 cm.

3399. The system of claim 3394, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

3400. The system of claim 3394, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a rubber insulated conductor.

3401. The system of claim 3394, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a copper wire.

3402. The system of claim 3394, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor.

3403. The system of claim 3394, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3404. ~~The system of claim 3394, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises a thermally conductive material.~~

5 3405. The system of claim 3394, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

10 3406. The system of claim 3394, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

15 3407. The system of claim 3394, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

20 3408. The system of claim 3394, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configured to occupy porous spaces within the magnesium oxide.

25 3409. The system of claim 3394, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

30 3410. The system of claim 3394, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3411. The system of claim 3394, further comprising two additional insulated conductors, wherein the insulated conductor and the two additional insulated conductors are configured in a 3-phase Y configuration.

3412. The system of claim 3394, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a support member, and wherein the insulated conductor and the additional insulated conductor are configured in a series electrical configuration.

3413. The system of claim 3394, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a support member, and wherein the insulated conductor and the additional insulated conductor are configured in a parallel electrical configuration.

3414. The system of claim 3394, wherein the insulated conductor is configured to generate radiant heat of approximately 500 W/m to approximately 1150 W/m during use.

3415. The system of claim 3394, further comprising a support member configured to support the insulated conductor, wherein the support member comprises orifices configured to provide fluid flow through the support member into the opening during use.

3416. The system of claim 3394, further comprising a support member configured to support the insulated conductor, wherein the support member comprises critical flow orifices configured to provide a substantially constant amount of fluid flow through the support member into the opening during use.

3417. The system of claim 3394, further comprising a tube coupled to the insulated conductor, wherein the tube is configured to provide a flow of fluid into the opening during use.

09841437-04240-1

3418. The system of claim 3394, further comprising a tube coupled to the insulated conductor, wherein the tube comprises critical flow orifices configured to provide a substantially constant amount of fluid flow through the support member into the opening during use.

3419. The system of claim 3394, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3420. The system of claim 3394, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3421. The system of claim 3394, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3422. The system of claim 3394, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3423. The system of claim 3394, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3424. The system of claim 3394, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the

formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3425. The system of claim 3394, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, the system further comprising a wellhead coupled to the overburden casing and a lead-in conductor coupled to the insulated conductor, wherein the wellhead is disposed external to the overburden, wherein the wellhead comprises at least one sealing flange, and wherein at least the one sealing flange is configured to couple to the lead-in conductor.

3426. The system of claim 3394, wherein the system is further configured to transfer heat such that the transferred heat can pyrolyze at least some hydrocarbons in the selected section.

3427. A system configurable to heat a hydrocarbon containing formation, comprising:
an insulated conductor configurable to be disposed within an opening in the formation, wherein the insulated conductor is further configurable to provide heat to at least a portion of the formation during use, wherein the insulated conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight;

wherein the system is configurable to allow heat to transfer from the insulated conductor to a selected section of the formation during use.

3428. The system of claim 3427, wherein the insulated conductor is further configurable to generate heat during application of an electrical current to the insulated conductor during use.

3429. The system of claim 3427, further comprising a support member, wherein the support member is configurable to support the insulated conductor.

3430. The system of claim 3427, further comprising a support member and a centralizer, wherein the support member is configurable to support the insulated conductor, and wherein the centralizer is configurable to maintain a location of the insulated conductor on the support member.

3431. The system of claim 3427, wherein the opening comprises a diameter of at least approximately 5 cm.

3432. The system of claim 3427, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a low resistance conductor configurable to generate substantially no heat.

3433. The system of claim 3427, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a rubber insulated conductor.

3434. The system of claim 3427, further comprising a lead-in conductor coupled to the insulated conductor, wherein the lead-in conductor comprises a copper wire.

3435. The system of claim 3427, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor.

3436. The system of claim 3427, further comprising a lead-in conductor coupled to the insulated conductor with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3437. The system of claim 3427, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises a thermally conductive material.

3438. The system of claim 3427, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

3439. The system of claim 3427, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

3440. The system of claim 3427, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

3441. The system of claim 3427, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configurable to occupy porous spaces within the magnesium oxide.

3442. The system of claim 3427, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3443. The system of claim 3427, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3444. The system of claim 3427, further comprising two additional insulated conductors, wherein the insulated conductor and the two additional insulated conductors are configurable in a 3-phase Y configuration.

3445. The system of claim 3427, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a support member, and wherein the insulated conductor and the additional insulated conductor are configurable in a series electrical configuration.

3446. The system of claim 3427, further comprising an additional insulated conductor, wherein the insulated conductor and the additional insulated conductor are coupled to a support member, and wherein the insulated conductor and the additional insulated conductor are configurable in a parallel electrical configuration.

3447. The system of claim 3427, wherein the insulated conductor is configurable to generate radiant heat of approximately 500 W/m to approximately 1150 W/m during use.

3448. The system of claim 3427, further comprising a support member configurable to support the insulated conductor, wherein the support member comprises orifices configurable to provide fluid flow through the support member into the open wellbore during use.

3449. The system of claim 3427, further comprising a support member configurable to support the insulated conductor, wherein the support member comprises critical flow orifices configurable to provide a substantially constant amount of fluid flow through the support member into the opening during use.

3450. The system of claim 3427, further comprising a tube coupled to the insulated conductor, wherein the tube is configurable to provide a flow of fluid into the opening during use.

3451. The system of claim 3427, further comprising a tube coupled to the insulated conductor, wherein the tube comprises critical flow orifices configurable to provide a substantially constant amount of fluid flow through the support member into the opening during use.

3452. The system of claim 3427, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3453. The system of claim 3427, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3454. The system of claim 3427, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3455. The system of claim 3427, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3456. The system of claim 3427, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3457. The system of claim 3427, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3458. The system of claim 3427, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the

09041437
1042401

formation, the system further comprising a wellhead coupled to the overburden casing and a lead-in conductor coupled to the insulated conductor, wherein the wellhead is disposed external to the overburden, wherein the wellhead comprises at least one sealing flange, and wherein at least the one sealing flange is configurable to couple to the lead-in conductor.

3459. The system of claim 3427, wherein the system is further configured to transfer heat such that the transferred heat can pyrolyze at least some hydrocarbons in the selected section.

3460. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to an insulated conductor to provide heat to at least a portion of the formation, wherein the insulated conductor is disposed within an opening in the formation, and wherein the insulated conductor comprises a copper-nickel alloy of approximately 7 % nickel by weight to approximately 12 % nickel by weight; and
allowing the heat to transfer from the insulated conductor to a selected section of the formation.

3461. The method of claim 3460, further comprising supporting the insulated conductor on a support member.

3462. The method of claim 3460, further comprising supporting the insulated conductor on a support member and maintaining a location of the first insulated conductor on the support member with a centralizer.

3463. The method of claim 3460, wherein the insulated conductor is coupled to two additional insulated conductors, wherein the insulated conductor and the two insulated conductors are disposed within the opening, and wherein the three insulated conductors are electrically coupled in a 3-phase Y configuration.

3464. The method of claim 3460, wherein an additional insulated conductor is disposed within the opening.

3465. The method of claim 3460, wherein an additional insulated conductor is disposed within the opening, and wherein the insulated conductor and the additional insulated conductor are electrically coupled in a series configuration.

3466. The method of claim 3460, wherein an additional insulated conductor is disposed within the opening, and wherein the insulated conductor and the additional insulated conductor are electrically coupled in a parallel configuration.

3467. The method of claim 3460, wherein the provided heat comprises approximately 500 W/m to approximately 1150 W/m.

3468. The method of claim 3460, wherein the copper-nickel alloy is disposed in an electrically insulating material.

3469. The method of claim 3460, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

3470. The method of claim 3460, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

3471. The method of claim 3460, wherein the copper-nickel alloy is disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

0904143-04401

3472. The method of claim 3460, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configured to occupy porous spaces within the magnesium oxide.

3473. The method of claim 3460, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3474. The method of claim 3460, wherein the copper-nickel alloy is disposed in an electrically insulating material, wherein the insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3475. The method of claim 3460, further comprising supporting the insulated conductor on a support member and flowing a fluid into the opening through an orifice in the support member.

3476. The method of claim 3460, further comprising supporting the insulated conductor on a support member and flowing a substantially constant amount of fluid into the opening through critical flow orifices in the support member.

3477. The method of claim 3460, wherein a perforated tube is disposed in the opening proximate to the insulated conductor, the method further comprising flowing a fluid into the opening through the perforated tube.

3478. The method of claim 3460, wherein a tube is disposed in the opening proximate to the insulated conductor, the method further comprising flowing a substantially constant amount a fluid into the opening through critical flow orifices in the tube.

3479. The method of claim 3460, further comprising supporting the insulated conductor on a support member and flowing a corrosion inhibiting fluid into the opening through an orifice in the support member.

5 3480. The method of claim 3460, wherein a perforated tube is disposed in the opening proximate to the insulated conductor, the method further comprising flowing a corrosion inhibiting fluid into the opening through the perforated tube.

10 3481. The method of claim 3460, further comprising determining a temperature distribution in the insulated conductor using an electromagnetic signal provided to the insulated conductor.

15 3482. The method of claim 3460, further comprising monitoring a leakage current of the insulated conductor.

20 3483. The method of claim 3460, further comprising monitoring the applied electrical current.

3484. The method of claim 3460, further comprising monitoring a voltage applied to the insulated conductor.

3485. The method of claim 3460, further comprising monitoring a temperature in the insulated conductor with at least one thermocouple.

25 3486. The method of claim 3460, further comprising electrically coupling a lead-in conductor to the insulated conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

30 3487. The method of claim 3460, further comprising electrically coupling a lead-in conductor to the insulated conductor using a cold pin transition conductor.

3488. The method of claim 3460, further comprising electrically coupling a lead-in conductor to the insulated conductor using a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3489. The method of claim 3460, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3490. The method of claim 3460, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3491. The method of claim 3460, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3492. The method of claim 3460, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3493. The method of claim 3460, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with a packing material.

3494. The method of claim 3460, further comprising heating at least the portion of the formation to substantially pyrolyze at least some hydrocarbons within the formation.

3495. A system configured to heat a hydrocarbon containing formation, comprising:

09041437-042401

at least three insulated conductors disposed within an opening in the formation, wherein at least the three insulated conductors are electrically coupled in a 3-phase Y configuration, and wherein at least the three insulated conductors are configured to provide heat to at least a portion of the formation during use; and

5 wherein the system is configured to allow heat to transfer from at least the three insulated conductors to a selected section of the formation during use.

3496. The system of claim 3495, wherein at least the three insulated conductors are further configured to generate heat during application of an electrical current to at least
10 the three insulated conductors during use.

3497. The system of claim 3495, further comprising a support member, wherein the support member is configured to support at least the three insulated conductors.

3498. The system of claim 3495, further comprising a support member and a centralizer,
15 wherein the support member is configured to support at least the three insulated conductors, and wherein the centralizer is configured to maintain a location of at least the three insulated conductors on the support member.

3499. The system of claim 3495, wherein the opening comprises a diameter of at least
20 approximately 5 cm.

3500. The system of claim 3495, further comprising at least one lead-in conductor coupled to at least the three insulated conductors, wherein at least the one lead-in
25 conductor comprises a low resistance conductor configured to generate substantially no heat.

3501. The system of claim 3495, further comprising at least one lead-in conductor coupled to at least the three insulated conductors, wherein at least the one lead-in
30 conductor comprises a rubber insulated conductor.

3502. The system of claim 3495, further comprising at least one lead-in conductor coupled to at least the three insulated conductors, wherein at least the one lead-in conductor comprises a copper wire.

3503. The system of claim 3495, further comprising at least one lead-in conductor coupled to at least the three insulated conductors with a cold pin transition conductor.

3504. The system of claim 3495, further comprising at least one lead-in conductor coupled to at least the three insulated conductors with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3505. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath.

3506. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the conductor comprises a copper-nickel alloy.

3507. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight.

3508. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 2 % nickel by weight to approximately 6 % nickel by weight.

3509. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises a thermally conductive material.

5 3510. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

10 3511. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

15 3512. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

20 3513. The system of claim 3495, wherein the insulated conductor comprises a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configured to occupy porous spaces within the magnesium oxide.

25 3514. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

30 3515. The system of claim 3495, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the

09841437-042401

electrically insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3516. The system of claim 3495, wherein at least the three insulated conductors are configured to generate radiant heat of approximately 500 W/m to approximately 1150 W/m of at least the three insulated conductors during use.

3517. The system of claim 3495, further comprising a support member configured to support at least the three insulated conductors, wherein the support member comprises orifices configured to provide fluid flow through the support member into the opening during use.

3518. The system of claim 3495, further comprising a support member configured to support at least the three insulated conductors, wherein the support member comprises critical flow orifices configured to provide a substantially constant amount of fluid flow through the support member into the opening during use.

3519. The system of claim 3495, further comprising a tube coupled to at least the three insulated conductors, wherein the tube is configured to provide a flow of fluid into the opening during use.

3520. The system of claim 3495, further comprising a tube coupled to at least the three insulated conductors, wherein the tube comprises critical flow orifices configured to provide a substantially constant amount of fluid flow through the support member into the opening during use.

3521. The system of claim 3495, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

09841437-042401

3522. The system of claim 3495, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

5 3523. The system of claim 3495, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

10 3524. The system of claim 3495, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

15 3525. The system of claim 3495, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

20 3526. The system of claim 3495, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

25 3527. The system of claim 3495, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, the system further comprising a wellhead coupled to the overburden casing and a lead-in conductor coupled to the insulated conductor, wherein the wellhead is disposed external to the overburden, wherein the wellhead comprises at least one sealing flange, and wherein at least the one sealing flange is configured to couple to the lead-in conductor.

30

3528. The system of claim 3495, wherein the system is further configured to transfer heat such that the transferred heat can pyrolyze at least some hydrocarbons in the selected section.

3529. A system configurable to heat a hydrocarbon containing formation, comprising:
at least three insulated conductors configurable to be disposed within an opening in the formation, wherein at least the three insulated conductors are electrically coupled in a 3-phase Y configuration, and wherein at least the three insulated conductors are further configurable to provide heat to at least a portion of the formation during use; and wherein the system is configurable to allow heat to transfer from at least the three insulated conductors to a selected section of the formation during use.

3530. The system of claim 3529, wherein at least the three insulated conductors are further configurable to generate heat during application of an electrical current to at least the three insulated conductors during use.

3531. The system of claim 3529, further comprising a support member, wherein the support member is configurable to support at least the three insulated conductors.

3532. The system of claim 3529, further comprising a support member and a centralizer, wherein the support member is configurable to support at least the three insulated conductors, and wherein the centralizer is configurable to maintain a location of at least the three insulated conductors on the support member.

3533. The system of claim 3529, wherein the opening comprises a diameter of at least approximately 5 cm.

3534. The system of claim 3529, further comprising at least one lead-in conductor coupled to at least the three insulated conductors, wherein at least the one lead-in

conductor comprises a low resistance conductor configurable to generate substantially no heat.

3535. The system of claim 3529, further comprising at least one lead-in conductor coupled to at least the three insulated conductors, wherein at least the one lead-in conductor comprises a rubber insulated conductor.

3536. The system of claim 3529, further comprising at least one lead-in conductor coupled to at least the three insulated conductors, wherein at least the one lead-in conductor comprises a copper wire.

3537. The system of claim 3529, further comprising at least one lead-in conductor coupled to at least the three insulated conductors with a cold pin transition conductor.

3538. The system of claim 3529, further comprising at least one lead-in conductor coupled to at least the three insulated conductors with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3539. The system of claim 3529, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath.

3540. The system of claim 3529, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the conductor comprises a copper-nickel alloy.

3541. The system of claim 3529, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight.

09841437-042401

3542. The system of claim 3529, wherein at least the three insulated conductors
comprise a conductor disposed in an electrically insulating material, wherein the
conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy
comprises approximately 2 % nickel by weight to approximately 6 % nickel by weight.

3543. The system of claim 3529, wherein at least the three insulated conductors
comprise a conductor disposed in an electrically insulating material, and wherein the
electrically insulating material comprises a thermally conductive material.

3544. The system of claim 3529, wherein at least the three insulated conductors
comprise a conductor disposed in an electrically insulating material, and wherein the
electrically insulating material comprises magnesium oxide.

3545. The system of claim 3529, wherein at least the three insulated conductors
comprise a conductor disposed in an electrically insulating material, wherein the
electrically insulating material comprises magnesium oxide, and wherein the magnesium
oxide comprises a thickness of at least approximately 1 mm.

3546. The system of claim 3529, wherein at least the three insulated conductors
comprise a conductor disposed in an electrically insulating material, and wherein the
electrically insulating material comprises aluminum oxide and magnesium oxide.

3547. The system of claim 3529, wherein the insulated conductor comprises a conductor
disposed in an electrically insulating material, wherein the electrically insulating material
comprises magnesium oxide, wherein the magnesium oxide comprises grain particles,
and wherein the grain particles are configurable to occupy porous spaces within the
magnesium oxide.

3548. The system of claim 3529, wherein at least the three insulated conductors
comprise a conductor disposed in an electrically insulating material, and wherein the

electrically insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3549. The system of claim 3529, wherein at least the three insulated conductors
5 comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material is disposed in a sheath, and wherein the sheath comprises stainless steel.

3550. The system of claim 3529, wherein at least the three insulated conductors are
10 configurable to generate radiant heat of approximately 500 W/m to approximately 1150 W/m during use.

3551. The system of claim 3529, further comprising a support member configurable to support at least the three insulated conductors, wherein the support member comprises
15 orifices configurable to provide fluid flow through the support member into the opening during use.

3552. The system of claim 3529, further comprising a support member configurable to support at least the three insulated conductors, wherein the support member comprises
20 critical flow orifices configurable to provide a substantially constant amount of fluid flow through the support member into the opening during use.

3553. The system of claim 3529, further comprising a tube coupled to at least the three insulated conductors, wherein the tube is configurable to provide a flow of fluid into the
25 opening during use.

3554. The system of claim 3529, further comprising a tube coupled to at least the three insulated conductors, wherein the tube comprises critical flow orifices configurable to provide a substantially constant amount of fluid flow through the support member into
30 the opening during use.

~~3555. The system of claim 3529, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.~~

5 3556. The system of claim 3529, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

10 3557. The system of claim 3529, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

15 3558. The system of claim 3529, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

20 3559. The system of claim 3529, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

25 3560. The system of claim 3529, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

30 3561. The system of claim 3529, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, the system further comprising a wellhead coupled to the overburden casing

and a lead-in conductor coupled to the insulated conductor, wherein the wellhead is disposed external to the overburden, wherein the wellhead comprises at least one sealing flange, and wherein at least the one sealing flange is configurable to couple to the lead-in conductor.

5

3562. The system of claim 3529, wherein the system is further configured to transfer heat such that the transferred heat can pyrolyze at least some hydrocarbons in the selected section.

10

3563. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to at least three insulated conductors to provide heat to at least a portion of the formation, wherein at least the three insulated conductors are disposed within an opening in the formation; and

15

allowing the heat to transfer from at least the three insulated conductors to a selected section of the formation.

3564. The method of claim 3563, further comprising supporting at least the three insulated conductors on a support member.

20

3565. The method of claim 3563, further comprising supporting at least the three insulated conductors on a support member and maintaining a location of at least the three insulated conductors on the support member with a centralizer.

25

3566. The method of claim 3563, wherein the provided heat comprises approximately 500 W/m to approximately 1150 W/m.

30

3567. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the conductor comprises a copper-nickel alloy.

3568. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 7 % nickel by weight to approximately 12 % nickel by weight.

3569. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the conductor comprises a copper-nickel alloy, and wherein the copper-nickel alloy comprises approximately 2 % nickel by weight to approximately 6 % nickel by weight.

3570. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises magnesium oxide.

3571. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, and wherein the magnesium oxide comprises a thickness of at least approximately 1 mm.

3572. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, and wherein the electrically insulating material comprises aluminum oxide and magnesium oxide.

3573. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the electrically insulating material comprises magnesium oxide, wherein the magnesium oxide comprises grain particles, and wherein the grain particles are configured to occupy porous spaces within the magnesium oxide.

3574. The method of claim 3563, wherein at least the three insulated conductors comprise a conductor disposed in an electrically insulating material, wherein the

insulating material is disposed in a sheath, and wherein the sheath comprises a corrosion-resistant material.

3575. The method of claim 3563, wherein at least the three insulated conductors
5 comprise a conductor disposed in an electrically insulating material, wherein the
insulating material is disposed in a sheath, and wherein the sheath comprises stainless
steel.

3576. The method of claim 3563, further comprising supporting at least the three
10 insulated conductors on a support member and flowing a fluid into the opening through
an orifice in the support member.

3577. The method of claim 3563, further comprising supporting at least the three
15 insulated conductors on a support member and flowing a substantially constant amount of
fluid into the opening through critical flow orifices in the support member.

3578. The method of claim 3563, wherein a perforated tube is disposed in the opening
proximate to at least the three insulated conductors, the method further comprising
20 flowing a fluid into the opening through the perforated tube.

3579. The method of claim 3563, wherein a tube is disposed in the opening proximate to
at least the three insulated conductors, the method further comprising flowing a
substantially constant amount a fluid into the opening through critical flow orifices in the
tube.

3580. The method of claim 3563, further comprising supporting at least the three
25 insulated conductors on a support member and flowing a corrosion inhibiting fluid into
the opening through an orifice in the support member.

3581. The method of claim 3563, wherein a perforated tube is disposed in the opening proximate to at least the three insulated conductors, the method further comprising flowing a corrosion inhibiting fluid into the opening through the perforated tube.

5 3582. The method of claim 3563, further comprising determining a temperature distribution in at least the three insulated conductors using an electromagnetic signal provided to the insulated conductor.

10 3583. The method of claim 3563, further comprising monitoring a leakage current of at least the three insulated conductors.

3584. The method of claim 3563, further comprising monitoring the applied electrical current.

15 3585. The method of claim 3563, further comprising monitoring a voltage applied to at least the three insulated conductors.

20 3586. The method of claim 3563, further comprising monitoring a temperature in at least the three insulated conductors with at least one thermocouple.

3587. The method of claim 3563, further comprising electrically coupling a lead-in conductor to at least the three insulated conductors, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

25 3588. The method of claim 3563, further comprising electrically coupling a lead-in conductor to at least the three insulated conductors using a cold pin transition conductor.

30 3589. The method of claim 3563, further comprising electrically coupling a lead-in conductor to at least the three insulated conductors using a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

09341437-042401

3590. The method of claim 3563, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

5

3591. The method of claim 3563, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

10

3592. The method of claim 3563, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

15

3593. The method of claim 3563, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

20

3594. The method of claim 3563, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with a packing material.

25

3595. The method of claim 3563, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the hydrocarbons within the formation.

30

3596. A system configured to heat a hydrocarbon containing formation, comprising:
a first conductor disposed in a first conduit, wherein the first conduit is disposed within an opening in the formation, and wherein the first conductor is configured to provide heat to at least a portion of the formation during use; and

wherein the system is configured to allow heat to transfer from the first conductor to a section of the formation during use.

3597. The system of claim 3596, wherein the first conductor is further configured to generate heat during application of an electrical current to the first conductor.

3598. The system of claim 3596, wherein the first conductor comprises a pipe.

3599. The system of claim 3596, wherein the first conductor comprises stainless steel.

3600. The system of claim 3596, wherein the first conduit comprises stainless steel.

3601. The system of claim 3596, further comprising a centralizer configured to maintain a location of the first conductor within the first conduit.

3602. The system of claim 3596, further comprising a centralizer configured to maintain a location of the first conductor within the first conduit, wherein the centralizer comprises ceramic material.

3603. The system of claim 3596, further comprising a centralizer configured to maintain a location of the first conductor within the first conduit, wherein the centralizer comprises ceramic material and stainless steel.

3604. The system of claim 3596, wherein the opening comprises a diameter of at least approximately 5 cm.

3605. The system of claim 3596, further comprising a lead-in conductor coupled to the first conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

09041437-042401

09041437 042401

3606. The system of claim 3596, further comprising a lead-in conductor coupled to the first conductor, wherein the lead-in conductor comprises copper.

3607. The system of claim 3596, further comprising a sliding electrical connector coupled to the first conductor.

3608. The system of claim 3596, further comprising a sliding electrical connector coupled to the first conductor, wherein the sliding electrical connector is further coupled to the first conduit.

3609. The system of claim 3596, further comprising a sliding electrical connector coupled to the first conductor, wherein the sliding electrical connector is further coupled to the first conduit, and wherein the sliding electrical connector is configured to complete an electrical circuit with the first conductor and the first conduit.

3610. The system of claim 3596, further comprising a second conductor disposed within the first conduit and at least one sliding electrical connector coupled to the first conductor and the second conductor, wherein at least the one sliding electrical connector is configured to generate less heat than the first conductor or the second conductor during use.

3611. The system of claim 3596, wherein the first conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

3612. The system of claim 3596, further comprising a fluid disposed within the first conduit, wherein the fluid is configured to maintain a pressure within the first conduit to substantially inhibit deformation of the first conduit during use.

3613. The system of claim 3596, further comprising a thermally conductive fluid disposed within the first conduit.

3614. The system of claim 3596, further comprising a thermally conductive fluid disposed within the first conduit, wherein the thermally conductive fluid comprises helium.

3615. The system of claim 3596, further comprising a fluid disposed within the first conduit, wherein the fluid is configured to substantially inhibit arcing between the first conductor and the first conduit during use.

3616. The system of claim 3596, further comprising a tube disposed within the opening external to the first conduit, wherein the tube is configured to remove vapor produced from at least the heated portion of the formation such that a pressure balance is maintained between the first conduit and the opening to substantially inhibit deformation of the first conduit during use.

3617. The system of claim 3596, wherein the first conductor is further configured to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

3618. The system of claim 3596, further comprising a second conductor disposed within a second conduit and a third conductor disposed within a third conduit, wherein first conduit, the second conduit and the third conduit are disposed in different openings of the formation, wherein the first conductor is electrically coupled to the second conductor and the third conductor, and wherein the first, second, and third conductors are configured to operate in a 3-phase Y configuration during use.

3619. The system of claim 3596, further comprising a second conductor disposed within the first conduit, wherein the second conductor is electrically coupled to the first conductor to form an electrical circuit.

09841437:042401

3620. ~~The system of claim 3596, further comprising a second conductor disposed within the first conduit, wherein the second conductor is electrically coupled to the first conductor to form an electrical circuit with a connector.~~

5 3621. The system of claim 3596, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

10 3622. The system of claim 3596, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

15 3623. The system of claim 3596, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

20 3624. The system of claim 3596, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

25 3625. The system of claim 3596, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

30 3626. The system of claim 3596, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to the first conductor.

3627. The system of claim 3596, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to the first conductor, and wherein the substantially low resistance conductor comprises carbon steel.

3628. The system of claim 3596, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing and a centralizer configured to support the substantially low resistance conductor within the overburden casing.

3629. The system of claim 3596, wherein the heated section of the formation is substantially pyrolyzed.

3630. A system configurable to heat a hydrocarbon containing formation, comprising:
a first conductor configurable to be disposed in a first conduit, wherein the first conduit is configurable to be disposed within an opening in the formation, and wherein the first conductor is further configurable to provide heat to at least a portion of the formation during use; and

wherein the system is configurable to allow heat to transfer from the first conductor to a section of the formation during use.

3631. The system of claim 3630, wherein the first conductor is further configurable to generate heat during application of an electrical current to the first conductor.

3632. The system of claim 3630, wherein the first conductor comprises a pipe.

3633. The system of claim 3630, wherein the first conductor comprises stainless steel.

3634. The system of claim 3630, wherein the first conduit comprises stainless steel.

0941437-042401

3635. The system of claim 3630, further comprising a centralizer configurable to maintain a location of the first conductor within the first conduit.

5 3636. The system of claim 3630, further comprising a centralizer configurable to maintain a location of the first conductor within the first conduit, wherein the centralizer comprises ceramic material.

10 3637. The system of claim 3630, further comprising a centralizer configurable to maintain a location of the first conductor within the first conduit, wherein the centralizer comprises ceramic material and stainless steel.

15 3638. The system of claim 3630, wherein the opening comprises a diameter of at least approximately 5 cm.

3639. The system of claim 3630, further comprising a lead-in conductor coupled to the first conductor, wherein the lead-in conductor comprises a low resistance conductor configurable to generate substantially no heat.

20 3640. The system of claim 3630, further comprising a lead-in conductor coupled to the first conductor, wherein the lead-in conductor comprises copper.

25 3641. The system of claim 3630, further comprising a sliding electrical connector coupled to the first conductor.

3642. The system of claim 3630, further comprising a sliding electrical connector coupled to the first conductor, wherein the sliding electrical connector is further coupled to the first conduit.

30 3643. The system of claim 3630, further comprising a sliding electrical connector coupled to the first conductor, wherein the sliding electrical connector is further coupled

to the first conduit, and wherein the sliding electrical connector is configurable to complete an electrical circuit with the first conductor and the first conduit.

5 3644. The system of claim 3630, further comprising a second conductor disposed within the first conduit and at least one sliding electrical connector coupled to the first conductor and the second conductor, wherein at least the one sliding electrical connector is configurable to generate less heat than the first conductor or the second conductor during use.

10 3645. The system of claim 3630, wherein the first conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

15 3646. The system of claim 3630, further comprising a fluid disposed within the first conduit, wherein the fluid is configurable to maintain a pressure within the first conduit to substantially inhibit deformation of the first conduit during use.

20 3647. The system of claim 3630, further comprising a thermally conductive fluid disposed within the first conduit.

25 3648. The system of claim 3630, further comprising a thermally conductive fluid disposed within the first conduit, wherein the thermally conductive fluid comprises helium.

30 3649. The system of claim 3630, further comprising a fluid disposed within the first conduit, wherein the fluid is configurable to substantially inhibit arcing between the first conductor and the first conduit during use.

09441437-042401

3650. The system of claim 3630, further comprising a tube disposed within the opening external to the first conduit, wherein the tube is configurable to remove vapor produced from at least the heated portion of the formation such that a pressure balance is maintained between the first conduit and the opening to substantially inhibit deformation of the first conduit during use.

3651. The system of claim 3630, wherein the first conductor is further configurable to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

3652. The system of claim 3630, further comprising a second conductor disposed within a second conduit and a third conductor disposed within a third conduit, wherein first conduit, the second conduit and the third conduit are disposed in different openings of the formation, wherein the first conductor is electrically coupled to the second conductor and the third conductor, and wherein the first, second, and third conductors are configurable to operate in a 3-phase Y configuration during use.

3653. The system of claim 3630, further comprising a second conductor disposed within the first conduit, wherein the second conductor is electrically coupled to the first conductor to form an electrical circuit.

3654. The system of claim 3630, further comprising a second conductor disposed within the first conduit, wherein the second conductor is electrically coupled to the first conductor to form an electrical circuit with a connector.

3655. The system of claim 3630, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3656. The system of claim 3630, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

09041437-042401

3657. The system of claim 3630, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

5

3658. The system of claim 3630, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

10

3659. The system of claim 3630, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

15

3660. The system of claim 3630, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to the first conductor.

20

3661. The system of claim 3630, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to the first conductor, and wherein the substantially low resistance conductor comprises carbon steel.

25

3662. The system of claim 3630, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing and a centralizer configurable to support the substantially low resistance conductor within the overburden casing.

30

3663. The system of claim 3630, wherein the heated section of the formation is substantially pyrolyzed.

5 3664. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to a first conductor to provide heat to at least a
portion of the formation, wherein the first conductor is disposed in a first conduit, and
wherein the first conduit is disposed within an opening in the formation; and
allowing the heat to transfer from the first conductor to a section of the formation.

10 3665. The method of claim 3664, wherein the first conductor comprises a pipe.

3666. The method of claim 3664, wherein the first conductor comprises stainless steel.

15 3667. The method of claim 3664, wherein the first conduit comprises stainless steel.

3668. The method of claim 3664, further comprising maintaining a location of the first
conductor in the first conduit with a centralizer.

20 3669. The method of claim 3664, further comprising maintaining a location of the first
conductor in the first conduit with a centralizer, wherein the centralizer comprises
ceramic material.

25 3670. The method of claim 3664, further comprising maintaining a location of the first
conductor in the first conduit with a centralizer, wherein the centralizer comprises
ceramic material and stainless steel.

30 3671. The method of claim 3664, further comprising coupling a sliding electrical
connector to the first conductor.

3672. The method of claim 3664, further comprising electrically coupling a sliding electrical connector to the first conductor and the first conduit, wherein the first conduit comprises an electrical lead configured to complete an electrical circuit with the first conductor.

5

3673. The method of claim 3664, further comprising coupling a sliding electrical connector to the first conductor and the first conduit, wherein the first conduit comprises an electrical lead configured to complete an electrical circuit with the first conductor, and wherein the generated heat comprises approximately 20 percent generated by the first conduit.

10

3674. The method of claim 3664, wherein the provided heat comprises approximately 650 W/m to approximately 1650 W/m.

15

3675. The method of claim 3664, further comprising determining a temperature distribution in the first conduit using an electromagnetic signal provided to the conduit.

3676. The method of claim 3664, further comprising monitoring the applied electrical current.

20

3677. The method of claim 3664, further comprising monitoring a voltage applied to the first conductor.

3678. The method of claim 3664, further comprising monitoring a temperature in the conduit with at least one thermocouple.

25

3679. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

30

094437-04401

09841437-042401

3680. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

5 3681. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

10 3682. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

15 3683. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with a packing material.

20 3684. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein a substantially low resistance conductor is disposed within the overburden casing, and wherein the substantially low resistance conductor is electrically coupled to the first conductor.

25 3685. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein a substantially low resistance conductor is disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to the first conductor, and wherein the substantially low resistance conductor comprises carbon steel.

30 3686. The method of claim 3664, further comprising coupling an overburden casing to the opening, wherein a substantially low resistance conductor is disposed within the

overburden casing, wherein the substantially low resistance conductor is electrically coupled to the first conductor, and wherein the method further comprises maintaining a location of the substantially low resistance conductor in the overburden casing with a centralizer support.

5

3687. The method of claim 3664, further comprising electrically coupling a lead-in conductor to the first conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

10

3688. The method of claim 3664, further comprising electrically coupling a lead-in conductor to the first conductor, wherein the lead-in conductor comprises copper.

15

3689. The method of claim 3664, further comprising maintaining a sufficient pressure between the first conduit and the formation to substantially inhibit deformation of the first conduit.

3690. The method of claim 3664, further comprising providing a thermally conductive fluid within the first conduit.

20

3691. The method of claim 3664, further comprising providing a thermally conductive fluid within the first conduit, wherein the thermally conductive fluid comprises helium.

25

3692. The method of claim 3664, further comprising inhibiting arcing between the first conductor and the first conduit with a fluid disposed within the first conduit.

3693. The method of claim 3664, further comprising removing a vapor from the opening using a perforated tube disposed proximate to the first conduit in the opening to control a pressure in the opening.

30

3694. The method of claim 3664, further comprising flowing a corrosion-inhibiting fluid through a perforated tube disposed proximate to the first conduit in the opening.

3695. The method of claim 3664, wherein a second conductor is disposed within the first conduit, wherein the second conductor is electrically coupled to the first conductor to form an electrical circuit.

3696. The method of claim 3664, wherein a second conductor is disposed within the first conduit, wherein the second conductor is electrically coupled to the first conductor with a connector.

3697. The method of claim 3664, wherein a second conductor is disposed within a second conduit and a third conductor is disposed within a third conduit, wherein the second conduit and the third conduit are disposed in different openings of the formation, wherein the first conductor is electrically coupled to the second conductor and the third conductor, and wherein the first, second, and third conductors are configured to operate in a 3-phase Y configuration.

3698. The method of claim 3664, wherein a second conductor is disposed within the first conduit, wherein at least one sliding electrical connector is coupled to the first conductor and the second conductor, and wherein heat generated by at least the one sliding electrical connector is less than heat generated by the first conductor or the second conductor.

3699. The method of claim 3664, wherein the first conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

3700. The method of claim 3664, further comprising flowing an oxidizing fluid through an orifice in the first conduit.

3701. The method of claim 3664, further comprising disposing a perforated tube proximate to the first conduit and flowing an oxidizing fluid through the perforated tube.

3702. The method of claim 3664, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the carbon within the formation.

3703. A system configured to heat a hydrocarbon containing formation, comprising:
a first conductor disposed in a first conduit, wherein the first conduit is disposed within a first opening in the formation;

a second conductor disposed in a second conduit, wherein the second conduit is disposed within a second opening in the formation;

a third conductor disposed in a third conduit, wherein the third conduit is disposed within a third opening in the formation, wherein the first, second, and third conductors are electrically coupled in a 3-phase Y configuration, and wherein the first, second, and third conductors are configured to provide heat to at least a portion of the formation during use; and

wherein the system is configured to allow heat to transfer from the first, second, and third conductors to a selected section of the formation during use.

3704. The system of claim 3703, wherein the first, second, and third conductors are further configured to generate heat during application of an electrical current to the first conductor.

3705. The system of claim 3703, wherein the first, second, and third conductors comprise a pipe.

3706. The system of claim 3703, wherein the first, second, and third conductors comprise stainless steel.

3707. The system of claim 3703, wherein the first, second, and third openings comprise a diameter of at least approximately 5 cm.

3708. The system of claim 3703, further comprising a first sliding electrical connector coupled to the first conductor and a second sliding electrical connector coupled to the second conductor and a third sliding electrical connector coupled to the third conductor.

5

3709. The system of claim 3703, further comprising a first sliding electrical connector coupled to the first conductor, wherein the first sliding electrical connector is further coupled to the first conduit.

10

3710. The system of claim 3703, further comprising a second sliding electrical connector coupled to the second conductor, wherein the second sliding electrical connector is further coupled to the second conduit.

15

3711. The system of claim 3703, further comprising a third sliding electrical connector coupled to the third conductor, wherein the third sliding electrical connector is further coupled to the third conduit.

20

3712. The system of claim 3703, wherein each of the first, second, and third conduits comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from each of the first, second, and third conductors to the section along the first section of each of the conduits is less than heat radiated from the first, second, and third conductors to the section along the second section of each of the conduits.

25

3713. The system of claim 3703, further comprising a fluid disposed within the first, second, and third conduits, wherein the fluid is configured to maintain a pressure within the first conduit to substantially inhibit deformation of the first, second, and third conduits during use.

30

3714. The system of claim 3703, further comprising a thermally conductive fluid disposed within the first, second, and third conduits.

0984437-042401

3715. The system of claim 3703, further comprising a thermally conductive fluid disposed within the first, second, and third conduits, wherein the thermally conductive fluid comprises helium.

5

3716. The system of claim 3703, further comprising a fluid disposed within the first, second, and third conduits, wherein the fluid is configured to substantially inhibit arcing between the first, second, and third conductors and the first, second, and third conduits during use.

10

3717. The system of claim 3703, further comprising at least one tube disposed within the first, second, and third openings external to the first, second, and third conduits, wherein at least the one tube is configured to remove vapor produced from at least the heated portion of the formation such that a pressure balance is maintained between the first, second, and third conduits and the first, second, and third openings to substantially inhibit deformation of the first, second, and third conduits during use.

15

3718. The system of claim 3703, wherein the first, second, and third conductors are further configured to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

20

3719. The system of claim 3703, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation.

25

3720. The system of claim 3703, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, and wherein at least the one overburden casing comprises steel.

30

3721. The system of claim 3703, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, and wherein at least the one overburden casing is further disposed in cement.

3722. The system of claim 3703, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of at least the one overburden casing and the first, second, and third openings.

3723. The system of claim 3703, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of at least the one overburden casing and the first, second, and third openings, and wherein the packing material is further configured to substantially inhibit a flow of fluid between the first, second, and third opening and at least the one overburden casing during use.

3724. The system of claim 3703, wherein the heated section of the formation is substantially pyrolyzed.

3725. A system configurable to heat a hydrocarbon containing formation, comprising:
a first conductor configurable to be disposed in a first conduit, wherein the first conduit is configurable to be disposed within a first opening in the formation;
a second conductor configurable to be disposed in a second conduit, wherein the second conduit is configurable to be disposed within a second opening in the formation;
a third conductor configurable to be disposed in a third conduit, wherein the third conduit is configurable to be disposed within a third opening in the formation, wherein the first, second, and third conductors are further configurable to be electrically coupled

in a 3-phase Y configuration, and wherein the first, second, and third conductors are further configurable to provide heat to at least a portion of the formation during use; and wherein the system is configurable to allow heat to transfer from the first, second, and third conductors to a selected section of the formation during use.

5

3726. The system of claim 3725, wherein the first, second, and third conductors are further configurable to generate heat during application of an electrical current to the first conductor.

10

3727. The system of claim 3725, wherein the first, second, and third conductors comprise a pipe.

3728. The system of claim 3725, wherein the first, second, and third conductors comprise stainless steel.

15

3729. The system of claim 3725, wherein the first, second, and third opening comprise a diameter of at least approximately 5 cm.

20

3730. The system of claim 3725, further comprising a first sliding electrical connector coupled to the first conductor and a second sliding electrical connector coupled to the second conductor and a third sliding electrical connector coupled to the third conductor.

25

3731. The system of claim 3725, further comprising a first sliding electrical connector coupled to the first conductor, wherein the first sliding electrical connector is further coupled to the first conduit.

30

3732. The system of claim 3725, further comprising a second sliding electrical connector coupled to the second conductor, wherein the second sliding electrical connector is further coupled to the second conduit.

3733. The system of claim 3725, further comprising a third sliding electrical connector coupled to the third conductor, wherein the third sliding electrical connector is further coupled to the third conduit.

5 3734. The system of claim 3725, wherein each of the first, second, and third conduits comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from each of the first, second, and third conductors to the section along the first section of each of the conduits is less than heat radiated from the first, second, and third conductors to the section along the second section of each of the conduits.

10 3735. The system of claim 3725, further comprising a fluid disposed within the first, second, and third conduits, wherein the fluid is configurable to maintain a pressure within the first conduit to substantially inhibit deformation of the first, second, and third conduits during use.

15 3736. The system of claim 3725, further comprising a thermally conductive fluid disposed within the first, second, and third conduits.

20 3737. The system of claim 3725, further comprising a thermally conductive fluid disposed within the first, second, and third conduits, wherein the thermally conductive fluid comprises helium.

25 3738. The system of claim 3725, further comprising a fluid disposed within the first, second, and third conduits, wherein the fluid is configurable to substantially inhibit arcing between the first, second, and third conductors and the first, second, and third conduits during use.

30 3739. The system of claim 3725, further comprising at least one tube disposed within the first, second, and third openings external to the first, second, and third conduits, wherein at least the one tube is configurable to remove vapor produced from at least the

heated portion of the formation such that a pressure balance is maintained between the first, second, and third conduits and the first, second, and third openings to substantially inhibit deformation of the first, second, and third conduits during use.

5 3740. The system of claim 3725, wherein the first, second, and third conductors are further configurable to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

10 3741. The system of claim 3725, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation.

15 3742. The system of claim 3725, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, and wherein at least the one overburden casing comprises steel.

20 3743. The system of claim 3725, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, and wherein at least the one overburden casing is further disposed in cement.

25 3744. The system of claim 3725, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of at least the one overburden casing and the first, second, and third openings.

30 3745. The system of claim 3725, further comprising at least one overburden casing coupled to the first, second, and third openings, wherein at least the one overburden casing is disposed in an overburden of the formation, wherein a packing material is

09841437-042401

disposed at a junction of at least the one overburden casing and the first, second, and third openings, and wherein the packing material is further configurable to substantially inhibit a flow of fluid between the first, second, and third opening and at least the one overburden casing during use.

3746. The system of claim 3725, wherein the heated section of the formation is substantially pyrolyzed.

3747. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to a first conductor to provide heat to at least a portion of the formation, wherein the first conductor is disposed in a first conduit, and wherein the first conduit is disposed within a first opening in the formation;

applying an electrical current to a second conductor to provide heat to at least a portion of the formation, wherein the second conductor is disposed in a second conduit, and wherein the second conduit is disposed within a second opening in the formation;

applying an electrical current to a third conductor to provide heat to at least a portion of the formation, wherein the third conductor is disposed in a third conduit, and wherein the third conduit is disposed within a third opening in the formation; and

allowing the heat to transfer from the first, second, and third conductors to a selected section of the formation.

3748. The method of claim 3747, wherein the first, second, and third conductors comprise a pipe.

3749. The method of claim 3747, wherein the first, second, and third conductors comprise stainless steel.

3750. The method of claim 3747, wherein the first, second, and third conduits comprise stainless steel.

3751. The method of claim 3747, wherein the provided heat comprises approximately 650 W/m to approximately 1650 W/m.

3752. The method of claim 3747, further comprising determining a temperature distribution in the first, second, and third conduits using an electromagnetic signal provided to the first, second, and third conduits.

3753. The method of claim 3747, further comprising monitoring the applied electrical current.

3754. The method of claim 3747, further comprising monitoring a voltage applied to the first, second, and third conductors.

3755. The method of claim 3747, further comprising monitoring a temperature in the first, second, and third conduits with at least one thermocouple.

3756. The method of claim 3747, further comprising maintaining a sufficient pressure between the first, second, and third conduits and the first, second, and third openings to substantially inhibit deformation of the first, second, and third conduits.

3757. The method of claim 3747, further comprising providing a thermally conductive fluid within the first, second, and third conduits.

3758. The method of claim 3747, further comprising providing a thermally conductive fluid within the first, second, and third conduits, wherein the thermally conductive fluid comprises helium.

3759. The method of claim 3747, further comprising inhibiting arcing between the first, second, and third conductors and the first, second, and third conduits with a fluid disposed within the first, second, and third conduits.

3760. The method of claim 3747, further comprising removing a vapor from the first, second, and third openings using at least one perforated tube disposed proximate to the first, second, and third conduits in the first, second, and third openings to control a pressure in the first, second, and third openings.

3761. The method of claim 3747, wherein the first, second, and third conduits comprise a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first, second, and third conductors to the section along the first section of the first, second, and third conduits is less than heat radiated from the first, second, and third conductors to the section along the second section of the first, second, and third conduits.

3762. The method of claim 3747, further comprising flowing an oxidizing fluid through an orifice in the first, second, and third conduits.

3763. The method of claim 3747, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the carbon within the formation.

3764. A system configured to heat a hydrocarbon containing formation, comprising:
a first conductor disposed in a conduit, wherein the conduit is disposed within an opening in the formation; and

a second conductor disposed in the conduit, wherein the second conductor is electrically coupled to the first conductor with a connector, and wherein the first and second conductors are configured to provide heat to at least a portion of the formation during use; and

wherein the system is configured to allow heat to transfer from the first and second conductors to a selected section of the formation during use.

3765. The system of claim 3764, wherein the first conductor is further configured to generate heat during application of an electrical current to the first conductor.

0984-1437-042401

3766. The system of claim 3764, wherein the first and second conductors comprise a pipe.

3767. The system of claim 3764, wherein the first and second conductors comprise stainless steel.

3768. The system of claim 3764, wherein the conduit comprises stainless steel.

3769. The system of claim 3764, further comprising a centralizer configured to maintain a location of the first and second conductors within the conduit.

3770. The system of claim 3764, further comprising a centralizer configured to maintain a location of the first and second conductors within the conduit, wherein the centralizer comprises ceramic material.

3771. The system of claim 3764, further comprising a centralizer configured to maintain a location of the first and second conductors within the conduit, wherein the centralizer comprises ceramic material and stainless steel.

3772. The system of claim 3764, wherein the opening comprises a diameter of at least approximately 5 cm.

3773. The system of claim 3764, further comprising a lead-in conductor coupled to the first and second conductors, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

3774. The system of claim 3764, further comprising a lead-in conductor coupled to the first and second conductors, wherein the lead-in conductor comprises copper.

3775. The system of claim 3764, wherein the conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the

second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

5 3776. The system of claim 3764, further comprising a fluid disposed within the conduit, wherein the fluid is configured to maintain a pressure within the conduit to substantially inhibit deformation of the conduit during use.

10 3777. The system of claim 3764, further comprising a thermally conductive fluid disposed within the conduit.

3778. The system of claim 3764, further comprising a thermally conductive fluid disposed within the conduit, wherein the thermally conductive fluid comprises helium.

15 3779. The system of claim 3764, further comprising a fluid disposed within the conduit, wherein the fluid is configured to substantially inhibit arcing between the first and second conductors and the conduit during use.

20 3780. The system of claim 3764, further comprising a tube disposed within the opening external to the conduit, wherein the tube is configured to remove vapor produced from at least the heated portion of the formation such that a pressure balance is maintained between the conduit and the opening to substantially inhibit deformation of the conduit during use.

25 3781. The system of claim 3764, wherein the first and second conductors are further configured to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

30 3782. The system of claim 3764, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

09841437-042401

3783. The system of claim 3764, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

5

3784. The system of claim 3764, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

10

3785. The system of claim 3764, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

15

3786. The system of claim 3764, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

20

3787. The system of claim 3764, wherein the heated section of the formation is substantially pyrolyzed.

25

3788. A system configurable to heat a hydrocarbon containing formation, comprising:
a first conductor configurable to be disposed in a conduit, wherein the conduit is configurable to be disposed within an opening in the formation; and
a second conductor configurable to be disposed in the conduit, wherein the second conductor is configurable to be electrically coupled to the first conductor with a connector, and wherein the first and second conductors are further configurable to provide heat to at least a portion of the formation during use; and

30

wherein the system is configurable to allow heat to transfer from the first and second conductors to a selected section of the formation during use.

5 3789. The system of claim 3788, wherein the first conductor is further configurable to generate heat during application of an electrical current to the first conductor.

3790. The system of claim 3788, wherein the first and second conductors comprise a pipe.

10 3791. The system of claim 3788, wherein the first and second conductors comprise stainless steel.

3792. The system of claim 3788, wherein the conduit comprises stainless steel.

15 3793. The system of claim 3788, further comprising a centralizer configurable to maintain a location of the first and second conductors within the conduit.

20 3794. The system of claim 3788, further comprising a centralizer configurable to maintain a location of the first and second conductors within the conduit, wherein the centralizer comprises ceramic material.

25 3795. The system of claim 3788, further comprising a centralizer configurable to maintain a location of the first and second conductors within the conduit, wherein the centralizer comprises ceramic material and stainless steel.

3796. The system of claim 3788, wherein the opening comprises a diameter of at least approximately 5 cm.

30 3797. The system of claim 3788, further comprising a lead-in conductor coupled to the first and second conductors, wherein the lead-in conductor comprises a low resistance conductor configurable to generate substantially no heat.

FOI b7D - 042437

3798. The system of claim 3788, further comprising a lead-in conductor coupled to the first and second conductors, wherein the lead-in conductor comprises copper.

5 3799. The system of claim 3788, wherein the conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

10 3800. The system of claim 3788, further comprising a fluid disposed within the conduit, wherein the fluid is configurable to maintain a pressure within the conduit to substantially inhibit deformation of the conduit during use.

15 3801. The system of claim 3788, further comprising a thermally conductive fluid disposed within the conduit.

3802. The system of claim 3788, further comprising a thermally conductive fluid disposed within the conduit, wherein the thermally conductive fluid comprises helium.

20 3803. The system of claim 3788, further comprising a fluid disposed within the conduit, wherein the fluid is configurable to substantially inhibit arcing between the first and second conductors and the conduit during use.

25 3804. The system of claim 3788, further comprising a tube disposed within the opening external to the conduit, wherein the tube is configurable to remove vapor produced from at least the heated portion of the formation such that a pressure balance is maintained between the conduit and the opening to substantially inhibit deformation of the conduit during use.

30

3805. The system of claim 3788, wherein the first and second conductors are further configurable to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

5 3806. The system of claim 3788, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

10 3807. The system of claim 3788, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

15 3808. The system of claim 3788, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

20 3809. The system of claim 3788, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

25 3810. The system of claim 3788, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

30 3811. The system of claim 3788, wherein the heated section of the formation is substantially pyrolyzed.

3812. An in situ method for heating a hydrocarbon containing formation, comprising:

applying an electrical current to at least two conductors to provide heat to at least a portion of the formation, wherein at least the two conductors are disposed within a conduit, wherein the conduit is disposed within an opening in the formation, and wherein at least the two conductors are electrically coupled with a connector; and

5 allowing heat to transfer from at least the two conductors to a selected section of the formation.

3813. The method of claim 3812, wherein at least the two conductors comprise a pipe.

10 3814. The method of claim 3812, wherein at least the two conductors comprise stainless steel.

3815. The method of claim 3812, wherein the conduit comprises stainless steel.

15 3816. The method of claim 3812, further comprising maintaining a location of at least the two conductors in the conduit with a centralizer.

20 3817. The method of claim 3812, further comprising maintaining a location of at least the two conductors in the conduit with a centralizer, wherein the centralizer comprises ceramic material.

25 3818. The method of claim 3812, further comprising maintaining a location of at least the two conductors in the conduit with a centralizer, wherein the centralizer comprises ceramic material and stainless steel.

3819. The method of claim 3812, wherein the provided heat comprises approximately 650 W/m to approximately 1650 W/m.

30 3820. The method of claim 3812, further comprising determining a temperature distribution in the conduit using an electromagnetic signal provided to the conduit.

3821. The method of claim 3812, further comprising monitoring the applied electrical current.

3822. The method of claim 3812, further comprising monitoring a voltage applied to at least the two conductors.

3823. The method of claim 3812, further comprising monitoring a temperature in the conduit with at least one thermocouple.

3824. The method of claim 3812, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3825. The method of claim 3812, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3826. The method of claim 3812, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3827. The method of claim 3812, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3828. The method of claim 3812, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with a packing material.

3829. The method of claim 3812, further comprising maintaining a sufficient pressure between the conduit and the formation to substantially inhibit deformation of the conduit.

3830. The method of claim 3812, further comprising providing a thermally conductive fluid within the conduit.

3831. The method of claim 3812, further comprising providing a thermally conductive fluid within the conduit, wherein the thermally conductive fluid comprises helium.

3832. The method of claim 3812, further comprising inhibiting arcing between at least the two conductors and the conduit with a fluid disposed within the conduit.

3833. The method of claim 3812, further comprising removing a vapor from the opening using a perforated tube disposed proximate to the conduit in the opening to control a pressure in the opening.

3834. The method of claim 3812, further comprising flowing a corrosion inhibiting fluid through a perforated tube disposed proximate to the conduit in the opening.

3835. The method of claim 3812, wherein the conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

3836. The method of claim 3812, further comprising flowing an oxidizing fluid through an orifice in the conduit.

3837. The method of claim 3812, further comprising disposing a perforated tube proximate to the conduit and flowing an oxidizing fluid through the perforated tube.

3838. ~~The method of claim 3812, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the carbon within the formation.~~

3839. A system configured to heat a hydrocarbon containing formation, comprising:

5 at least one conductor disposed in a conduit, wherein the conduit is disposed within an opening in the formation, and wherein at least the one conductor is configured to provide heat to at least a first portion of the formation during use,

10 at least one sliding connector, wherein at least the one sliding connector is coupled to at least the one conductor, wherein at least the one sliding connector is configured to provide heat during use, and wherein heat provided by at least the one sliding connector is substantially less than the heat provided by at least the one conductor during use; and

15 wherein the system is configured to allow heat to transfer from at least the one conductor to a section of the formation during use.

3840. The system of claim 3839, wherein at least the one conductor is further configured to generate heat during application of an electrical current to at least the one conductor.

20 3841. The system of claim 3839, wherein at least the one conductor comprises a pipe.

3842. The system of claim 3839, wherein at least the one conductor comprises stainless steel.

25 3843. The system of claim 3839, wherein the conduit comprises stainless steel.

3844. The system of claim 3839, further comprising a centralizer configured to maintain a location of at least the one conductor within the conduit.

09841437-042401

3845. The system of claim 3839, further comprising a centralizer configured to maintain a location of at least the one conductor within the conduit, wherein the centralizer comprises ceramic material.

5 3846. The system of claim 3839, further comprising a centralizer configured to maintain a location of at least the one conductor within the conduit, wherein the centralizer comprises ceramic material and stainless steel.

10 3847. The system of claim 3839, wherein the opening comprises a diameter of at least approximately 5 cm.

15 3848. The system of claim 3839, further comprising a lead-in conductor coupled to at least the one conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

3849. The system of claim 3839, further comprising a lead-in conductor coupled to at least the one conductor, wherein the lead-in conductor comprises copper.

20 3850. The system of claim 3839, wherein the conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

25 3851. The system of claim 3839, further comprising a fluid disposed within the conduit, wherein the fluid is configured to maintain a pressure within the conduit to substantially inhibit deformation of the conduit during use.

30 3852. The system of claim 3839, further comprising a thermally conductive fluid disposed within the conduit.

3853. The system of claim 3839, further comprising a thermally conductive fluid disposed within the conduit, wherein the thermally conductive fluid comprises helium.

3854. The system of claim 3839, further comprising a fluid disposed within the conduit, wherein the fluid is configured to substantially inhibit arcing between at least the one conductor and the conduit during use.

3855. The system of claim 3839, further comprising a tube disposed within the opening external to the conduit, wherein the tube is configured to remove vapor produced from at least the heated portion of the formation such that a pressure balance is maintained between the conduit and the opening to substantially inhibit deformation of the conduit during use.

3856. The system of claim 3839, wherein at least the one conductor is further configured to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

3857. The system of claim 3839, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3858. The system of claim 3839, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3859. The system of claim 3839, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3860. The system of claim 3839, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the

formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

5 3861. The system of claim 3839, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

10 3862. The system of claim 3839, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to at least the one conductor.

15 3863. The system of claim 3839, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to at least the one conductor, and wherein the substantially low resistance conductor comprises carbon steel.

20 3864. The system of claim 3839, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing and a centralizer configured to support the substantially low resistance conductor within the overburden casing.

25 3865. The system of claim 3839, wherein the heated section of the formation is substantially pyrolyzed.

30 3866. A system configurable to heat a hydrocarbon containing formation, comprising:
at least one conductor configurable to be disposed in a conduit, wherein the conduit is configurable to be disposed within an opening in the formation, and wherein at

104240 2E44360

least the one conductor is further configurable to provide heat to at least a first portion of the formation during use;

at least one sliding connector, wherein at least the one sliding connector is configurable to be coupled to at least the one conductor, wherein at least the one sliding connector is further configurable to provide heat during use, and wherein heat provided by at least the one sliding connector is substantially less than the heat provided by at least the one conductor during use; and

wherein the system is configurable to allow heat to transfer from at least the one conductor to a section of the formation during use.

3867. The system of claim 3866, wherein at least the one conductor is further configurable to generate heat during application of an electrical current to at least the one conductor.

3868. The system of claim 3866, wherein at least the one conductor comprises a pipe.

3869. The system of claim 3866, wherein at least the one conductor comprises stainless steel.

3870. The system of claim 3866, wherein the conduit comprises stainless steel.

3871. The system of claim 3866, further comprising a centralizer configurable to maintain a location of at least the one conductor within the conduit.

3872. The system of claim 3866, further comprising a centralizer configurable to maintain a location of at least the one conductor within the conduit, wherein the centralizer comprises ceramic material.

3873. The system of claim 3866, further comprising a centralizer configurable to maintain a location of at least the one conductor within the conduit, wherein the centralizer comprises ceramic material and stainless steel.

09841437-042401

3874. The system of claim 3866, wherein the opening comprises a diameter of at least approximately 5 cm.

5 3875. The system of claim 3866, further comprising a lead-in conductor coupled to at least the one conductor, wherein the lead-in conductor comprises a low resistance conductor configurable to generate substantially no heat.

10 3876. The system of claim 3866, further comprising a lead-in conductor coupled to at least the one conductor, wherein the lead-in conductor comprises copper.

15 3877. The system of claim 3866, wherein the conduit comprises a first section and a second section, wherein a thickness of the first section is greater than a thickness of the second section such that heat radiated from the first conductor to the section along the first section of the conduit is less than heat radiated from the first conductor to the section along the second section of the conduit.

20 3878. The system of claim 3866, further comprising a fluid disposed within the conduit, wherein the fluid is configurable to maintain a pressure within the conduit to substantially inhibit deformation of the conduit during use.

3879. The system of claim 3866, further comprising a thermally conductive fluid disposed within the conduit.

25 3880. The system of claim 3866, further comprising a thermally conductive fluid disposed within the conduit, wherein the thermally conductive fluid comprises helium.

30 3881. The system of claim 3866, further comprising a fluid disposed within the conduit, wherein the fluid is configurable to substantially inhibit arcing between at least the one conductor and the conduit during use.

3882. The system of claim 3866, further comprising a tube disposed within the opening external to the conduit, wherein the tube is configurable to remove vapor produced from at least the heated portion of the formation such that a pressure balance is maintained between the conduit and the opening to substantially inhibit deformation of the conduit during use.

3883. The system of claim 3866, wherein at least the one conductor is further configurable to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

3884. The system of claim 3866, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3885. The system of claim 3866, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3886. The system of claim 3866, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3887. The system of claim 3866, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3888. The system of claim 3866, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing

and the opening, and wherein the packing material is further configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3889. The system of claim 3866, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to at least the one conductor.

3890. The system of claim 3866, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to at least the one conductor, and wherein the substantially low resistance conductor comprises carbon steel.

3891. The system of claim 3866, further comprising an overburden casing coupled to the opening and a substantially low resistance conductor disposed within the overburden casing and a centralizer configurable to support the substantially low resistance conductor within the overburden casing.

3892. The system of claim 3866, wherein the heated section of the formation is substantially pyrolyzed.

3893. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to at least one conductor and at least one sliding connector to provide heat to at least a portion of the formation, wherein at least the one conductor and at least the one sliding connector are disposed within a conduit, and wherein heat provided by at least the one conductor is substantially greater than heat provided by at least the one sliding connector; and

allowing the heat to transfer from at least the one conductor and at least the one sliding connector to a section of the formation.

3894. The method of claim 3893, wherein at least the one conductor comprises a pipe.

3895. The method of claim 3893, wherein at least the one conductor comprises stainless steel.

3896. The method of claim 3893, wherein the conduit comprises stainless steel.

3897. The method of claim 3893, further comprising maintaining a location of at least the one conductor in the conduit with a centralizer.

3898. The method of claim 3893, further comprising maintaining a location of at least the one conductor in the conduit with a centralizer, wherein the centralizer comprises ceramic material.

3899. The method of claim 3893, further comprising maintaining a location of at least the one conductor in the conduit with a centralizer, wherein the centralizer comprises ceramic material and stainless steel.

3900. The method of claim 3893, wherein the provided heat comprises approximately 650 W/m to approximately 1650 W/m.

3901. The method of claim 3893, further comprising determining a temperature distribution in the conduit using an electromagnetic signal provided to the conduit.

3902. The method of claim 3893, further comprising monitoring the applied electrical current.

3903. The method of claim 3893, further comprising monitoring a voltage applied to at least the one conductor.

3904. The method of claim 3893, further comprising monitoring a temperature in the conduit with at least one thermocouple.

3905. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3906. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3907. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3908. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3909. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with a packing material.

3910. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein a substantially low resistance conductor is disposed within the overburden casing, and wherein the substantially low resistance conductor is electrically coupled to at least the one conductor.

5 3911. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein a substantially low resistance conductor is disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to at least the one conductor, and wherein the substantially low resistance conductor comprises carbon steel.

10 3912. The method of claim 3893, further comprising coupling an overburden casing to the opening, wherein a substantially low resistance conductor is disposed within the overburden casing, wherein the substantially low resistance conductor is electrically coupled to at least the one conductor, and wherein the method further comprises maintaining a location of the substantially low resistance conductor in the overburden casing with a centralizer support.

15 3913. The method of claim 3893, further comprising electrically coupling a lead-in conductor to at least the one conductor, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

20 3914. The method of claim 3893, further comprising electrically coupling a lead-in conductor to at least the one conductor, wherein the lead-in conductor comprises copper.

3915. The method of claim 3893, further comprising maintaining a sufficient pressure between the conduit and the formation to substantially inhibit deformation of the conduit.

25 3916. The method of claim 3893, further comprising providing a thermally conductive fluid within the conduit.

3917. The method of claim 3893, further comprising providing a thermally conductive fluid within the conduit, wherein the thermally conductive fluid comprises helium.

30 3918. The method of claim 3893, further comprising inhibiting arcing between the conductor and the conduit with a fluid disposed within the conduit.

3919. The method of claim 3893, further comprising removing a vapor from the opening using a perforated tube disposed proximate to the conduit in the opening to control a pressure in the opening.

3920. The method of claim 3893, further comprising flowing a corrosion inhibiting fluid through a perforated tube disposed proximate to the conduit in the opening.

3921. The method of claim 3893, further comprising flowing an oxidizing fluid through an orifice in the conduit.

3922. The method of claim 3893, further comprising disposing a perforated tube proximate to the conduit and flowing an oxidizing fluid through the perforated tube.

3923. The method of claim 3893, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the carbon within the formation.

3924. A system configured to heat a hydrocarbon containing formation, comprising:
 at least one elongated member disposed within an opening in the formation,
 wherein at least the one elongated member is configured to provide heat to at least a portion of the formation during use; and
 wherein the system is configured to allow heat to transfer from at least the one elongated member to a section of the formation during use.

3925. The system of claim 3924, wherein at least the one elongated member comprises stainless steel.

3926. The system of claim 3924, wherein at least the one elongated member is further configured to generate heat during application of an electrical current to at least the one elongated member.

09841437-04240-1

3927. The system of claim 3924, further comprising a support member coupled to at least the one elongated member, wherein the support member is configured to support at least the one elongated member.

5 3928. The system of claim 3924, further comprising a support member coupled to at least the one elongated member, wherein the support member is configured to support at least the one elongated member, and wherein the support member comprises openings.

10 3929. The system of claim 3924, further comprising a support member coupled to at least the one elongated member, wherein the support member is configured to support at least the one elongated member, wherein the support member comprises openings, wherein the openings are configured to flow a fluid along a length of at least the one elongated member during use, and wherein the fluid is configured to substantially inhibit carbon deposition on or proximate to at least the one elongated member during use.

15 3930. The system of claim 3924, further comprising a tube disposed in the opening, wherein the tube comprises openings, wherein the openings are configured to flow a fluid along a length of at least the one elongated member during use, and wherein the fluid is configured to substantially inhibit carbon deposition on or proximate to at least the one elongated member during use.

20 3931. The system of claim 3924, further comprising a centralizer coupled to at least the one elongated member, wherein the centralizer is configured to electrically isolate at least the one elongated member.

25 3932. The system of claim 3924, further comprising a centralizer coupled to at least the one elongated member and a support member coupled to at least the one elongated member, wherein the centralizer is configured to maintain a location of at least the one elongated member on the support member.

30

09841437-042401

3933. The system of claim 3924, wherein the opening comprises a diameter of at least approximately 5 cm.

3934. The system of claim 3924, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

3935. The system of claim 3924, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a rubber insulated conductor.

3936. The system of claim 3924, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises copper wire.

3937. The system of claim 3924, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor.

3938. The system of claim 3924, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3939. The system of claim 3924, wherein at least the one elongated member is arranged in a series electrical configuration.

3940. The system of claim 3924, wherein at least the one elongated member is arranged in a parallel electrical configuration.

3941. The system of claim 3924, wherein at least the one elongated member is configured to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

3942. The system of claim 3924, further comprising a perforated tube disposed in the opening external to at least the one elongated member, wherein the perforated tube is configured to remove vapor from the opening to control a pressure in the opening during use.

3943. The system of claim 3924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3944. The system of claim 3924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3945. The system of claim 3924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3946. The system of claim 3924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3947. The system of claim 3924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3948. The system of claim 3924, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing

and the opening, and wherein the packing material is further configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3949. The system of claim 3924, wherein the heated section of the formation is substantially pyrolyzed.

3950. A system configurable to heat a hydrocarbon containing formation, comprising:
at least one elongated member configurable to be disposed within an opening in the formation, wherein at least the one elongated member is further configurable to provide heat to at least a portion of the formation during use; and
wherein the system is configurable to allow heat to transfer from at least the one elongated member to a section of the formation during use.

3951. The system of claim 3950, wherein at least the one elongated member comprises stainless steel.

3952. The system of claim 3950, wherein at least the one elongated member is further configurable to generate heat during application of an electrical current to at least the one elongated member.

3953. The system of claim 3950, further comprising a support member coupled to at least the one elongated member, wherein the support member is configurable to support at least the one elongated member.

3954. The system of claim 3950, further comprising a support member coupled to at least the one elongated member, wherein the support member is configurable to support at least the one elongated member, and wherein the support member comprises openings.

3955. The system of claim 3950, further comprising a support member coupled to at least the one elongated member, wherein the support member is configurable to support at least the one elongated member, wherein the support member comprises openings,

09841437-042401

wherein the openings are configurable to flow a fluid along a length of at least the one elongated member during use, and wherein the fluid is configurable to substantially inhibit carbon deposition on or proximate to at least the one elongated member during use.

5

3956. The system of claim 3950, further comprising a tube disposed in the opening, wherein the tube comprises openings, wherein the openings are configurable to flow a fluid along a length of at least the one elongated member during use, and wherein the fluid is configurable to substantially inhibit carbon deposition on or proximate to at least the one elongated member during use.

10

3957. The system of claim 3950, further comprising a centralizer coupled to at least the one elongated member, wherein the centralizer is configurable to electrically isolate at least the one elongated member.

15

3958. The system of claim 3950, further comprising a centralizer coupled to at least the one elongated member and a support member coupled to at least the one elongated member, wherein the centralizer is configurable to maintain a location of at least the one elongated member on the support member.

20

3959. The system of claim 3950, wherein the opening comprises a diameter of at least approximately 5 cm.

3960. The system of claim 3950, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a low resistance conductor configurable to generate substantially no heat.

25

3961. The system of claim 3950, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a rubber insulated conductor.

30

3962. The system of claim 3950, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises copper wire.

3963. The system of claim 3950, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor.

3964. The system of claim 3950, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

3965. The system of claim 3950, wherein at least the one elongated member is arranged in a series electrical configuration.

3966. The system of claim 3950, wherein at least the one elongated member is arranged in a parallel electrical configuration.

3967. The system of claim 3950, wherein at least the one elongated member is configurable to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

3968. The system of claim 3950, further comprising a perforated tube disposed in the opening external to at least the one elongated member, wherein the perforated tube is configurable to remove vapor from the opening to control a pressure in the opening during use.

3969. The system of claim 3950, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

0984-1437-0424-01

3970. The system of claim 3950, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

3971. The system of claim 3950, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

3972. The system of claim 3950, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

3973. The system of claim 3950, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

3974. The system of claim 3950, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

3975. The system of claim 3950, wherein the heated section of the formation is substantially pyrolyzed.

3976. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to at least one elongated member to provide heat to at least a portion of the formation, wherein at least the one elongated member is disposed within an opening of the formation; and

allowing heat to transfer from at least the one elongated member to a section of the formation.

3977. The method of claim 3976, wherein at least the one elongated member comprises a metal strip.

3978. The method of claim 3976, wherein at least the one elongated member comprises a metal rod.

3979. The method of claim 3976, wherein at least the one elongated member comprises stainless steel.

3980. The method of claim 3976, further comprising supporting at least the one elongated member on a center support member.

3981. The method of claim 3976, further comprising supporting at least the one elongated member on a center support member, wherein the center support member comprises a tube.

3982. The method of claim 3976, further comprising electrically isolating at least the one elongated member with a centralizer.

3983. The method of claim 3976, further comprising laterally spacing at least the one elongated member with a centralizer.

3984. The method of claim 3976, further comprising electrically coupling at least the one elongated member in a series configuration.

3985. The method of claim 3976, further comprising electrically coupling at least the one elongated member in a parallel configuration.

3986. The method of claim 3976, wherein the provided heat comprises approximately 650 W/m to approximately 1650 W/m.

3987. The method of claim 3976, further comprising determining a temperature distribution in at least the one elongated member using an electromagnetic signal provided to at least the one elongated member.

3988. The method of claim 3976, further comprising monitoring the applied electrical current.

3989. The method of claim 3976, further comprising monitoring a voltage applied to at least the one elongated member.

3990. The method of claim 3976, further comprising monitoring a temperature in at least the one elongated member with at least one thermocouple.

3991. The method of claim 3976, further comprising supporting at least the one elongated member on a center support member, wherein the center support member comprises openings, the method further comprising flowing an oxidizing fluid through the openings to substantially inhibit carbon deposition proximate to or on at least the one elongated member.

3992. The method of claim 3976, further comprising flowing an oxidizing fluid through a tube disposed proximate to at least the one elongated member to substantially inhibit carbon deposition proximate to or on at least the one elongated member.

3993. The method of claim 3976, further comprising flowing an oxidizing fluid through an opening in at least the one elongated member to substantially inhibit carbon deposition proximate to or on at least the one elongated member.

3994. The method of claim 3976, further comprising electrically coupling a lead-in conductor to at least the one elongated member, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

5 3995. The method of claim 3976, further comprising electrically coupling a lead-in conductor to at least the one elongated member using a cold pin transition conductor.

10 3996. The method of claim 3976, further comprising electrically coupling a lead-in conductor to at least the one elongated member using a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

15 3997. The method of claim 3976, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

3998. The method of claim 3976, further comprising coupling an overburden casing to the opening, wherein the overburden casing comprises steel.

20 3999. The method of claim 3976, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in cement.

25 4000. The method of claim 3976, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

30 4001. The method of claim 3976, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with the packing material.

4002. The method of claim 3976, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the carbon within the formation.

4003. A system configured to heat a hydrocarbon containing formation, comprising:

at least one elongated member disposed within an opening in the formation, wherein at least the one elongated member is configured to provide heat to at least a portion of the formation during use;

an oxidizing fluid source;

a conduit disposed within the opening, wherein the conduit is configured to provide an oxidizing fluid from the oxidizing fluid source to the opening during use, and wherein the oxidizing fluid is selected to substantially inhibit carbon deposition on or proximate to at least the one elongated member during use; and

wherein the system is configured to allow heat to transfer from at least the one elongated member to a section of the formation during use.

4004. The system of claim 4003, wherein at least the one elongated member comprises stainless steel.

4005. The system of claim 4003, wherein at least the one elongated member is further configured to generate heat during application of an electrical current to at least the one elongated member.

4006. The system of claim 4003, wherein at least the one elongated member is coupled to the conduit, wherein the conduit is further configured to support at least the one elongated member.

4007. The system of claim 4003, wherein at least the one elongated member is coupled to the conduit, wherein the conduit is further configured to support at least the one elongated member, and wherein the conduit comprises openings.

09841437-042401

4008. The system of claim 4003, further comprising a centralizer coupled to at least the one elongated member and the conduit, wherein the centralizer is configured to electrically isolate at least the one elongated member from the conduit.

5 4009. The system of claim 4003, further comprising a centralizer coupled to at least the one elongated member and the conduit, wherein the centralizer is configured to maintain a location of at least the one elongated member on the conduit.

10 4010. The system of claim 4003, wherein the opening comprises a diameter of at least approximately 5 cm.

15 4011. The system of claim 4003, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

20 4012. The system of claim 4003, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a rubber insulated conductor.

25 4013. The system of claim 4003, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises copper wire.

30 4014. The system of claim 4003, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor.

4015. The system of claim 4003, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

4016. The system of claim 4003, wherein at least the one elongated member is arranged in a series electrical configuration.

4017. The system of claim 4003, wherein at least the one elongated member is arranged in a parallel electrical configuration.

5 4018. The system of claim 4003, wherein at least the one elongated member is configured to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

10 4019. The system of claim 4003, further comprising a perforated tube disposed in the opening external to at least the one elongated member, wherein the perforated tube is configured to remove vapor from the opening to control a pressure in the opening during use.

15 4020. The system of claim 4003, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

20 4021. The system of claim 4003, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

25 4022. The system of claim 4003, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

30 4023. The system of claim 4003, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

098443-04240-2

4024. The system of claim 4003, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

5

4025. The system of claim 4003, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configured to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

10

4026. The system of claim 4003, wherein the heated section of the formation is substantially pyrolyzed.

15

4027. A system configurable to heat a hydrocarbon containing formation, comprising:
at least one elongated member configurable to be disposed within an opening in the formation, wherein at least the one elongated member is further configurable to provide heat to at least a portion of the formation during use;

20

a conduit configurable to be disposed within the opening, wherein the conduit is further configurable to provide an oxidizing fluid from the oxidizing fluid source to the opening during use, and wherein the system is configurable to allow the oxidizing fluid to substantially inhibit carbon deposition on or proximate to at least the one elongated member during use; and

25

wherein the system is further configurable to allow heat to transfer from at least the one elongated member to a section of the formation during use.

4028. The system of claim 4027, wherein at least the one elongated member comprises stainless steel.

4029. The system of claim 4027, wherein at least the one elongated member is further configurable to generate heat during application of an electrical current to at least the one elongated member.

5 4030. The system of claim 4027, wherein at least the one elongated member is coupled to the conduit, wherein the conduit is further configurable to support at least the one elongated member.

10 4031. The system of claim 4027, wherein at least the one elongated member is coupled to the conduit, wherein the conduit is further configurable to support at least the one elongated member, and wherein the conduit comprises openings.

15 4032. The system of claim 4027, further comprising a centralizer coupled to at least the one elongated member and the conduit, wherein the centralizer is configurable to electrically isolate at least the one elongated member from the conduit.

20 4033. The system of claim 4027, further comprising a centralizer coupled to at least the one elongated member and the conduit, wherein the centralizer is configurable to maintain a location of at least the one elongated member on the conduit.

4034. The system of claim 4027, wherein the opening comprises a diameter of at least approximately 5 cm.

25 4035. The system of claim 4027, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a low resistance conductor configurable to generate substantially no heat.

30 4036. The system of claim 4027, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises a rubber insulated conductor.

4037. The system of claim 4027, further comprising a lead-in conductor coupled to at least the one elongated member, wherein the lead-in conductor comprises copper wire.

4038. The system of claim 4027, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor.

4039. The system of claim 4027, further comprising a lead-in conductor coupled to at least the one elongated member with a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

4040. The system of claim 4027, wherein at least the one elongated member is arranged in a series electrical configuration.

4041. The system of claim 4027, wherein at least the one elongated member is arranged in a parallel electrical configuration.

4042. The system of claim 4027, wherein at least the one elongated member is configurable to generate radiant heat of approximately 650 W/m to approximately 1650 W/m during use.

4043. The system of claim 4027, further comprising a perforated tube disposed in the opening external to at least the one elongated member, wherein the perforated tube is configurable to remove vapor from the opening to control a pressure in the opening during use.

4044. The system of claim 4027, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation.

09841437-042401

4045. The system of claim 4027, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

5 4046. The system of claim 4027, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

10 4047. The system of claim 4027, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the opening.

15 4048. The system of claim 4027, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material comprises cement.

20 4049. The system of claim 4027, further comprising an overburden casing coupled to the opening, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the packing material is further configurable to substantially inhibit a flow of fluid between the opening and the overburden casing during use.

25 4050. The system of claim 4027, wherein the heated section of the formation is substantially pyrolyzed.

30 4051. An in situ method for heating a hydrocarbon containing formation, comprising:
applying an electrical current to at least one elongated member to provide heat to at least a portion of the formation, wherein at least the one elongated member is disposed within an opening in the formation;

providing an oxidizing fluid to at least the one elongated member to substantially inhibit carbon deposition on or proximate to at least the one elongated member; and allowing heat to transfer from at least the one elongated member to a section of the formation.

5

4052. The method of claim 4051, wherein at least the one elongated member comprises a metal strip.

10

4053. The method of claim 4051, wherein at least the one elongated member comprises a metal rod.

4054. The method of claim 4051, wherein at least the one elongated member comprises stainless steel.

15

4055. The method of claim 4051, further comprising supporting at least the one elongated member on a center support member.

20

4056. The method of claim 4051, further comprising supporting at least the one elongated member on a center support member, wherein the center support member comprises a tube.

4057. The method of claim 4051, further comprising electrically isolating at least the one elongated member with a centralizer.

25

4058. The method of claim 4051, further comprising laterally spacing at least the one elongated member with a centralizer.

30

4059. The method of claim 4051, further comprising electrically coupling at least the one elongated member in a series configuration.

4060. The method of claim 4051, further comprising electrically coupling at least the one elongated member in a parallel configuration.

5 4061. The method of claim 4051, wherein the provided heat comprises approximately 650 W/m to approximately 1650 W/m.

10 4062. The method of claim 4051, further comprising determining a temperature distribution in at least the one elongated member using an electromagnetic signal provided to at least the one elongated member.

15 4063. The method of claim 4051, further comprising monitoring the applied electrical current.

20 4064. The method of claim 4051, further comprising monitoring a voltage applied to at least the one elongated member.

25 4065. The method of claim 4051, further comprising monitoring a temperature in at least the one elongated member with at least one thermocouple.

4066. The method of claim 4051, further comprising supporting at least the one elongated member on a center support member, wherein the center support member comprises openings, wherein providing the oxidizing fluid to at least the one elongated member comprises flowing the oxidizing fluid through the openings in the center support member.

4067. The method of claim 4051, wherein providing the oxidizing fluid to at least the one elongated member comprises flowing the oxidizing fluid through orifices in a tube disposed in the opening proximate to at least the one elongated member.

FOH240" 4E4F4860

4068. The method of claim 4051, further comprising electrically coupling a lead-in conductor to at least the one elongated member, wherein the lead-in conductor comprises a low resistance conductor configured to generate substantially no heat.

5 4069. The method of claim 4051, further comprising electrically coupling a lead-in conductor to at least the one elongated member using a cold pin transition conductor.

4070. The method of claim 4051, further comprising electrically coupling a lead-in conductor to at least the one elongated member using a cold pin transition conductor, wherein the cold pin transition conductor comprises a substantially low resistance insulated conductor.

10

4071. The method of claim 4051, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in an overburden of the formation.

15

4072. The method of claim 4051, further comprising coupling an overburden casing to the opening, wherein the overburden casing comprises steel.

20 4073. The method of claim 4051, further comprising coupling an overburden casing to the opening, wherein the overburden casing is disposed in cement.

4074. The method of claim 4051, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening.

25

4075. The method of claim 4051, further comprising coupling an overburden casing to the opening, wherein a packing material is disposed at a junction of the overburden casing and the opening, and wherein the method further comprises inhibiting a flow of fluid between the opening and the overburden casing with the packing material.

30

4076. The method of claim 4051, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the carbon within the formation.

4077. An in situ method for heating a hydrocarbon containing formation, comprising:

5 oxidizing a fuel fluid in a heater;
providing at least a portion of the oxidized fuel fluid into a conduit disposed in an opening of the formation;
allowing heat to transfer from the oxidized fuel fluid to a section of the formation;
and

10 allowing additional heat to transfer from an electric heater disposed in the opening to the section of the formation, wherein heat is allowed to transfer substantially uniformly along a length of the opening.

4078. The method of claim 4077, wherein providing at least the portion of the oxidized fuel fluid into the opening comprises flowing the oxidized fuel fluid through a perforated conduit disposed in the opening.

4079. The method of claim 4077, wherein providing at least the portion of the oxidized fuel fluid into the opening comprises flowing the oxidized fuel fluid through a perforated conduit disposed in the opening, the method further comprising removing an exhaust fluid through the opening.

4080. The method of claim 4077, further comprising initiating oxidation of the fuel fluid in the heater with a flame.

4081. The method of claim 4077, further comprising removing the oxidized fuel fluid through the conduit.

4082. The method of claim 4077, further comprising removing the oxidized fuel fluid through the conduit and providing the removed oxidized fuel fluid to at least one additional heater disposed in the formation.

09841437-042401

4083. The method of claim 4077, wherein the conduit comprises an insulator disposed on a surface of the conduit, the method further comprising tapering a thickness of the insulator such that heat is allowed to transfer substantially uniformly along a length of the conduit.

4084. The method of claim 4077, wherein the electric heater is an insulated conductor.

4085. The method of claim 4077, wherein the electric heater is a conductor disposed in the conduit.

4086. The method of claim 4077, wherein the electric heater is an elongated conductive member.

4087. The method of claim 4077, wherein the hydrocarbon containing formation comprises a coal containing formation.

4088. The method of claim 4077, wherein the hydrocarbon containing formation comprises an oil shale containing formation.

4089. The method of claim 4077, wherein the hydrocarbon containing formation comprises a heavy oil and/or tar containing permeable formation.

4090. The method of claim 4077, wherein the hydrocarbon containing formation comprises a heavy oil and/or tar containing impermeable formation.

4091. A system configured to heat a hydrocarbon containing formation, comprising:
one or more heat sources disposed within one or more open wellbores in the formation, wherein the one or more heat sources are configured to provide heat to at least a portion of the formation during use; and

wherein the system is configured to allow heat to transfer from the one or more heat sources to a selected section of the formation during use.

4092. The system of claim 4091, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

4093. The system of claim 4091, wherein the one or more heat sources comprise electrical heaters.

4094. The system of claim 4091, wherein the one or more heat sources comprise surface burners.

4095. The system of claim 4091, wherein the one or more heat sources comprise flameless distributed combustors.

4096. The system of claim 4091, wherein the one or more heat sources comprise natural distributed combustors.

4097. The system of claim 4091, wherein the one or more open wellbores comprise a diameter of at least approximately 5 cm.

4098. The system of claim 4091, further comprising an overburden casing coupled to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation.

4099. The system of claim 4091, further comprising an overburden casing coupled to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprises steel.

T04240-04440

4100. The system of claim 4091, further comprising an overburden casing coupled to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

4101. The system of claim 4091, further comprising an overburden casing coupled to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the at least one of the one or more open wellbores.

4102. The system of claim 4091, further comprising an overburden casing coupled to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the at least one of the one or more open wellbores, and wherein the packing material is configured to substantially inhibit a flow of fluid between at least one of the one or more open wellbores and the overburden casing during use.

4103. The system of claim 4091, further comprising an overburden casing coupled to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, wherein a packing material is disposed at a junction of the overburden casing and the at least one of the one or more open wellbores, and wherein the packing material comprises cement.

4104. The system of claim 4091, wherein the system is further configured to transfer heat such that the transferred heat can pyrolyze at least some hydrocarbons in the selected section.

4105. The system of claim 4091, further comprising a valve coupled to at least one of the one or more heat sources configured to control pressure within at least a majority of the selected section of the formation.

4106. The system of claim 4091, further comprising a valve coupled to a production well configured to control a pressure within at least a majority of the selected section of the formation.

5

4107. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least one portion of the
formation, wherein the one or more heat sources are disposed within one or more open
wellbores in the formation;

10

allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and
producing a mixture from the formation.

15

4108. The method of claim 4107, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

20

4109. The method of claim 4107, wherein controlling formation conditions comprises maintaining a temperature within the selected section within a pyrolysis temperature range with a lower pyrolysis temperature of about 250 °C and an upper pyrolysis temperature of about 400 °C.

25

4110. The method of claim 4107, wherein the one or more heat sources comprise electrical heaters.

4111. The method of claim 4107, wherein the one or more heat sources comprise surface burners.

30

4112. The method of claim 4107, wherein the one or more heat sources comprise flameless distributed combustors.

09444360
104240" 2444360

4113. The method of claim 4107, wherein the one or more heat sources comprise natural distributed combustors.

5 4114. The method of claim 4107, wherein the one or more heat sources are suspended within the one or more open wellbores.

10 4115. The method of claim 4107, wherein a tube is disposed in at least one of the one or more open wellbores proximate to heat source, the method further comprising flowing a substantially constant amount of fluid into at least one of the one or more open wellbores through critical flow orifices in the tube.

15 4116. The method of claim 4107, wherein a perforated tube is disposed in at least one of the one or more open wellbores proximate to the heat source, the method further comprising flowing a corrosion inhibiting fluid into at least one of the open wellbores through the perforated tube.

20 4117. The method of claim 4107, further comprising coupling an overburden casing to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation.

25 4118. The method of claim 4107, further comprising coupling an overburden casing to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing comprise steel.

30 4119. The method of claim 4107, further comprising coupling an overburden casing to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, and wherein the overburden casing is further disposed in cement.

4120. The method of claim 4107, further comprising coupling an overburden casing to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, and wherein a packing material is disposed at a junction of the overburden casing and the at least one of the one or more open wellbores.

4121. The method of claim 4107, further comprising coupling an overburden casing to at least one of the one or more open wellbores, wherein the overburden casing is disposed in an overburden of the formation, and wherein the method further comprises inhibiting a flow of fluid between the at least one of the one or more open wellbores and the overburden casing with a packing material.

4122. The method of claim 4107, further comprising heating at least the portion of the formation to substantially pyrolyze at least some of the carbon within the formation.

4123. The method of claim 4107, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

4124. The method of claim 4107, further comprising controlling a pressure with the wellbore.

4125. The method of claim 4107, further comprising controlling a pressure within at least a majority of the selected section of the formation with a valve coupled to at least one of the one or more heat sources.

4126. The method of claim 4107, further comprising controlling a pressure within at least a majority of the selected section of the formation with a valve coupled to a production well located in the formation.

4127. The method of claim 4107, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

4128. The method of claim 4107, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:

heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity(C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

wherein heating energy/day provided to the volume is equal to or less than P_{wr} , wherein P_{wr} is calculated by the equation:

$$P_{wr} = h * V * C_v * \rho_B$$

wherein P_{wr} is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

4129. The method of claim 4107, wherein allowing the heat to transfer from the one or more heat sources to the selected section comprises transferring heat substantially by conduction.

4130. The method of claim 4107, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

4131. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

4132. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

4133. The method of claim 4107, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

4134. The method of claim 4107, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein about 0.1 % by weight to about 15 % by weight of the non-condensable hydrocarbons are olefins.

4135. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

4136. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

4137. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

4138. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

4139. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

09841437-042401

4140. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

5 4141. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

10 4142. The method of claim 4107, wherein the produced mixture comprises condensable hydrocarbons, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

15 4143. The method of claim 4107, wherein the produced mixture comprises a non-condensable component, wherein the non-condensable component comprises hydrogen, and wherein the hydrogen is greater than about 10 % by volume of the non-condensable component and wherein the hydrogen is less than about 80 % by volume of the non-condensable component.

20 4144. The method of claim 4107, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

4145. The method of claim 4107, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

25 4146. The method of claim 4107, further comprising controlling a pressure within at least a majority of the selected section of the formation.

30 4147. The method of claim 4107, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.

09841437-042401

4148. The method of claim 4107, further comprising controlling formation conditions such that the produced mixture comprises a partial pressure of H_2 within the mixture greater than about 0.5 bar.

5 4149. The method of claim 4148, wherein the partial pressure of H_2 is measured when the mixture is at a production well.

4150. The method of claim 4107, wherein controlling formation conditions comprises recirculating a portion of hydrogen from the mixture into the formation.

10 4151. The method of claim 4107, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.

15 4152. The method of claim 4107, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.

20 4153. The method of claim 4107, wherein the produced mixture comprises hydrogen and condensable hydrocarbons, the method further comprising hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

25 4154. The method of claim 4107, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

30 4155. The method of claim 4107, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.

4156. The method of claim 4107, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.

5 4157. The method of claim 4107, wherein producing the mixture comprises producing the mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for the production well.

10 4158. The method of claim 4107, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.

15 4159. The method of claim 4107, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.

20 4160. The method of claim 4107, further comprising separating the produced mixture into a gas stream and a liquid stream.

25 4161. The method of claim 4107, further comprising separating the produced mixture into a gas stream and a liquid stream and separating the liquid stream into an aqueous stream and a non-aqueous stream.

30 4162. The method of claim 4107, wherein the produced mixture comprises H₂S, the method further comprising separating a portion of the H₂S from non-condensable hydrocarbons.

4163. The method of claim 4107, wherein the produced mixture comprises CO₂, the method further comprising separating a portion of the CO₂ from non-condensable hydrocarbons.

5 4164. The method of claim 4107, wherein the mixture is produced from a production well, wherein the heating is controlled such that the mixture can be produced from the formation as a vapor.

10 4165. The method of claim 4107, wherein the mixture is produced from a production well, the method further comprising heating a wellbore of the production well to inhibit condensation of the mixture within the wellbore.

15 4166. The method of claim 4107, wherein the mixture is produced from a production well, wherein a wellbore of the production well comprises a heater element configured to heat the formation adjacent to the wellbore, and further comprising heating the formation with the heater element to produce the mixture, wherein the mixture comprises a large non-condensable hydrocarbon gas component and H₂.

20 4167. The method of claim 4107, wherein the selected section is heated to a minimum pyrolysis temperature of about 270 °C.

25 4168. The method of claim 4107, further comprising maintaining the pressure within the formation above about 2.0 bar absolute to inhibit production of fluids having carbon numbers above 25.

30 4169. The method of claim 4107, further comprising controlling pressure within the formation in a range from about atmospheric pressure to about 100 bar, as measured at a wellhead of a production well, to control an amount of condensable hydrocarbons within the produced mixture, wherein the pressure is reduced to increase production of condensable hydrocarbons, and wherein the pressure is increased to increase production of non-condensable hydrocarbons.

4170. The method of claim 4107, further comprising controlling pressure within the formation in a range from about atmospheric pressure to about 100 bar, as measured at a wellhead of a production well, to control an API gravity of condensable hydrocarbons within the produced mixture, wherein the pressure is reduced to decrease the API gravity, and wherein the pressure is increased to reduce the API gravity.

4171. A mixture produced from a portion of a hydrocarbon containing formation, the mixture comprising:

- an olefin content of less than about 10% by weight; and
- an average carbon number less than about 35.

4172. The mixture of claim 4171, further comprising an average carbon number less than about 30.

4173. The mixture of claim 4171, further comprising an average carbon number less than about 25.

4174. The mixture of claim 4171, further comprising:

- non-condensable hydrocarbons comprising hydrocarbons having carbon numbers of less than 5; and

wherein a weight ratio of the hydrocarbons having carbon numbers from 2 through 4, to methane, in the mixture is greater than approximately 1.

4175. The mixture of claim 4171, further comprising condensable hydrocarbons, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

4176. The mixture of claim 4171, further comprising ammonia, wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

4177. The mixture of claim 4171, further comprising condensable hydrocarbons, wherein an olefin content of the condensable hydrocarbons is greater than about 0.1 % by weight of the condensable hydrocarbons, and wherein the olefin content of the condensable hydrocarbons is less than about 15 % by weight of the condensable hydrocarbons.

4178. The mixture of claim 4171, further comprising condensable hydrocarbons, wherein less than about 15 % by weight of the condensable hydrocarbons have a carbon number greater than about 25.

4179. The condensable hydrocarbons of claim 4178, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

4180. The mixture of claim 4177, further comprising condensable hydrocarbons, wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

4181. The mixture of claim 4171, further comprising:

non-condensable hydrocarbons comprising hydrocarbons having carbon numbers of less than about 5, wherein a weight ratio of the hydrocarbons having carbon number from 2 through 4, to methane, in the mixture is greater than approximately 1;

wherein the non-condensable hydrocarbons further comprise H₂, wherein greater than about 15 % by weight of the non-condensable hydrocarbons comprises H₂; and

condensable hydrocarbons, comprising:

oxygenated hydrocarbons, wherein greater than about 1.5 % by weight of the condensable hydrocarbons comprises oxygenated hydrocarbons; and aromatic compounds, wherein greater than about 20 % by weight of the condensable hydrocarbons comprises aromatic compounds.

5

4182. The mixture of claim 4171, further comprising:
condensable hydrocarbons, wherein less than about 5 % by weight of the condensable hydrocarbons comprises hydrocarbons having a carbon number greater than about 25;

10

wherein the condensable hydrocarbons further comprise:
oxygenated hydrocarbons, wherein greater than about 5 % by weight of the condensable hydrocarbons comprises oxygenated hydrocarbons; and aromatic compounds, wherein greater than about 30 % by weight of the condensable hydrocarbons comprises aromatic compounds; and
non-condensable hydrocarbons comprising H₂, wherein greater than about 15 % by weight of the non-condensable hydrocarbons comprises H₂.

15

4183. The mixture of claim 4171, further comprising a condensable mixture, comprising:

20

olefins, wherein about 0.1 % by weight to about 15 % by weight of the condensable mixture comprises olefins; and
asphaltenes, wherein less than about 0.1 % by weight of the condensable mixture comprises asphaltenes.

25

4184. The condensable mixture of claim 4183, further comprising, oxygenated hydrocarbons, wherein less than about 15 % by weight of the condensable mixture comprises oxygenated hydrocarbons;

30

4185. The mixture of claim 4171, further comprising a condensable mixture, comprising:

olefins, wherein about 0.1 % by weight to about 2 % by weight of the condensable mixture comprises olefins; and

multi-ring aromatics, wherein less than about 2 % by weight of the condensable mixture comprises multi-ring aromatics with more than two rings.

5

4186. The condensable mixture of claim 4184, further comprising oxygenated hydrocarbons, wherein greater than about 25 % by weight of the condensable mixture comprises oxygenated hydrocarbons.

10

4187. The mixture of claim 4171, further comprising:

non-condensable hydrocarbons, wherein the non-condensable hydrocarbons comprise H_2 , wherein greater than about 10 % by weight of the non-condensable hydrocarbons comprises H_2 ;

15

ammonia, wherein greater than about 0.5 % by weight of the mixture comprises ammonia; and

hydrocarbons, wherein a weight ratio of hydrocarbons having greater than about 2 carbon atoms, to methane, is greater than about 0.4.

20

4188. A mixture produced from a portion of a hydrocarbon containing formation, the mixture, comprising:

non-condensable hydrocarbons comprising hydrocarbons having carbon numbers of less than 5; and

25

wherein a weight ratio of the hydrocarbons having carbon numbers from 2 through 4, to methane, in the mixture is greater than approximately 1.

4189. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

30

4190. The mixture of claim 4175, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

4191. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

5

4192. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

10

4193. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

15

4194. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

20

4195. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

25

4196. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

4197. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

30

094447-04401

4198. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise cycloalkanes.

5 4199. The mixture of claim 4175, wherein the non-condensable hydrocarbons further comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable hydrocarbons, and wherein the hydrogen is less than about 80 % by volume of the non-condensable hydrocarbons.

10 4200. The mixture of claim 4175, further comprising ammonia, wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

4201. The mixture of claim 4175, further comprising ammonia, wherein the ammonia is used to produce fertilizer.

15 4202. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein less than about 15 weight % of the condensable hydrocarbons have a carbon number greater than approximately 25.

20 4203. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein the condensable hydrocarbons comprise olefins, and wherein about 0.1 % to about 5 % by weight of the condensable hydrocarbons comprises olefins.

25 4204. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein the condensable hydrocarbons comprises olefins, and wherein about 0.1 % to about 2.5 % by weight of the condensable hydrocarbons comprises olefins.

30 4205. The mixture of claim 4175, further comprising condensable hydrocarbons, wherein the condensable hydrocarbons comprise oxygenated hydrocarbons, and wherein greater than about 5 % by weight of the condensable hydrocarbons comprises oxygenated hydrocarbons.

4206. The mixture of claim 4175, further comprising non-condensable hydrocarbons, wherein the non-condensable hydrocarbons comprise H_2 , and wherein greater than about 5 % by weight of the non-condensable hydrocarbons comprises H_2 .

4207. The mixture of claim 4175, further comprising non-condensable hydrocarbons, wherein the non-condensable hydrocarbons comprise H_2 , and wherein greater than about 15 % by weight of the non-condensable hydrocarbons comprises H_2 .

4208. The mixture of claim 4175, wherein a weight ratio of hydrocarbons having greater than about 2 carbon atoms, to methane, is greater than about 0.3.

4209. A mixture produced from a portion of a hydrocarbon containing formation, the mixture comprising:

non-condensable hydrocarbons comprising hydrocarbons having carbon numbers of less than 5, wherein a weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, is greater than approximately 1; and

condensable hydrocarbons comprising oxygenated hydrocarbons, wherein greater than about 5 % by weight of the condensable component comprises oxygenated hydrocarbons.

4210. The mixture of claim 4209, wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

4211. The mixture of claim 4209, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

4212. The mixture of claim 4209, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

4213. The mixture of claim 4209, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

4214. The mixture of claim 4209, wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

4215. The mixture of claim 4209, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

4216. The mixture of claim 4209, wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

4217. The mixture of claim 4209, wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

4218. The mixture of claim 4209, wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

4219. The mixture of claim 4209, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

4220. The mixture of claim 4209, wherein the non-condensable hydrocarbons comprises hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable hydrocarbons, and wherein the hydrogen is less than about 80 % by volume of the non-condensable hydrocarbons.

4221. The mixture of claim 4209, wherein the produced mixture comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

09841437-04240-2

4222. The mixture of claim 4209, wherein the produced mixture comprises ammonia, and wherein the ammonia is used to produce fertilizer.

5 4223. The mixture of claim 4209, wherein less than about 5 weight % of the condensable hydrocarbons in the mixture have a carbon number greater than approximately 25.

10 4224. The mixture of claim 4209, wherein the condensable hydrocarbons further comprise olefins, and wherein about 0.1 % to about 5 % by weight of the condensable hydrocarbons comprises olefins.

15 4225. The mixture of claim 4209, wherein the condensable hydrocarbons further comprise olefins, and wherein about 0.1 % to about 2.5 % by weight of the condensable hydrocarbons comprises olefins.

4226. The mixture of claim 4209, wherein the non-condensable hydrocarbons further comprise H₂, wherein greater than about 5 % by weight of the mixture comprises H₂.

20 4227. The mixture of claim 4209, wherein the non-condensable hydrocarbons further comprise H₂, wherein greater than about 15 % by weight of the mixture comprises H₂.

4228. The mixture of claim 4209, wherein a weight ratio of hydrocarbons having greater than about 2 carbon atoms, to methane, is greater than about 0.3.

25 4229. A mixture produced from a portion of a hydrocarbon containing formation, the mixture comprising:

non-condensable hydrocarbons comprising hydrocarbons having carbon numbers of less than 5, wherein a weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, is greater than approximately 1;

30 condensable hydrocarbons;

wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons comprises nitrogen;

wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons comprises oxygen; and

5 wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons comprises sulfur.

4230. The mixture of claim 4229, further comprising ammonia, wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

10 4231. The mixture of claim 4229, wherein less than about 5 weight % of the condensable hydrocarbons have a carbon number greater than approximately 25.

4232. The mixture of claim 4229, wherein the condensable hydrocarbons comprise olefins, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

15 4233. The mixture of claim 4229, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

20 4234. The mixture of claim 4229, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

25 4235. The mixture of claim 4229, wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

30 4236. The mixture of claim 4229, wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

4237. The mixture of claim 4229, wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

4238. The mixture of claim 4229, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

4239. The mixture of claim 4229, wherein the non-condensable hydrocarbons comprises hydrogen, and wherein the hydrogen is greater than about 10 % by volume of the non-condensable hydrocarbons and wherein the hydrogen is less than about 80 % by volume of the non-condensable hydrocarbons.

4240. The mixture of claim 4229, further comprising ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

4241. The mixture of claim 4229, further comprising ammonia, and wherein the ammonia is used to produce fertilizer.

4242. The mixture of claim 4229, wherein the condensable hydrocarbons comprises oxygenated hydrocarbons, and wherein greater than about 5 % by weight of the condensable component comprises oxygenated hydrocarbons.

4243. The mixture of claim 4229, wherein the non-condensable hydrocarbons comprise H_2 , and wherein greater than about 5 % by weight of the non-condensable hydrocarbons comprises H_2 .

4244. The mixture of claim 4229, wherein the non-condensable hydrocarbons comprise H_2 , and wherein greater than about 15 % by weight of the mixture comprises H_2 .

4245. The mixture of claim 4229, wherein a weight ratio of hydrocarbons having greater than about 2 carbon atoms, to methane, is greater, than about 0.3.

4246. A mixture produced from a portion of a hydrocarbon containing formation, the mixture comprising:

non-condensable hydrocarbons comprising hydrocarbons having carbon numbers of less than 5, wherein a weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, is greater than approximately 1;

ammonia, wherein greater than about 0.5 % by weight of the mixture comprises ammonia; and

condensable hydrocarbons comprising oxygenated hydrocarbons, wherein greater than about 5 % by weight of the condensable hydrocarbons comprises oxygenated hydrocarbons.

4247. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise olefins, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

4248. The mixture of claim 4246, wherein the non-condensable hydrocarbons further comprise ethene and ethane, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

4249. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise nitrogen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

4250. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise oxygen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

4251. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise sulfur, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

4252. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise oxygen containing compounds, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

4253. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise aromatic compounds, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

4254. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise multi-aromatic rings, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

4255. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise asphaltenes, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

4256. The mixture of claim 4246, wherein the condensable hydrocarbons further comprise cycloalkanes, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

4257. The mixture of claim 4246, wherein the non-condensable hydrocarbons further comprise hydrogen, wherein the hydrogen is greater than about 10 % by volume of the non-condensable hydrocarbons, and wherein the hydrogen is less than about 80 % by volume of the non-condensable hydrocarbons.

4258. The mixture of claim 4246, wherein the produced mixture further comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

4259. The mixture of claim 4246, wherein the produced mixture further comprises ammonia, and wherein the ammonia is used to produce fertilizer.

4260. The mixture of claim 4246, wherein the condensable hydrocarbons comprise hydrocarbons having a carbon number of greater than approximately 25, and wherein less than about 15 weight % of the hydrocarbons in the mixture have a carbon number greater than approximately 25.

4261. The mixture of claim 4246, wherein the non-condensable hydrocarbons further comprise H_2 , and wherein greater than about 5 % by weight of the mixture comprises H_2 .

4262. The mixture of claim 4246, wherein the non-condensable hydrocarbons further comprise H_2 , and wherein greater than about 15 % by weight of the mixture comprises H_2 .

4263. The mixture of claim 4246, wherein the non-condensable hydrocarbons further comprise hydrocarbons having carbon numbers of greater than 2, wherein a weight ratio of hydrocarbons having carbon numbers greater than 2, to methane, is greater than about 0.3.

4264. A mixture produced from a portion of a hydrocarbon containing formation, the mixture comprising:

non-condensable hydrocarbons comprising hydrocarbons having carbon numbers of less than 5, wherein a weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, is greater than approximately 1; and

condensable hydrocarbons comprising olefins, wherein less than about 10 % by weight of the condensable hydrocarbons comprises olefins.

4265. The mixture of claim 4264, wherein the non-condensable hydrocarbons further comprise ethene and ethane, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

FOI b7D b7E b7F b7G b7H b7I b7J b7K b7L b7M b7N b7O b7P b7Q b7R b7S b7T b7U b7V b7W b7X b7Y b7Z

4266. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise nitrogen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

5

4267. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise oxygen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

10

4268. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise sulfur, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

15

4269. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise oxygen containing compounds, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

20

4270. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise aromatic compounds, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

25

4271. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise multi-ring aromatics, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

30

4272. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise asphaltenes, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

4273. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise cycloalkanes, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

5 4274. The mixture of claim 4264, wherein the non-condensable hydrocarbons further comprise hydrogen, and wherein the hydrogen is greater than about 10 % by volume of the non-condensable hydrocarbons and wherein the hydrogen is less than about 80 % by volume of the non-condensable hydrocarbons.

10 4275. The mixture of claim 4264, wherein the produced mixture further comprises ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

15 4276. The mixture of claim 4264, wherein the produced mixture further comprises ammonia, and wherein the ammonia is used to produce fertilizer.

20 4277. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise hydrocarbons having a carbon number of greater than approximately 25, and wherein less than about 15 % by weight of the hydrocarbons have a carbon number greater than approximately 25.

4278. The mixture of claim 4264, wherein about 0.1 % to about 5 % by weight of the condensable component comprises olefins.

25 4279. The mixture of claim 4264, wherein about 0.1% to about 2 % by weight of the condensable component comprises olefins.

30 4280. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise oxygenated hydrocarbons, and wherein greater than about 5 % by weight of the condensable hydrocarbons comprises oxygenated hydrocarbons.

09841437-042401

4281. The mixture of claim 4264, wherein the condensable hydrocarbons further comprise oxygenated hydrocarbons, and wherein greater than about 25 % by weight of the condensable component comprises oxygenated hydrocarbons.

5 4282. The mixture of claim 4264, wherein the non-condensable hydrocarbons further comprise H_2 , and wherein greater than about 5 % by weight of the non-condensable hydrocarbons comprises H_2 .

10 4283. The mixture of claim 4264, wherein the non-condensable hydrocarbons further comprise H_2 , and wherein greater than about 15 % by weight of the non-condensable hydrocarbons comprises H_2 .

15 4284. The mixture of claim 4264, wherein a weight ratio of hydrocarbons having greater than about 2 carbon atoms, to methane, is greater than about 0.3.

4285. A mixture produced from a portion of a hydrocarbon containing formation, comprising:

condensable hydrocarbons, wherein less than about 15 weight % of the condensable hydrocarbons have a carbon number greater than 25; and

20 wherein the condensable hydrocarbons comprise oxygenated hydrocarbons, and wherein greater than about 5 % by weight of the condensable hydrocarbons comprises oxygenated hydrocarbons.

25 4286. The mixture of claim 4285, further comprising non-condensable hydrocarbons, wherein the non-condensable hydrocarbons comprise hydrocarbons having carbon numbers of less than 5, and wherein a weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, is greater than approximately 1.

30 4287. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise olefins, and wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

4288. The mixture of claim 4285, further comprising non-condensable hydrocarbons, wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

4289. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise nitrogen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

4290. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise oxygen, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

4291. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise sulfur, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

4292. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise oxygen containing compounds, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

4293. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise aromatic compounds, and wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

4294. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise multi-ring aromatics, and wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-ring aromatics with more than two rings.

09041437-0440-0000

4295. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise asphaltenes, and wherein less than about 0.3 % by weight of the condensable hydrocarbons are asphaltenes.

5 4296. The mixture of claim 4285, wherein the condensable hydrocarbons further comprise cycloalkanes, and wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons are cycloalkanes.

10 4297. The mixture of claim 4285, further comprising non-condensable hydrocarbons, wherein the non-condensable hydrocarbons comprise hydrogen, and wherein the hydrogen is greater than about 10 % by volume of the non-condensable hydrocarbons and wherein the hydrogen is less than about 80 % by volume of the non-condensable hydrocarbons.

15 4298. The mixture of claim 4285, further comprising ammonia, and wherein greater than about 0.05 % by weight of the produced mixture is ammonia.

20 4299. The mixture of claim 4285, further comprising ammonia, and wherein the ammonia is used to produce fertilizer.

4300. The mixture of claim 4285, wherein the condensable hydrocarbons further comprises olefins, and wherein less than about 10 % by weight of the condensable hydrocarbons comprises olefins.

25 4301. The mixture of claim 4285, wherein the condensable hydrocarbons further comprises olefins, and wherein about 0.1 % to about 5 % by weight of the condensable hydrocarbons comprises olefins.

30 4302. The mixture of claim 4285, wherein the condensable hydrocarbons further comprises olefins, and wherein about 0.1 % to about 2 % by weight of the condensable hydrocarbons comprises olefins.